MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: jdwater@mpcb.gov.in

Kalpataru Point, 2nd - 4th FI.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

Red/LSI

Consent No.MPCB/JD(WPC)/RO ABD/EIC NO AD-6481-10/R/CC-CA C-\54 Date: \6/01/2012

Consent to **Operate** under Section **26** of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008 [To be referred as Water Act. Air Act and HW(M,H & T) Rules respectively].

MAHARASHTRA

CONSENT is hereby granted to

M/s Bhaurao ChavanS.S.K. Ltd. (Distillary Division) A/p Laxmi Nagar, Tq. Ardhapur, Dist. Nanded,

located in the area declared under the provisions of the Water Act, Air act and Authorisation under the provisions of (M,H & T) Rules subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period upto 31.12.2012
- 2. The consent is valid for the manufacture of -

| Sr. No. | Product | Maximum Quantity | | |
|----------------------------|----------------------|------------------|--|--|
| 1 | Recitified Spirit | 27KL/Day | | |
| 2 | Absolute alchol | 30KL/day | | |
| 3 | Extra Neutal alcohol | 18KL/Day | | |
| 4 | Impure Spirit | 3KI/Day | | |
| 5 | Technical Alcohol | 2KL/Day | | |
| 6 | Fusel oil | 62.5Ltr/Day | | |
| Total not exceeding 30KLPD | | | | |
| 7 | Compost | 2338.5MT/M | | |

(The Distillery shall remain closed during Rainy Season i.e from 10th june to 10th September Ever Year)

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 334M³ (Including 94 CMD of effluent from cooling tower).
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 2.50 M³.
- (ii) Trade Effluent:

<u>Treatment</u>: The applicant shall provide comprehensive treatment consists of biomethanisation / reboiler as primary followed by well designed aerobic composting. The arrangement shall be leaked proof and no effluent or leakage/seepages shall find its way into environment thereby causing pollution of surface/ground/generated water.

A)Condition for Aerobic Composting are as below:-

1] The spent wash should be stored in impervious tanks. The spent wash tanks should have proper lining with HDPE and should be kept in proper condition to prevent ground

water pollution. As per the CPCB recommendation and undertaking given by the company, storage should not exceed 30 days capacity.

- 2] Application shall ensure availability of adequate filler material such as press mud, bagasses, agricultural, biological waste as required for effective composting system.
- 3] Composting material should meet the following specifications:

| Moisture | 30 to 35% |
|------------|---------------|
| Carbon | Below 17 |
| Nitrogen | 1.5 to 2% |
| Phosphorus | 1.5 to 2% |
| Potassium | 3.0 to 4% |
| | |

4] The compost leachet (1 gram of compost mixed with 100 ml of water distilled water and filtered) / filtrate shall confirm to the following limit:-

| pН | Not to exceed | 7.5 to 8.0 |
|--------|---------------|------------|
| B.O.D. | Not to exceed | 30 mg/l |

- 5] A pucca leak proof guard pound of sufficient holding capacity should be provided to cope up with the effluent discharge during short term process disturbances/monsoon. In case of prolonged disturbance in effluent treatment and disposal system, the contributing units shall be shut sown and shall not be restarted without rectifying the system.
- 6] The composting site/pits shall be made leak proof by proper lining. A catch drain shall be provided round the composting site to collect, leachates/runoff and safe shall be recycled into the storage pond for application on compost depots. Arrangements for overturning of compost material in pits/windrows and spraying of spent wash shall be made to ensure appropriate aeration and uniform distribustion of spent wash.
- 7] In case of composting in open fields, the application of spent wash shall stop by end of April, so that compost is ready and the site is cleared if the composted manure before onset of monsoon. The composted manure shall be collected and stored on a raised platform with suitable rain cover so that the compost manure is not washed away by rain/runoff.
- 8] Characteristics of the soil, ground water and effect on crop yield should be monitored in the area where compost is used as manure and results thereof shall be compiled and reported in the Environment Statement to be submitted every year.
- 9] The test wells shall be provided around the compost site for ground water monitoring. The well water quality has to be maintained at 2006 level.
- 10] Top pullover impervious sheets shall be provided for entire compost yard, press mud and compost storage so as to cover the same during untimely rains and idle period.
- 11] The operation of distillery should be restricted to 270 days in year and that it will not operate during rainy season.
- (v) **Sewage Effluent Treatment**: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
 - (1) Suspended Solids Not to exceed 100 mg/l.
 (2) BOD 3 days 27 Deg. C. Not to exceed 100 mg/l.
- (vi) **Sewage Effluent Disposal**: The treated effluent shall be connected to soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening only.
- (vii) Non-Hazardous Solid Waste:

| Sr No | Type of Waste | Quantity | Disposal |
|----------|----------------------|-------------|----------------|
| 1 | By composting sludge | 2000Mt/Year | Used as manure |

(viii) Other Conditions:

1. The industry shall monitor effluent quality regularly.

4. CONDITIONS FOR MOLASSES STORAGE:-

- i] The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutcha pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, non-lifting of molasses etc.
- All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorised officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- v] The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near the tank.
- vi] The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Torage and Supply Regulation, 1965".
- 4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under :

The daily water consumption for the following categories is as under:

| (i) Domestic | ••• | 3.0 CMD |
|----------------------------|-----|---------|
| (ii) Industrial Processing | | 248 CMD |
| (iii) Industrial Cooling | | 309 CMD |
| (iv) Agriculture/Gardening | ••• | CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the fcllowing standards:

Standards for Emissions of Air Pollutants:

| (i) | SPM | Not to exceed | 100 | mg/Nm3. |
|------|-----|---------------|-----|---------|
| (ii) | So2 | Not to exceed | 150 | Kg/day |

- A) Control Equipment: The pollution control equipments of adequate capacity shall be provided to limit the dust and air emission.
- (ii) The applicant shall observe the following fuel pattern :-

| , | Sr.No. | Type of Fuel | | Quantity |
|----|-----------------|-------------------------|---------------------|-------------------|
| | 1 | Bagasse | | 150Mt/Day |
| i) | The applicant s | hall erect the chimney(| s) of the following | specifications :- |

(iii) The applicant shall erect the chimney(s) of the following specifications:-Sr.No. Chimney attached to Height in Mtrs.

Boiler 3

2. D.G.Set 500KVA 05 meters above roof in which it is installed.

- (iv) The applicant shall provide ports in the chimney/(s) and facilitates such as ladder, platform etc. For monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.
- (v) The industry shall take adequate measures for control for noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. And 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(Vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

6. CONDITIONS UNDER HW(M,H & TM) RULES, 2008.

The applicant shall handle hazardous wastes as specified below:

NO Haz waste is generated.

7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. General Conditions:

- (i) The applicant should bring minimum 33% of the available open land under green coverage/ plantation. The applicant should submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant should provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant should stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels
- (iii) The applicant should make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant should not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm should submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- (v) The applicant should install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment should be maintained. The applicant should also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- (vi) Separate drainage system should be provided for collection of trade and sewage effluents. Terminal manholes should be provided at the end of collection system with arrangement for measuring the flow. No effluent should be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent should find its way other than in designed and provided collection

- system. Neither storm water nor discharge from other premises should be allowed to mix with the effluents from the factory.
- (vii) The applicant should provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and should pay to the Board for the services rendered in this behalf. An inspection book should be opened and made available to the Board's officers during their visit to the applicant.
- (v ii) The industry should ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant should maintain good house keeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
 - 9. Industry shall make provisions for Piezometric wells for water quality monitoring.
 - 10. Industry shall make provisions for temperature recording and monitoring system to Aero tiller machines.
 - 11. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
 - 12. Industry shall submit Bank Guarantee of Rs 2.0 lakhs towards Compliance of CREP Guidelines within 15 days at Regional Office Aurangabad..
 - 13. This consent is issued pursuant to the decision of Consent Appraisal committee meeting of Board held on 10/01/2012.
 - 14. The capital investment of the industry is Rs. 15.16 Crore.

For and on Behalf of the Maharashtra Pollution Control Board,

(Milind Mhaiskat) Member Secretary

To, M/s Bhaurao ChavanS.S.K. Ltd. (Distillary Division) A/p Laxmi Nagar, Tq. Ardhapur, Dist. Nanded,

Copy to:

RO-Aurangabad /SRO- Nanded:- They are directed to collect the Bank Guarantee of Rs 2.0 Lakhs from industry and ensure compliance of consent conditions.

CAO / Cess Branch / Master File

Received Consent fee of -

| · | a donochi lee oi | | | | |
|---|------------------|----------|------------|----------------|--|
| | Amount | D.D. No. | Date | Bank | |
| | 1,00000/- | 001700 | 03.12.2010 | Bank of India. | |