MAHARASHATRA POLLUTION CONTROL BOARD

Phone :

022-24020781,24014701

Fax

022-24023516,24093814



Kalpataru Point, 2nd - 4th Floor Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Email

idwater@mpcb.gov.in

Visit At :

http://mpcb.gov.in

Red/L.S.I

CAC-204 20/01/2012

Consent No.BO/JD (WPC)/RO ABAD/ EIC-AD-8281-11/O/CC-

Date: /01/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

Nath Pulp And Paper Mills Ltd Nathnagar, Wahegaon, Tq Paithan Paithan 431148

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate $\,$ is granted for a period up to:31/12/2012.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Kraft Paper	2400	Ton/M
2	Writing printing paper	1200	Ton/M
3	Coated paper	800	Ton/M
4	Electrcity (Cogeneration)	3.5	Million KWH/Month

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 5778.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed $10.00M^3$.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

	following standards:			
1	На	Between	5.5 to 9.0	
0	Suspended Solids	Not to exceed	100	mg/l.
2		Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.		250	mg/l.
4	COD	Not to exceed		1115/11

5	Oil & Grease	Not to exceed	10	mg/l.
C	T.D.S.	Not to exceed	2100	mg/l
0		Not to exceed	600	mg/l.
1	Chlorides	Not to exceed	1000	mg/l.
8	Sulphates	TVOU US CARCOCA	1 11	de commundonci

(iv) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids Not to exceed 100 mg/l. (2) BOD 3 days 270 C. Not to exceed 100 mg/l.

(vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be discharged into sewerage system provided by MIDC.

(vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Waste	Quantity	UOM	Disposal
1	Fibrous Wast	2.10	MT/Day	Sale to Board Mill
9	Sweepage	0.50	MT/Day	Reused
3	Coal Ash	120.00	MT/Day	Sale to Brick Mfg.

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose ... 20.00 CMD

(ii) Water gets Polluted & 6300.00 CMD

Pollutants are Biodegradable ... 6300.00 CM

(iii) Water gets Polluted, Pollutants
are not Biodegradable & Toxic ... 0.00 CMD

(iv) Industrial Cooling, spraying in mine pits or boiler feed ... 0.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Multi cyclone dust collection system of adequate capacity provided to all the boilers should be operated and maintained properly.

b) Standards for Stack Emissions:

1) SPM Not to exceed 150 mg/Nm3
2) So2 Not to exceed 350MT/day

(ii) The applicant shall observe the following fuel pattern:-

C. No	Type Of Fuel	Quantity	UOM
Sr. No.	Type of Fact	050.00	MT /day
1	l Coal	350.00	IVI I ruay
1 1			

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Chimney Attached To	Height in Mtrs.
	46.50
	24.00
	25.00
	46.00
	Boiler FBC (30 TPH) Boiler LIPI-I (10 TPH) Boiler LIPI-II (12.50 TPH) soda recovery Boiler

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
 - d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
 - e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG

manufacturer which would help to prevent noise levels of DG set from deteriorating with use

g. D.G. Set shall be operated only in case of power failure

h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below.

Disposal **UOM** Type Of Waste Quantity Sr. No.

Treatment: - NIL (ii)

The authorization is hereby granted to operate a facility for collection, 1. storage, transport & disposal of hazardous waste.

The industry should comply with the Hazardous Waste (M&H) Rules, 2.

2003.

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 8. Industry shall comply with following additional conditions:
- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

ii. The applicant shall bring minimum 33% of the available open land under green

coverage/ tree plantation.

iii. Solid waste - The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the

Board.

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in

the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

ix. As inspection book shall be opened and made available to the Board's officers

during their visit to the applicant.

x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

xii. Neither storm water nor discharge from other premises shall be allowed to

mix with the effluents from the factory.

9. Industry shall submit Bank Guarantee of Rs 5.0 lakhs for recycling the treated effluent in the process so as to achieve ZERO DISCHARGE by 31.05.2012. The Bank guarantees shall be submitted within 15 days at Regional Office Aurangabad.

10. The consent is issued pursuant to the recommendations of Consent Appraisal Committee meeting of Board held on 10/01/2012.

11. The Capital investment of the industry is Rs. 15827 Lacs.

(Milind Mhaiskar) Member Secretary

To, M/s Nath Pulp And Paper Mills Ltd Nathnagar , Wahegaon , Tq Paithan

Paithan -431148

Copy to :- RO Aurangabad/SRO Aurangabad-I :- They are directed to obtain Bank Guarantee from industry & ensure compliance of consent conditions. Submit the compliance report of Zero discharge on monthly basis

CAO/Cess wing/Master file.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	158110	028932	31 Dec 2010	Axis Bank
2	3000	030410	07 Apr 2011	Axis Bank
3	158110	030367	25 Jan 2011	Axis Bank
4	158110	14925	31 Mar 2011	Axis Bank
4	3312	030446	11 Apr 2011	Axis Bank
5	3,70,146/-	021268	16 Jan 2012	ICICI Bank
6	3,70,140/-	021200	10 3412 = 1	