MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023515 Website: http://mpcb.gov.in E-mail: pci2@mpcb.gov.in



Kalpataru Point, 2nd - 4th Floor Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Red/LSI

Consent No .BO/ RO Kolhapur/ PCI-I/ EIC- KP-7768-11/ CC-156 Date: 23/01/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry), Rules 2008 [To be referred as Water Act, Air Act and HW(M&H) Rules respectively]

CONSENT is hereby granted to,

M/s Shreyas Intermediates Ltd, Plot No. D-21, MIDC Lote Parshuram Tal. Khed, Dist. Ratnagiri - 415722.

Water Act, Air act and located in the area declared under the provisions of the Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to operate is granted for a period up to- 31/12/2012. 1.

2. The Consent is valid for the manufacture of -Sr.No. Product Maximum Quantity CPC crude Blue 1. 1000.0 MT/M 2. Pigment Blue 300.0 MT/M **By-Products** Ammoniùm Sulphate 1. 1000.0 MT/M 2. Ammonium Bicarbonate 1000.0 MT/M. 3. Galcium Carbonate 1000.0 MT/M.

CONDITIONS UNDER WATER ACT: 3.

The daily quantity of trade effluent from the factory shall not exceed 110. m³. (i)

The daily quantity of sewage effluent from the factory shall not exceed 10.0 m³. (ii) Trade Effluent :

Treatment : The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards :

1)	pH	Between	6.0 to 8.5
2)	Suspended Solids	Not to exceed	100 mg/l.
3)	BOD 3days 27 Deg. C.	Not to exceed	100 mg/l.
4)	COD	Not to exceed	250 mg/l.
5)	Oil & Grease	Not to exceed	10 mg/l.
6)	Copper	Not to exceed	3.0 mg/l.
7)	Mercury (as Hg)	Not to exceed	0.01 mg/l.
8)	Chromium (as Cr ⁶⁺)	Not to exceed	0.1 mg/l.

SRO Chiplun/Ind/Red/L.S.I/01039296

Page 1 of 5

	9)		ot to exceed	d 2.0 mg/l.	
	10)	Copper (as Cu) Not to ex	ceed	3.0	mg/l.
	11)	Zinc (as Zn) Not to ex	ceed	5.0	mg/l.
	12)	Nickel (as Ni) Not to ex	ceed	3.0	mg/l.
	13)	Lead (as Pb) Not to ex	ceed	0.1	mg/l.
	14)	Manganese (as Mn) Not to ex	ceed	2.0	mg/l.
	15)	Cadmium (as Cd) Not to ex	ceed	2.0	mg/l.
	16)	Chloride (as Cl) Not to ex	ceed	1000	mg/l.
	17)	Sulphate (as SO ₄) Not to ex		1000	mg/l.
	18)	Phenolic Compounds (as C ₆ H ₅ OH) No			mg/l.
	19)	The bioassay test on fish show 90% su in 100 % effluent.			~~~ <u>,</u> ,,,,
		m 100 % emident.		A.	
(iv)	Trad	e Effluent Disposal : The treated tra	de effluent	shall be recve	led to
. ,	the m	aximum extent & remaining connected	to CETP I	ote through	ewerage
		m provided by MIDC.		- AN	Jonorago
			Å	~ 00	
(v)	Sewa	ge Effluent Treatment : The applic	ant chall r	voule compr	ohonsivo
	treat	nent system as is warranted with re	oference to	influent que	lity and
		te and maintain the same continuous			
	troat	ed effluent to the following standards:	y su as w	acmeve the y	luanty or
	UL CA U	(1) Suspended Solids Not to ex		100 mg/l.	
		(1) Buspended Sonds Not to ex (2) BOD 3 days 27° C. Not to ex		Ģ	
(vi)	Somo				ı. ı
(*1)		ge Effluent Disposal : The treated s	ewage emi	uent snall be	aisposed
(vii)		d for gardening only.			
(011)		Hazardous Solid Waste:	ал <i>с</i>	·	,
		of Waste Quantity	<u>Treatmer</u>		
		S. scrap 1.0 T/m.		By Sa	
		ste Plastic Bags 2.0 1/m.		By Sa	
	3. Bo	ler ash		By sa	le
(viii)	Othe	r conditions :			
	1] TI	e industry shall monitor effluent qualit	ty regularly	7.	
The a	applica	at shall comply with the provisions	of the Wa	ter (Preve	ntion &
Cont	rol of	nt shall comply with the provisions Pollution) Cess Act, 1977 (tc be r	eferred as	Cess Act) as	nd Rules
there	under:			,	
	~**	ter consumption for the following categ	ories is as	under:	
		amption		Quantity	
	Dom			12.5 CMD	
	Indu		gradable	110 CMD	
X 2#	SI	e water	DIGINAL		
					-
2		trial Proceeding generating Non Diade	madabla		
3	Indu	strial Processing generating Non-Biode	gradable	CMD	
3 🔊	Indus waste	e water	gradable		
3 3	Indus waste Indu	e water strial Cooling/Bciler	egradable	320 CMD	
3 4 5	Indus waste Indu Othe	e water		320 CMD 10CMD	

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

SRO Chiplun/Ind/Red/L.S.I/01039296

4.

Page 2 of 5

A)Control Equipment:

- 1. Dust collector of sufficient capacity shall be provided .
- 2. Scrubber of sufficient capacity shall be provided to the reactor to scrub the ammonia fumes, Process emissions.
- 3. Stacks provided to the Boiler & D.G. Set.

B) Conditions for D.G. Set :-

- Noise from the D.G. Set should be controlled by providing an acoustic 1] enclosure or by treating the room acoustically.
- 2] Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insection loss of 25 dB(A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 metres from acoustic enclosure/room and then average.
- The industry shall take adequate measures for control of noise levels 3] from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- Industry should make efforts to bring down noise level due to DG set. 4] outside industrial premises, within ambient noise requirements by proper siting and control measures.
- Installation of DG Set much be strictly in compliance with recommendations 5] of DG Set manufacturer.
- A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would 6] help to prevent noise levels of DG set from deteriorating with use.
- D.G. Set shall be operated only in case of power failure. 7]
- 81 The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

C) Standards for Emissions of Air Pollutants :

(i) SPM/TPM	Not to exceed	150 mg/Nm ³
(ii) <u>S</u> O ₂	Not to exceed	137.0 Kg/Day.
(iii) SO2 process	Not to exceed	50.0 PPM
(ivi) Ammonia	Not to exceed	3.0 PPM
M Acid Mist	Not to exceed	35.0 mg/Nm ³

The applicant shall observe the following fuel pattern:-

<u>Sr.No.</u>	<u>Type of Fuel</u>
1.	Baggase Briquette
2.	Furness Oil

Quantity 34.32 T/Day 200 Lits/Day

(iii) The applicant shall erect the chimney(s) of the following specifications:-

<u>Sr.No.</u>	<u>Chimney attached to</u>	<u>Height in Mtrs.</u>
1.	Boiler 1 & 2	30.0 mtrs.
2.	Thermopack No. 1 & 2	26.0
3.	Scrubber (2 nos)	15.0
4.	D.G.Set (1400 KVA)	5.0 (above the crest)

The applicant shall provide ports in the chimney/(s) and facilities such as (iv) ladder, platform etc. for monitoring the air emissions and the same shall be Page 3 of 5

SRO Chiplun/Ind/Red/L.S.I/01039296

open for inspection to and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.

- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) **Other Conditions**:
 - 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality regularly.
 - 3) The industry should comply with Bombay Smoke Nuisance Act, 1912.

6. CONDITIONS UNDER HW (M&H) RULES, 1989 & AMENDMENT RULES:

Sr.	Item No. as	Type of Waste	Quantity	Disposal
No	per Sch-I			B
1.	26.2	Chemical Sludge From ETP	500 Kg/Day	CHWTSDF TTC
2.	26.3	Dust from Air filtration System	10 Kg/Day	CHWTSDF TTC

(i) The applicant shall handle hazardous wastes as specified below

7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. General conditions.

- (i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.

SRO Chiplun/Ind/Red/L.S.I/01039296

Page 4 of 5

(v) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.

(vi) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down-stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- (vii) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- available to the Board's officers during their visit to the applicant.
 (viii) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant shall maintain good house keeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- 09. If CETP dose not work for achieving standards & problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- 10. The consent should not be construed as any exemption from obtaining necessary NOC from other Govi, agencies as may deemed fit necessary.
- 11. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
- 12. This Consent is issued pursuant to the decision of 18th CC meeting held on 12.01.2012 of the Boards
- 13. The capital investment for expansion is ₹ 45.00 Crore.

(Milind Mhaiskar, IAS) Member Secretary

To, Ma

M/s Shreyas Intermediates Ltd, Plot No. D-21, MIDC Lote Parshuram,

Tal. Khed, Dist. Ratnagiri - 415722.

Copy to:

1) Regional Officer, MPCB, Kolhapur / Sub-Regional Officer, MPCB, Chiplun.

2) Chief Accounts Officer,	MPCB, Mumbai	3) Cess Bra	nch, MPCB.4]	Master file.
Received Consent fee of	– <u>Amount</u>	<u>D.D.No.</u>	Date	<u>Drawn on</u>
R	s. 2,60,100/-	901403	16/06/2011	Bank of Baroda

SRO Chiplun/Ind/Red/L.S.I/01039296

Page 5 of 5