MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

MAHARASHTRA

Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

Red/L.S.I

E-mail: mpcb@vsnl.net

CAC-300

Consent No: BO/JD(APC)/ EICNo.KN-5290-11/E/CC-

Date: 17/02/12

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. JSW STEEL LTD SHAHAPUR, VASHIND

S.NO. 176, 180/1, 180/2, 180/3, 180/4, 180/5, 6,7,8,9 AND 10, 183/2, 183/3, 184/1-P, 184/12-P, 184/11, 184/12, 179/1/1, 179/1/2, 184/13, 184/16,271, 272, 273, 274, 272-P, VILL. VASHIND, TAL. SHAHAPUR

Thane, Maharashtra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Establish is granted for a period up to commissioning of the unit OR 5 years whichever is earlier.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Colour Coated Coils/ Profile sheets	18750	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 110.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall be Nil.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Inter-1

1	pН	Between	5.5 to 9.0
2	Oil & Grease	Not to exceed	10 mg/l
3	Suspended Solids	Not to exceed	100 mg/l.
4	BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
5	COD	Not to exceed	250 mg/l.
6	TDS	Not to exceed	2100 mg/l.
7	Sulphates	Not to exceed	1000 mg/l.
8	Chlorides	Not to exceed	600 mg/l
9	Zinc (as Zn)	Not to exceed	5.0 mg/l
10	Total metal	Not to exceed	10.0 mg/l.

- (iv) Trade Effluent Disposal: The treated effluent shall be recycled /reused. There shall not be any discharge outside the factory premises
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed		mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	1	15000	T/Year		Sale
2	Packing Scrap	300	T/Year		Sale
3	Polythene laminat	tion			baic
	Waste	300	Kg/Year		Sale
(viii)Otl	ier C <mark>onditions:</mark> In	dustry shoul	d monitor eff	luent quality reg	rularly

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

	water combamption for	the tone	owing categories is as uno
(i)	Domestic purpose		0.00 CMD
(ii)	Water gets Polluted &		
	Pollutants are Biodegradable	e	190.00 CMD
(iii)	Water gets Polluted, Pollutar	nts	
	are not Biodegradable & Tox	ic	0.00 CMD
(iv)	Industrial Cooling, spraying		
	in mine pits or boiler feed		96.00CMD
TL	1 11		5 5.00 011115

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

Sont 8-2

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:


- Adequate fume extraction system followed by dust collector of sufficient capacity shall be provided at all dust generating locations and operated properly.
- II. Industry shall provide adequate air pollution controlling system to colour coating section to control air emissions.
- III. There shall not be any secondary (fugitive) emissions.
- IV. Fumes from CCL painting activity shall be incinerated in Regenerative Thermal Oxidiser.

b. Standards for Emissions of Air Pollutants:

WINII	Emissions of All 1 offulailts:				
(i) SPM/TPM (ii) Acid Mist (iii) SO ₂	Not to exceed Not to exceed Not to exceed	150 mg/Nm3 35 mg/Nm3 6.0 Kg/day			

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set



(i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM	
1	Re-Gasified LNG	78.00	MT/D	

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Incinerators (2 Nos)	20.00

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.		Type Of Wast	e Quantity	UOM	Disposal
	S.N	Item No. of process generating HW as per Schedule-I	Type of waste	Maximum Quantity	Disposal
	1	5.1	Used/Spent oil	600 kg/Year	Sale to authorized recyclers.
	2	33.3	Discarded Containers	6000 Nos/M	Sale to authorized
	3	21.1	Paint residue/sludge	300 Kg/Year	vendors/recycler CHWTSDF

Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

Sontar 4

a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- ix. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants

Sotze 5

and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 10. This is issued with the approval of Consent Appraisal Committee of the Board in its meeting held on 23/01/2011.
- 11. The Capital investment of the industry is Rs. 90/- Crs(for expansion) + Rs.779.44/- Crs (existing plant), the total is Rs. 869.44 Cr.
- 12. Industry shall confirm certification from IIT Mumbai regarding the no increase in pollution load. The consent to operate will not be granted without obtaining certificate from IIT Mumbai.

13. This is issued as per the office note dated 02.02.2012 approved by the Hon'ble chairman of the Board.

For and On Behalf of the Maharashtra Pollution Control Board,

(V.M.Motghare)

Joint Director (Air Pollution Control)

15/2/12

To,

M/s. JSW STEEL LTD SHAHAPUR, VASHIND

S.NO. 176, 180/1, 180/2, 180/3, 180/4, 180/5,6,7,8,9 AND 10, 183/2, 183/3, 184/1-P, 184/12-P, 184/11, 184/12, 179/1/1, 179/1/2, 184/13, 184/16,271, 272, 273, 274, 272-P, VILL. VASHIND, TAL. SHAHAPUR

Copy to:

- a. RO-/SRO-They are directed to ensure the compliance of consent conditions.
- b. CAO/Cess Branch/Master File

Received Consent fee of-

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs.75,100/-	703827	23/05/2011	Sangli Bank Ltd
2	Rs.50,000/-	708038	08/11/2011	State Bank of India
2	Rs.18,34,254/-	708968	28/12/2011	State Bank of India

* Consent Fees received as per revised consent fee GR of Env Deptt, GoM, dated 25.8.2011.