MAHARASHATRA POLLUTION CONTROL BOARD

Phone: 022-24020781,24014701

Fax

022-24023516,24093814



Kalpataru Point, 2nd - 4th Floor Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Email:

jdwater@mpcb.gov.in

Visit At :

http://mpcb.gov.in

Red/L.S.I

CAC-358

Date 28/03/2012 Consent No.BO/JD (WPC)/RO NG/EICNO NG6688-12/O/CC-

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M,H) TM) Rules respectively].

CONSENT is hereby granted to

M/s Dinshaws Dairy Foods Limited K-41/42, MIDC Butibori Dist. Nagpur

Nagpur, Maharastra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M,H& TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31/12/2012.

2. The Consent is valid for the manufacture of -

Si	r. Product Name	Maximum	UOM
No.		Quantity	
1	Ice cream & Froze	n 2500000	Ltr/M
	desert		
2	skimmed milk powder	450	Ton/M
3	Milk Products	1355	Ton/M
4	Milk	7242	Ton/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 667.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 50.00M3.
- (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	100	mg/l.
4	COD	Not to exceed	250	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	T.D.S.	Not to exceed	2100	mg/l.
7	Chlorides	Not to exceed	600	mg/l.
8	Sulphates	Not to exceed	1000	mg/l.

- (iv) Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be sent to CETP for disposal as Hydraulic load. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids

Not to exceed

100 mg/l.

(2) BOD 3 days 270 C.

Not to exceed

100 mg/l.

Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be disposed on land for gardening.

(vi) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quanti	1 UOM	Disposal
1	plastic & paper pack material	1.80	MT/M	Reuse/sale to reprocessor
2	Dried sludge from waste water treatment	10.50	MT/M	use as a manure
3	Coal Ash	300.00	MT/M	By sale to bricks mfg.
4	Fat Scum	2.00	MT/M	By sale to soap mfg.

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

70.00 CMD

(ii) Water gets Polluted &

Pollutants are Biodegradable

653.00 CMD

(iii) Water gets Polluted, Pollutants

are not Biodegradable & Toxic ... 0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed ... 267.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Dust collector of sufficient capacity shall be provided to the source of particulate matter emission section to limit the following standard.

b) Standards for Stack Emissions:

1) SPM

Not to exceed

150 mg/Nm3

2) SO2

Not to exceed

600 kg/day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Coal	30.00	MT/Day
2	Furnace Oil	2.00	KL/Day
3	HSD	175.00	MT /Day

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Coal fired Boilers 1&2	35.00
2	Oil Fired Boilers 1 &2	35.00

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as \$-1. S-2, etc. and these shall be painted/displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of finsertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste Quantity UOM Disposal

(ii) Treatment: -

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air

- pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- 9. The consent is issued in super session to earlier Consent issued by Board Consent No.BO/JD (WPC)/RO NG/EICNO NG6153-11/0/CC-CAC311 Date:21/02/2012
- 10. The consent is issued pursuant to the decision of Consent Appraisal Committee meeting of Board held on 20/03/2012.
- 11. The Capital investment of the industry is Rs. 10887 Lacs.

(Milind Mhaiskar)

Member Secretary

To, M/s Dinshaws Dairy Foods Limited K-41/42, MIDC Butibori Dist. Nagpur Nagpur, Maharastra

Copy to :- RO Nagpur/SRO Nagpur-II :- They are directed to ensure compliance of consent conditions. CAO/Cess wing/Master file.

Received Consent fee of

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	258030	520506	13 Dec 2011	Union Bank of India
2	100000	219368	13 Dec 2011	Union Bank of India