MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 0231-2652952 /2660448

0231-2652952

Email: rokolhapur@mpcb.gov.in

Visit At : http://mpcb.gov.in

Kolhapur - 416003



Date: 06.03,2012

Udyog Bhawan Near Collector Office,

Red/S.S.I

Consent No: MPCB/RO/KOP/\088/12.

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

Jubilee Synthetics Pvt. Ltd. S. No-21/6, A, MIDC Kupwad, Tal Miraj Dist. Sangli,

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H). Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1.The Consent to Operate is granted for a period up to commissioning of the unit or five years whichever is earlier.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM	
1	Sizing of Yarn	1400000	Mtrs/M	

3. CONDITIONS UNDER WATER ACT:

(i) The weekly quantity of trade effluent from the factory shall not exceed 3.00M³.
 (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.50M³.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Page 1 of 5

This Consent is Processed through IMIS Application Software. Copyright MPC

DVright MPC

1	На	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	100	mg/l.
4	COD	Not to exceed	250	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	Detergent	Not to exceed	2	mg/l.
7	TAN	Not to exceed	50	mg/l.
8	Chlorides	Not to exceed	600	mg/l.
9	Sulphates	Not to exceed	1000	mg/l.
10	Total Dissolved Solids	Not to exceed	2100	mg/l.

- (iv) Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be discharged in to drainage system provided by MIDC. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solids Not to exceed 100 mg/l.
(2) BOD 3 days 270 C. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be discharged into sewerage system provided by MIDC.
- (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Waste	Quantity	UOM	Treatment	Disposal
-		-	_	-	-

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

 (i) Domestic
 ...
 1.00 CMD

 (ii) Industrial Processing
 ...
 3.00 CMD

 (iii) Industrial Cooling
 ...
 0.00 CMD

 (iv) Agriculture / Gardening
 ...
 0.00 CMD

The applicant shall regularly submit to the Board the returns of consumption in the prescribed form and pay the Cess as specified Section 3 of the said Act.

Consent is Processed through IMIS Application Software, Copyright MPCB.

Page 2 of 5

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:
Industry shall provide fly ash arrester of sufficient capacity to the

b) Standards for Stack Emissions:

1) SPM Not to exceed 150 mg/Nm3 2) SO2 Not to exceed 3 kg/day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Wood/ Bagasse	3.00	Ton/D

(iii) The applicant shall erect the chimney s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler	20.00

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- The industry should not cause any nuisance in surrounding area.

 The industry should monitor stack emissions and ambient air quality regularly.
- 6. Conditions for D.G. Set.....
- 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste	Quantity	UOM	Disposal
The Industry shall not ger	erate any typ	e of Hazar	dous waste.

sent is Processed through IMIS Application Software, Copyright MPCB.

Page 3 of 5

- (ii) Treatment: NIL
- The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

2. The industry should comply with the Hazardous Waste (M&H) Rules,

8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- win. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

onsent is Processed through IMIS Application Software. Copyright MPCB.

Page 4 of 5

- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

9. The Capital investment of the industry is Rs. 43.71 Lacs.

Regional Officer, Kolhapur,

M/S. Jubilee Synthetics Pvt. Ltd. S. No-21/6, A, MIDC Kupwad, Tal-Miraj Dist. Sangli,

Copy submitted to:

- 1. The Member Secretary, MPC Board, Mumbai.

- The Chief Accounts Officer, M.P.C. Board, Mumbai.
 The Sub Regional officer, M.P.C. Board, Sangli.
 Cess wing/Statistical wing/Air wing/ Hazardous Management Wing, M.P.C. Board. Mumbai.

Received Consent fee of

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1 .	1500	528916	8 Oct. 2011	Ratnakar Bank
-	THE RESERVE			