MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 022-24020781,24014701

Fax : 022-24023516,24093814

Email : jdwater@mpcb.gov.in

Visit At : <u>http://mpcb.gov.in</u>

Red/L.S.I



CACKIS de HISIL

Consent No.BO/JD (WPC)/RO Nagpur/ EIC NO NG-5696-11R/CC- Date: /01/2012

AHARASHTR

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Suryalaxmi Cotton Mills Ltd[®] 9 Km,Ramtek Mouda Road,

vill-Nagardham, Tq-Ramtek,

Dist-Nagpur -441106 🌔

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to:31/05/2014.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Denim & other varieties of yarm fabrics	2000	MT/M
2 2 COND	Hard & soft waste	184.50	MT/M

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 774.50M³.
(ii) The daily quantity of sewage effluent from the factory shall not exceed 70.00M³.

(iii) **Trade Effluent :**

<u>Treatment</u>: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted withreference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	30	mg/l.
4	COD	Not to exceed	250	
5	Oil & Grease	Not to exceed	10	mg/l.
<u>6</u>	Detergent	Not to exceed	2	
7	TAN	Not to exceed	50	mg/l.

- (iv) Effluent Disposal: The treated trade effluent shall be recycled to the maximum extent and remaining shall be discharged in to drainage system provided by MIDC. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
 - (1)Suspended Solids Not to exceed 100 mg/l.
 - (2)BOD 3 days 27o C. Not to exceed 100 mg/l.
- (vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be discharged into sewerage system provided by MIDC.

Sr. N	Type Of Waste	Quantity	UOM	Disposal
	Boiler Ash	430.00	MT/M	Brick manufacturer and coment manufacturer
2	Packing Waste	5.50		Scientific disposal/Sale
3	Fabric / cotton waste	100.00	MT/M	Coloniane disposal/Sale
4	Micro dust	4.75	MTM	*
5	Biological Sludge from ETP	15.00	MT/M	Used as manure

(vii) Non-Hazardous Solid Wastes:

viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose (ii) Water gets Rolluted &	86.50 CMD
Pollutants are Biodegradable	800.00 CMD
(iii) Water gets Polluted, Pollutants	
are not Biodegradable & Toxic	0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

912.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of (i) control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Industry shall provide dust collector of sufficient capacity to control the emissions.

b) Standards for Stack Emissions:

(ii) Th	 SPM SO2 spplicant shall obse 	Not to exceed Not to exceed rve the following fuel J	150 mg/Nm3 300 kg/day
Sr. No.	Type Of Fuel	Quantity	
1			UOM
1	Coal	35.00	MT/Day
2	Husk	36.00	MT /Day
3	LPG	1.42	MT/Day
4	HSD	1.76	MT/day
(***) (11)			III/uay

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Chimney Attached To	Height in Mtrs.
Boiler I, II,III (One Stand by)	33.00 Common
Themopac Fluid Heater 1 no	36.00
D. G. Set	6.50
	Themopac Fluid Heater 1 no

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 6. Conditions for D.G. Set
 - a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
 - d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
 - e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

Sr. No.	(1) The Industry shall han Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used /spent oil	0.80	MT /M	sale to auth recyclers
2	24.1 Textile chemical residues	22	MT /M	CHWTSDF
3	26.2 Chemical sludge from waste water treatment		MT /M	CHWISDF C
4	24.2 Chemical sludge from waste water treatment	8	MT/M	CHWTSDF
5	Asbestos Material	0.04	MT/M	CHWTSDF
6	E-waste			Authorized recyclers.

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
 - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.



It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.

4

- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Xi. Separate drainage system shall be provided for collection of trade and sewage effluents.Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. Industry shall submit bank Guarantee of Rs 5.0 Lakhs (Five Lakhs) at Regional Office Nagpur within fifteen days, for operation and maintenance of Effluent treatment plant.
- 10.Regular ground water monitoring would be required to be done and sampling shall be carried out at least twice in a year.
- 11. The consent is issued pursuant to the decision of Consent Appraisal Committee meeting of Board held on 23/01/2012.
- 12. This consent is issued in supersession to earlier consent issued by Board vide Consent No.BO/JD (WPC)/RO Nagpur/ EIC NO NG-5696-11R/CC-Date: 03/02/2012
- 13. The Capital investment of the industry is Rs 208-33 Crores.

(Milind Mhaiskar) Member Secretary

To, M/s Suryalaxmi Cotton Mills Ltd 9 Km,Ramtek Mouda Road, vill-Nagardham,Tq-Ramtek, Dist-Nagpur 441106.

Copy to .: RO Nagpur /SRO Nagpur II :- They are directed to obtain bank guarantees & ensure compliance of consent conditions. CAO/Cess wing/Master file. Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	625108	066152	24 May 2011	State Bank of Hyderabad
2	6,25,108	531634	29 Nov2011	SBH
3	20,372/-	532096	10 Jan 2012	SBH