

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 0231-2652952 /2660448

Udyog Bhawan Near Collector Office,

Fax : 0231-2652952



Email : rokolhapur@mpcb.gov.in

Kolhapur - 416003

Visit At : <http://mpcb.gov.in>

Orange/S.S.I

Date: 17.01.2012.

Consent No: MPCB/RO/KOP/ 1011 /12

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to .....

M/S. Abhijit Stone Crusher.  
Gat No. 104, A/p. Muthewadi,  
Tal. Atpadi, Dist. Sangli,  
Maharashtra.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Establish is granted for a period up to commissioning of the unit or five years whichever is earlier.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Stone Aggregates	375	Brass/M

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be Nil.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 0.5 M<sup>3</sup>.
- (iii) Trade Effluent :.....
- (iv) Trade Effluent Disposal: .....
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
  - (1) Suspended Solids Not to exceed 100 mg/l.
  - (2) BOD 3 days 27o C. Not to exceed 100 mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Stone Dust	75	Brass/M	--	sale

(viii) **Other Conditions:** .....

**4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

- (i) Domestic purpose ... 1.00 CMD
- (ii) Water gets Polluted & Pollutants are Biodegradable ... 0.00 CMD
- (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ... 0.00 CMD
- (iv) Industrial Cooling, spraying in mine pits or boiler feed ... 2.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**5. CONDITIONS UNDER AIR ACT:**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**a. Control Equipment:**

1. Dust containment cum suppression system should be provided to the equipments
2. Construction of wind breaking wall.
3. Construction of the metalled roads within the premises.
4. Regular cleaning & wetting of the ground within the premises.
5. Growing of the green belt along the periferi.
6. Water sprinkling arrangement shall be provided & operated continuously.

No stone crushing shall be activity will be allowed within 500 mtrs. From National Highway, 200 mtrs. From State Highway and 100 mtrs from other roads such as major district road, other district road or village roads. Also crusher shall be located 500 mtrs away from human habitation.

  
15/7/12

Standards for emission of Air Pollutants :

1. SPM .. Not to exceed 600 mg/Nm<sup>3</sup>
2. SO<sub>2</sub> .. Not to exceed --Kg/D.

7. Conditions for D.G. Set .....

8. Standards for Stack Emissions:

(i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
--	--	--	--

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
--	Nil	--

(iii) The applicant shall provide ports in the chimney(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

(iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor ambient air quality regularly.

9. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
The Industry shall not generate any type of Hazardous Waste.				

(ii) Treatment: - NIL


1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.

10. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

*(Signature)*  
17/1/12

- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
  - iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
  - iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
  - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
  - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
  - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
  - viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
  - ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
  - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
  - Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
  - xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
10. The Capital investment of the industry is Rs. 12.00 Lacs.

  
(P.M. Joshi)  
Regional Officer, Kolhapur.

To,  
M/S. Abhijit Stone Crusher,  
Gat No. 104, A/p. Muthewadi,  
Tal. Atpadi, Dist. Sangli,  
Maharashtra.

Copy submitted to :

1. The Member Secretary, MPC Board, Mumbai.
2. The Chief Accounts Officer, M P C Board, Mumbai.
3. The Sub Regional officer, MPC Board, Sangli.
4. Cess wing/Statistical wing/Air wing/ Hazardous Management Wing, M.P.C. Board, Mumbai.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	1500	707734	02 Dec. 2011	Bank Of Maharashtra

*(Signature)*  
12/12