

MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: <http://mpcb.gov.in>

E-mail: mpcb@vsnl.net



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

BO/JD(APC)/EIC No.PN-7053-11/O/CC-373

Date: 25/12/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Spaco Technologies (India) Pvt. Ltd.,
Plot No.62, Block D-2, MIDC,
Chinchwad, Pune - 19.

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to 31/12/2012.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Carborators	2,00,000	Nos./Month
2	Auto & Non Auto Components	1,50,000	Nos./Month

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 4 M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 48M³.

(iii) **Trade Effluent Treatment:** The applicant shall provide comprehensive treatment System consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sr.no	Parameter	Limits
1.	pH	Between 5.5 to 9.0
2.	BOD 3 days 27 Deg. C	Not to exceed 100 mg/l
3.	COD	Not to exceed 250 mg/l
4.	Oil & Grease	Not to exceed 10 mg/l
5.	Suspended Solids	Not to exceed 100 mg/l.
6.	Total Dissolved Solids	Not to exceed 2100 mg/l.
7.	Sulphates	Not to exceed 1000 mg/l.
8.	Chlorides	Not to exceed 600 mg/l.
9.	Copper	Not to exceed 3 mg/l.
10.	Zinc	Not to exceed 5 mg/l.
11.	Total Chromium	Not to exceed 2 mg/l.

(iv) **Trade Effluent Disposal:** The treated effluent shall be used on land for gardening in own premises only.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	Suspended Solids	Not to exceed	100 mg/l.
2	BOD 3 days 27o C	Not to exceed	100 mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **NON HAZARDOUS SOLID WASTE:**

Sr. No.	Type of waste	Quantity	Disposal
1	Zink Alloy scrap	200.00 MT/A	Authorized Party
2	Brass	100.00 MT/A	Authorized Party
3	Nickel Silver	10.00 MT/A	Authorized Party
4	Aluminium	10.00 MT/A	Authorized Party
5	Wooden Scrap	20.00 MT/A	Sale
6	Corrugated Box	2.00 MT/A	Sale
7	Plastic waste	5.00 MT/A	Sale

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

1	Domestic purpose	85.0 CMD
2	Industrial Processing	5.0 CMD
3	Industrial Cooling, spraying or boiler feed	29.0 CMD
4	Agriculture and Gardening	----

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:

- I. Dust Collector of sufficient Capacity shall be provided to all sources of SPM.
- II. Scrubber of sufficient capacity should be provided to scrub gaseous emissions from the process.
- III. There shall not be any secondary (fugitive) emissions.

b. Standards for Emissions of Air Pollutants:

(i) SPM/TPM	Not to exceed	150 mg/Nm ³
(ii) SO ₂	Not to exceed	49 Kg/day
(iii) SO ₂ (process)	Not to exceed	50 ppm
(iv) NO _x	Not to exceed	50 ppm
(v) Acid Mist	Not to exceed	35 mg/Nm ³

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use

g. D.G. Set shall be operated only in case of power failure.

h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	LDO	730	Ltrs/Day
2	LPG	330	Ltrs./day
3	HSD	740	Kg/day

- (i) **The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Chimney Attached To	Height in Mtrs.
1	PDC Burner	30
2	Die Heating burner	30
3	DG Set (3 Nos.x 500 KVA)	4.5 Above the roof.
4	DG Set (300 KVA)	3.5 Above the roof.
5	DG Set (285 KVA)	3.5 Above the roof.

- (ii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iii) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry shall monitor stack emissions and ambient air quality Regularly and reports shall be submitted to MPCB regularly.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Item No. of process generating HW as per Schedule-1	Type of Waste	Quantity	Disposal
1	5.1	Spent Oil	0.23 MT/M	Authorized Reprocessor/ Recycler
2	5.2	Waste Oil	0.72 MT/M	
3	12.9	ETP Sludge	0.60 MT/M	At CHWTSDF
4	12.1	Acid Residue	0.01 MT/M	
5	12.2	Alkali Residue	0.01 MT/M	
6	12.3	Toxic Metal Sludge	0.02 MT/M	
7	12.4	Contaminated Solvents (TCE)	0.02 MT/M	

(ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

9. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.


10. Industry shall comply with following general conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
11. The total capital investment of industry is Rs.86.23 Crores (Capital Investment of the Existing Rs.83.20 Crores + Additional Investment Rs.3.03 Crores)
12. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
13. Industry shall provide necessary pollution control system to plating /melting section within next two months and submit the Bank Guarantee of Rs.5 Lakhs with one year validity towards compliance of the same.
14. Industry shall dispose hazardous waste within next one month and submit the Bank Guarantee of Rs.3 Lakhs with one year validity towards compliance of the same.
15. Industry shall up grade STP within next three months and submit the Bank Guarantee of Rs.3 Lakhs with one year validity towards compliance of the same.

16. Industry shall submit resolution from their Board within one month that they have carried out operations without obtaining prior permissions from the M.P.C.Board and violated the provisions of Environmental Laws and in future they will not do such violations. If industry authority fails to submit the above said resolution within one month ,consent will be treated as cancelled.
17. This is issued with approval of Consent Committee meeting of the Board held on dtd. 02.04.2012 and with the approval of Hon'ble Chairman of the Board.

For and On Behalf of the
Maharashtra Pollution Control Board,


(Milind Mhaiskar, IAS)
Member Secretary

To,
M/s Spaco Technologies (India) Pvt. Ltd.,
Plot No.62, Block D-2, MIDC,
Chinchwad, Pune – 19.

Copy to:

- RO, MPCB, Pune /SRO, MPCB, Pimpri Chinchwad
- CAO/Cess Branch/Master File

Received Consent fee as per the revised Env.Dept.G.R.25.08.2011 -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	10,000/-	255475	19.07.2010	UCO Bank
2	1,000/-	255486	02.08.2010	UCO Bank
3	1,25,000/-	255644	24.10.2011	UCO Bank