


MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 nd - 4 th Fl.
Fax: 24024068 / 24023516		Opp. Cine Planet Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: mpcb@vsnl.net		Mumbai-400 022.

BO/JD(APC)/EIC No. RD- 2159-11/O/CC-3A1

Date: 20 / 04/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Hindustan Inox Limited.

Sr. No.28/5,28/6,29/A, 2A (1, 2), 30/1-4, 33/1, 33/3A, 33/4A,B(1),
Village: Kumbhivali, Tal: Khalapur, Dist: Raigad.

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to 30/06/2015.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Stainless Steel Bars,	1000	MT/Month
2	Wires	600	MT/Month
3	Wire Rods	75	MT/Month
4	Stainless Steel Pipes & Tubes (Welded / Seamless)	300	MT/Month
5	Stainless Steel Threaded Bars	25	MT/Month

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 7 M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 6 M³.

(iii) **Trade Effluent Treatment:** The applicant shall provide comprehensive treatment System consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

(iv)

1	pH	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l.
3	BOD ₃ Days 27 ^o C	Not to exceed	30 mg/l.
4	COD	Not to exceed	250 mg/l.
5	Oil and Grease	Not to exceed	10 mg/l.
6	TDS	Not to exceed	2100 mg/l.
7	Chlorides	Not to exceed	600 mg/l.
8	Sulphates	Not to exceed	1000 mg/l.
9	Iron	Not to exceed	3 mg/l.

(v) **Trade Effluent Disposal:** The treated effluent shall be reused to the maximum extent and remaining shall be sent to PRIA CETP for further treatment and disposal. There shall not be any discharge outside the factory premises.

(vi) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	Suspended Solids	Not to exceed	100 mg/l.
2	BOD 3 days 27o C	Not to exceed	100 mg/l.

(vii) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(viii) **NON HAZARDOUS SOLID WASTE:**

Sr No	Type of waste	Quantity	Disposal
1	S.S.Scrap	150 MT/ Month	By sale

(ix) **Other Conditions:** Industry should monitor effluent quality regularly.

4. **The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

1	Domestic purpose	7 CMD
2	Industrial Processing	10 CMD
3	Industrial Cooling	22 CMD
4	Agriculture /Gardening	--- CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:

- I. Fume extraction system followed by dust collection system of sufficient capacity shall provided to all sources of SPM/TPM and operate properly.
- II. Fume extraction system followed by scrubbing system of sufficient capacity shall provided to all sources of gaseous emission and operate properly.
- III. Air pollution control equipments of adequate capacity shall provided to limit the emissions.
- IV. There shall not be any secondary (fugitive) emissions.

b. Standards for Emissions of Air Pollutants:

(i) SPM/TPM	Not to exceed	150 mg/Nm ³
(ii) SO ₂	Not to exceed	---- Kg/day
(iii) Acid Mist	Not to exceed	35 mg/Nm ³

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. (a)Standards for Stack Emissions:

The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	LPG	105	Kg/Hr
2	Diesel	70	Ltr/Hr.

- (i) **The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Annealing furnace No.1	12
2	Annealing furnace No.2	12
3	Annealing furnace No.3	22
4	Annealing furnace No.4	20
5	Scrubber	10
6	DG Set (250 KVA)	3.5* Above the roof level
7	DG Set (600 KVA)	3.5* Above the roof level

- (ii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder,platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iii) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (iv) **Other Conditions:**
- 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry shall monitor stack emissions and ambient air quality Regularly and reports shall be submitted to MPCB regularly.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Item No. of process generating HW as per Schedule-1	Type of Waste	Quantity	Disposal
1	12.1	Acid residue	12 MT/M	At CHWTSDF.
2	34.3	Chemical sludge from waste water treatment	108 MT/M	

- (ii) Treatment: - NIL

(iii) The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.


9. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

10. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year,
- ix. the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- x. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- xi. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

11. The total Capital investment of the industry is Rs. 33.38 Crores.
12. Industry shall submit resolution from their Board within one month that they have carried out modernization without obtaining permission from the MPC Board and violated the provisions of Environmental Laws and in future they will not do such violations. If industry authority fails to submit the above said resolution within one month period consent will be treated as cancelled.
13. Industry shall submit distance certificate from Executive Engineer as per RRZ policy, 2009 within two months. If industry authority fails to submit the above said certificate within two months period consent will be treated as cancelled.
14. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
15. This is issued with approval of Consent Committee meeting of the Board held on dtd. 02.04.2012.

For and On Behalf of the
Maharashtra Pollution Control Board,



(Milind Mhaiskar, IAS)
Member Secretary

To,
M/s Hindustan Inox Limited.
Sr.no.28/5,28/6,29/A, 2A (1, 2), 30/1-4, 33/1, 33/3A, 33/4A,B(1),
Village: Kumbhivali, Tal: Khalapur, Dist: Raigad.

Copy to:

- a. RO, MPCB, Raigad /SRO, MPCB, Raigad-I
- b. CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	2,74,000	719565	25.04.2011	Indusland Bank
2	3,75,000	000129	13.02.2012	Indusland Bank