# MAHARASHATRA POLLUTION CONTROL BOARD

Phone

4010437/4020781

/4037124/4035273

Fax

24044532/4024068 /4023516

Email

apae@mpcb.gov.in

Visit At :

http://mpeb.gov.in

MAHARASHTRA

Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/L.S.I

Date: 08/06/2012

Consent No: BO/JD(APC)/EIC No.PN-13063-12/E/CC-(AC-447

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Bridgestone India Private Limited (Phase-I &II), Plot No. A-43, MIDC Chakan, Phase-II, Tal. Khed, Dist. Pune 410 501

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to establish is granted for a period up to commissioning of the unit or 5 year which ever is earlier

2. The Consent is valid for the manufacture of -

S7. N6	i Product Name	Maximum . Quantity . (Phase-I)	Maximum Quantity (Phase II)
. 1	Steel Belt Radial Tire for PSR and TBR	18,25,000 Nos/Y	2,920,000 Nos/Y
		(42,665MT/A)	(66,430 MT/A)
2	Inner Tubes	3,28,500 Nos/Y	657,000 Nos/Y
		(1,672 MT/A)	(2,628 MT/A)
. 3 :	Flap	3.28,500Nos/Y	657,000 Nos/Y
		(986 MT/A)	(1971 MT/A)
-4	Retreading of Tire	-	20647 Nos/Y
			(250 MT/A)

<sup>\*</sup>Phase-I shall be commissioned within five year period from consent issued byBoard

3. CONDITIONS UNDER WATER ACT:

<sup>(</sup>i) The daily quantity of trade effluent from the factory shall not exceed 980.0 M<sup>3</sup>

<sup>(</sup>ii) The daily quantity of sewage effluent from the factory shall not exceed 290M³.

## (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to standards as specified in schedule –VI of part A of Environmental protestation Rules, 1986. These standards are applicable only for disposal of treated effluent on land for irrigation. Effluent standards applicable at the site delivery point

State	r   Palameter		Limits:
1	рН	Between	5.5 to 9.0
2	BOD	Not to exceed	30 mg/l
3	COD	Not to exceed	250 mg/l
-1	Oil & Grease	Not to exceed	10 mg/l
5	Suspended Solids	Not to exceed	100 mg/l
6	TDS	Not to exceed	2100 mg/l
7	Sulphate	Not to exceed	1000 mg/l
8	Chloride	Not to exceed	600 mg/l

- (iv) Trade Effluent Disposal: The treated industrial effluent shall be recycled to the maximum extent and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) Sewage Effluent Disposal: The domestic effluent shall be treated at Sewage Treatment Plant. Overflow, if any, shall be used on land for gardening / plantation only.

Non-Hazardous Solid Wastes:

SW	NeType Of Waste	Quantity	UOM	Disposal
1	Scrap Tyre, Tube . Intermediate Rubber	1.43	MT/Day	By Sale
2	Steel scrap	0.95	MT/Day	By Sale
3	Wood scrap	1.59	MT/Day	By Sale
-1	Paper scrap	0.28	MT/Day	By Sale
5	Waste cotton	1.1	MT/Day	By Sale
6	Waste carbon bags polythene plastic bags and films	0.66	MT/Day	By Sale
7	Canteen waste	0.30	MT/Day	Given to piggery farms

#### (viii) Other Conditions:

- i) The unit shall carry out monthly monitoring of treated domestic as well as industrial effluent and submit the report of the same to the Board regularly
- ii) The unit shall take necessary efforts for segregation of solid waste at source only and disposal salable waste regularly. The records showing waste segregation at source to be maintained.
- iii) The unit shall take necessary efforts regarding rain water harvesting every monsoosn.
- 4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic	***	310.0 CMD
(ii) Industrial Processing		458.0 CMD
(iii) Industrial Cooling		1488.0 CMD
(iv) Industrial Processing		
& floor washing	***	0.0  CMD
(iv) Agriculture / Gardening	•••	760.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

## 5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

#### a. Control Equipment:

- i) Fume extraction system followed by Dust collection system of sufficient capacity should be provided to all sources of SPM/TPM shall be operated properly and continuously
- ii) Adequate fume extraction system followed by Wet scrubber shall be provided to capacitor and resistor shall be operated properly and continuously
- iii) The industry shall provided Acid Alkali Scrubbers are proposed as per the emission & for VOC, Hydrogen & ammonia burning system shall be provided
- iv) There shall not be any secondary (Fugitive) emissions.

#### b. Standards for Emissions of Air Pollutants:

(i)	SPM/TPM	Not to exceed	150 mg/Nm <sup>3</sup>
(ii)	$SO_2$	Not to exceed	120 Kg/Day
(iii)	Chlorine	Not to exceed	15 mg/Nm <sup>3</sup>
(iv)	Hydrochloric acid	Not to exceeds	35 mg/Nm <sup>3</sup>
$(\nabla)$	HF	Not to exceeds	4 mg/Nm <sup>3</sup>
(vi)	Sulphuric acid mist	Not to exceeds	50 mg/Nm <sup>3</sup>

## c. Conditions for D.G. Set:

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

d.(I) The applicant shall observe the following fuel pattern:-

SM/D	Type Of Fuel	Quantity	UOM
1	GAS	3312.00	M3/Hr
2	Furnace Oil	1702	Kg/Hı

(ii) The applicant shall erect the chimney(s) of the following specifications:-

SEN	RAChimney Attached To 🧺 🔭 🔭	Height in Mtrs.
1	Boiler	52
2	Boiler	<b>5</b> 2
3	Banbury No 1 – Dust Collector	3.00
-1	Banbury No 2- Dust Collector	3.00
õ	Banbury No 3- Dust Collector	3.00
6	Banbury No 4- Dust Collector	3.00
-	Boiler	49.77
8	Banbury No 5 – Dust Collector	3.00
9	Banbury No 6- Dust Collector	3.00
10	Banbury No 7- Dust Collector	3.00

6. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents

- attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.
- 7. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

#### (iii) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 3) The D.G. Set shall be utilized as a standby power source and shall be operate only in case of power failure

# 8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

23.00	Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used/spent oil	800.00	Lit/D	Sale to authoris
	-			reprocessor
$\overline{2}$	5.2 Wastes/residue	45.00	Kg/D	CHWTSDF
	<sup>1</sup> containing oil			Ranjangaon
ें	34.3 Chemical slud	60.00	Kg/D	CHWTSDF
	from waste			Ranjangaon
	water treatment			

## (ii) Treatment: - NIL

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office. Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008 and shown & submitted to the Board as & when asked for.

## 9. Industry shall comply with following general conditions:

i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
  - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
  - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
  - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
  - viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
  - ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
  - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
  - xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down-stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system
  - xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory

- 11. The applicant shall install Three continuous automatic ambient air & micrometeological monitoring station at location indicate by state Board to be set up & operate at is own cost measure SO2, NOx and particulate matter & same shall be directly connected to MPCB website http://mpcb.gov.in as well as to the respective Regional Office.
- 12. Industry shall adopt cleaner technology manufacturing process by installing closed Raymond mill type machinery.
- 13. This issued with approval of Consent Appraisal Committee meeting of the Board held on dtd. 29/05/2012.
- 14. This consent is issued in supersession of earlier consent vide No.BO/APAE/EIC No. PN-7507-10/E-05 dated 04/01/2012
- 15. The Total Capital investment of the industry is Rs 1747.16 Crs (Phase-I Rs. 1221.60 Crs + Phase II Rs. 525.56 Crs)

(Milind Mhaiskar IAS) Member Secretary

To,

M/s. Bridgestone India Private Limited (Phase-I &II), Plot No. A-43, MIDC Chakan, Phase-II, Tal. Khed, Dist. Pune 410 501

#### Copy to:

- 1) Regional Officer/Sub-Regional Officer, MPCB, Pune-II-They are directed to submit the present status report within 1 month.
- 3) Chief Accounts Officer, MPCB, Mumbai Received Consent fee of

Sv. No. Amount (Rs.)	DD: No.	Date	Drawn On
1 1002600	125352	20 Jan 2012	HDFC Bank