MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 24020781 / 24010437

: 24024068 / 24044532



Kalpataru Point, 2nd, 3rd & 4th Floor, Opp. Cineplanet, Near Sion Circle, Sion (E), Mumbai-400022.

Email : mpcb@vsnl.net

Fax

Visit At : <u>http://mpcb.gov.in</u>

EIC No: MU-3696-12 RED/LSI Consent No. MPCBHQ/ROHQ/Mumbai/CO/CC/429

Date: | 2/06/2012

Consent to Operate Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

CONSENT is hereby granted to,

M/s. Verma Medicine Research Trust, "CDKD Hospital" (Centre for Digestive and Kidney Disease), C.S.No: 215/74 (pt) & 215A/74 of Parel-Sewree, Division in F/south Ward at Parel, Mumbai, Maharashtra.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31/03/2013.

For Hospital Project named as M/s. Verma Medicine Research Trust, "CDKD Hospital" (Centre for Digestive and Kidney Disease) at C.S.No: 215/74 (pt) & 215A/74 of Parel - Sewree, Division in F/south Ward at Parel, Mumbai, Maharashtra on Total plot area of 11,296.93 sq.mtr & Total Construction BUA of 27,444.84 sq.mtrs including utilities of Hospital Project as per occupancy certificate issued by local body.

2. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of sewage effluent from the factory shall not exceed 199.0 M3.

 (ii) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1

1	pH	Not to exceed	6.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l.
3	BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
4	Fecal Coliform	Not to exceed	500/100/1 mg/l.
5	Residual Chlorine	Not to exceed	01 mg/l.
6	Detergent	Not to exceed	01 mg/l.
7	Floating matters	Not to exceed	10 mg/l
8	COD	Not to exceed	250 mg/l

(iii) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners and remaining shall be discharged to Municipal sewer. In no case, effluent shall find its way to any water body directly/indirectly at any time.

[Project proponent shall operate STP for five years from the date of obtaining Occupation Certificate].

Sr.No	Type of Segregated solid waste	Quantity (Kg/Day)	Treatment	Disposal
1.	Wet Garbage	53	~	Use as Manure
2.	STP Sludge	30	Composting	
3.	Dry Garbage	123		landfill site
4.	Bio – Medical Waste	395		Medical Waste 1998 as amended

(iv) Non-Hazardous Solid Wastes:

3. Other Conditions: -

- 1. All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927). Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- 2. Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable;
- 3. Near the activities that are related to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- 4. In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.
- 5. The Applicant shall draw plans for the segregation of solid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e vermi-composting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000.
- 6. The applicant / generator shall be responsible for safe and scientific collection, transportation, treatment & disposal of Bio Medical waste as per the provisions made under Bio Medical Waste (M&H) Rules 1998 as amended. Any activity as defined under BMW (M&H) Rules has to obtain a separate authorisation from Maharashtra Pollution Control Board.
- 7. Applicant shall be responsible to take adequate precautionary measures as detailed in this consent.

- 8. For disinfections of waste water ultra violet radiation shall be used in place of chlorination.
- 4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under,

The daily water consumption for the following categories is as under:

(i) Domestic	•••	264.00 CMD
(ii) Water gets Polluted &Pollutants are Biodegradab(iii) Water gets Polluted, Polluta		0.00 CMD
are not Biodegradable & To (iii) Industrial Cooling, spraying	xic	0.00 CMD 0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACF, 1981:

(i) The Applicant may install 2-nos. of diesel generating sets (DG Sets), of capacity 2000 KVA each and shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Standards for Emissions of Air Pollutants:

(i) SPM/TPM	Not to exceed Not to exceed	150 mg/Nm3
(ii) SO2 (DG Set)	Not to exceed	183 Kg/day

(ii) The following measures shall be taken:

- a. Adequate mitigation measures shall be taken to control emissions of SO2, NOx, SPM, and RSPM.
- b. Applicant shall achieve following Ambient Air Quality standards.

1.	SPM_Not to Exceed (Annual Average) Not to Exceed (24 hours)	$\frac{140}{200}$	μg/ m3 μg/ m3
2.	SO2 Not to Exceed (Annual Average)	60	μg/ m3
	Not to Exceed (24 hours)	80	μg/ m3
3.	NOx Not to Exceed (Annual Average)	60	μg/ m3
	Not to Exceed (24 hours)	80	μg/ m3
4.	RSPM Not to Exceed (Annual Average)	60	μg/ m3
	Not to Exceed (24 hours)	100	μg/ m3

(iii) The applicant shall observe the following fuel pattern:-

	Sr. No.	Type Of Fuel	Quantity	
	1	Diesel	295 ltrs/Hr	
(iv)	specifications:-	shall erect the chim Chimney Attached To	mey(s) of the following Height in Mtrs.	
	1	D. G. Set 2000 KVA x 2-Nos	8.5 Mtrs each	

(v)

Conditions for D.G. Set

- 1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(vi) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- c) Construction material shall be carried in enclosed vehicles during construction activities.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

Sr.No	HW as per Schedule-I	Type of Waste	Quantity	Disposal
1.	••	Electrical & Electronic Waste	As per generaton	Sale to authorised
2.	5.1	Used / Spent Oil		recycler

(i) The Industry shall handle hazardous wastes as specified below.

7. The applicant shall adopt environment friendly technology in development of the project.

4

- 8. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant;
- 9. The applicant shall comply with the conditions stipulated in <u>Environment</u> <u>Clearance</u> granted by GOM, vide no: <u>SEAC-2009/CR.27/TC.2</u>, <u>dt: 19/05/2010.</u>
- 10. This is issued pursuant to the decision of <u>Consent Committee</u> of the Board in its meeting held on <u>29th May 2012 & approval of chairperson of the Board</u>.
- 11. The applicant shall submit <u>Bank Guarantee of Rs. 10.0 Lakhs</u> towards the compliance of consent conditions at Regional Office, MPCB, Mumbai <u>within</u> <u>15-days.</u>
- 12. The <u>Capital investment</u> of the total project is <u>Rs. 283.75 Cr</u> and that of the part completed is <u>227.68 Cr</u>.

(Milind Mhaiskar) Member Secretary

To,

M/s. Verma Medicine Research Trust, "CDKD Hospital" (Centre for Digestive and Kidney Disease), at C.S.No: 215/74 (pt) & 215A/74 of Parel-Sewree, Division in F/south Ward at Parel, Mumbai, Maharashtra.

Copy to-

- 1. Regional Officer, MPCB, Mumbai He is directed to obtain necessary Bank Guarantee from the applicant and ensure compliance of consent conditions
- 2. Sub Regional officer-I, Mumbai, MPCB,
- 3. Chief Accounts Officer, Mumbai, MPCB,

Received consent fee of:-

Sr. No.	Amount	DD. No.	Date	Drawn On
1.	Rs. 4,55,460/-	008536	23/08/2011	HDFC Bank

4. Cess Branch, MPCB, Mumbai.

5. Master file.