MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 24010437/24014701/24020781 : 24024068/24023516 Fax Website: http://mpcb.gov.in.

E-Mail: apae @mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8, Opp. Sion Circle, Sion (East), Mumbai-400 022.

RED/LSI

1

i

ì

į

09/07/2012 Consent No. BO/JD(APC)/EIC No.NG-5939-11/R/CC-480 Date Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act. 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes Management, Handling & Trans Boundary Movement) Rules 2008. [To be referred as Water Act. Air Act and H W (M. H & TM) Rules respectively].

CONSENT is hereby granted to

M/s. Shilpa Steel & Power Ltd.,

(Formerly known as M/s Shilpa Re-Rollers Pvt. Ltd.), Plot No. B-209, MIDC Industrial Area, Butibori, Dist: Nagpur.

coated in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of H W (M, H & TM) Rules subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to 31.03.2013.

1. The Consent is valid for the manufacture of -2.

ine Cons	ent is valid for the manufacture er	Maximum Quantity
Sr No	Product	
	Transmission Line Towers.	6000 MT/Month
	Sub-station structure. Telecom	
	Towers & Structures, Nuts & Bolts	
7	Hot Rolled Steel Products	7000 MT/Month
-	Gasifier Unit-I Producer Gas for captive	e use) 2400 MT/Month
.	Gasifier Unit-II Producer Gas for captiv	e use)2800 MT/Month
-	Odenio Oni in i	A THE A NAME AND

CONDITIONS UNDER WATER (Prevention & Control of Pollution) ACT, 1974: 3.

The daw quantity of trade effluent from the factory shall not exceed 15.2 m³.

The baily quantity of sewage effluent from the factory shall not exceed 9.4 m³.

Trade Effluent Treatment-

The applicant shall operate comprehensive treatment system consisting of primary / secondary and or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the folio ving standards:

	PH	Between	5.5 to 9.0
2 1	BOD 3 days 27 Deg. C.	Not to exceed	100 mg/l.
3	COD	Not to exceed	250 mg/l.
4	Suspended Solids	Not to exceed	100 mg/l.
E.	On & Grease	Not to exceed	10 mg/l.
5	TDS	Not to exceed	2100 mg/l.
-	Chiorides	Not to exceed	600 mg/l.
3.	Sulphates	Not to exceed	1000 mg/l.
9	Cr + 6 (as Cr)	Not to exceed	0.1 mg/l.
- 0	Zinc	Not to exceed	5 mg/l.
- 1	Total Metal	Not to exceed	10 mg/l.
			In a set the NAI

Trade Effluent Disposal: The treated effluent shall be sent to MIDC Butibori for further treatment and disposal. There shall not be any discharge outside the factory premises.

Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27° C.	Not to exceed	30	mg/l.

Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which scall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

Non-Hazardous Solid Wastes:

l

í

i

I

Sr. No. Type of waste Quantity Treatment Disposal	
Sr No Type of waste Quantity <u>Treations</u>	
1 Steel Scrap 617 MT/M By sale	
Oteeredatap	ran nlant
2 Mill Scale 300 MT/M By sale to sponge in	
E Du sala ta briek mon	nufacturer
The construction ONT/Month by sale to bot MIX PL	plant
4 Lar from Gasilier o Mitrivionul	

Other Conditions: The industry shall monitor effluent quality regularly. (Viii)

The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) 4. Cess Act. 1977 (to be referred as Cess Act) and Rules there under:

The daily water consumption for the following categories is as under:

- 11.0 CMD i Domestic 8.2 CMD dia Industrial Processing
- CMD 86.0 (ii) Industrial Cooling 10.0 CMD

(v) Agriculture/Gardening

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981: 5.

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment: A)

1) Fume extraction system followed by scrubber provided to Pickling Section, Galvanizing section and any other source producing emissions shall be operated and maintained properly so as to achieve following air emission standards.

2. Fume inhibitor shall be used continuously as anti vapor in HCL pickling section to bring down the gaseous emission and scrubber provided to pickling section should operate and maintain propert,

Conditions for DG Sets: -B)

- Noise from DG Sets shall be controlled by providing acoustic enclosure or by treating the room acoustically.
- 2 Applicant should provide acoustic enclosure for control of noise. The acoustic enclosure/ accustic treatment of the room shall be designed for minimum 25 dB(A) nsertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB(A) shall also be provided. The measurement of insertion loss shall be done at different points at 0.5 meters from acoustic enclosure/ room and then average.
- 3 The Applicant should make efforts to bring down noise level due to DG Set, outside the premises with ambient noise level requirements by proper setting and control measures.
- installation of DG Set must be strictly in compliance with recommendations of DG set manufacturer:
- 5. A proper routine and preventive maintenance procedure for DG Set shall be set and followed in consultation with the DG manufacturers, which would hep to prevent noise evels of DG Sets from deteriorating with use.
- 6 The DG set shall be operated only in case of power failure. The applicant shall make arrangement for regular electrical power.
- The Applicant shall not cause any nuisance in the surrounding area due to operation of DG sets.
- 8. In case of problems, the D.G. set shall not be operated until it is set back to satisfactory position.

Standards for Emissions of Air Pollutants: B)

- Not to exceed 150 mg/Nm³ SPM/TPM (i) –
- 574.8 Kg / day. Not to exceed (ii) SO-
- (iii) Acid Mist Not to exceed 35 mg/Nm^3

B: Standards for Emissions of Air Pollutants:

	SPM/TPM	Not to exceed	150 mg/Nm°
(11)	SO	Not to exceed	25.92 Kg / day.
(iii)	Acid Mist	Not to exceed	35 mg/Nm ³

The applicant shall observe the following fuel pattern

<u>Type of Fuel</u>	Quantity
LDO	4.85 KL/Day
LPG	0.050 T/Day
Coal	40 T/Day
	<u>Type of Fuel</u> LDO LPG

The applicant shall erect the chimney(s) of the following specifications:

Sr.No	Chimney <u>attached</u> to	<u>Height in Mtrs</u>
~	Acid Bath Scrubber	17.2
2	Drying Chamber	18.0
3	Bag Filter & Galvanizing Furnace	17.2
	Blending Furnace	12.0
Ē	Gasifier Unit-I	30.0
8	Gasifier Unit-II	30.0

The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.

The industry shall take adequate measures for control of noise levels from its own sources ... thin the premises so as to maintain ambient air quality standard in respect of noise to less than 75 aB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between S a million 10 p million night time is reckoned between 10 p.m. and 6 a.m.

Other Conditions:

The industry should not cause any nuisance in surrounding area.

The industry should monitor stack emissions and ambient air quality regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MH &TM) RULES, 2008:

The applicant shall handle hazardous wastes as specified below:

S: No	Item No. as per H.W. Schedule-I	Type of Waste	Quantity	Disposal
	34.3	ETP Sludge	1029 Kg/Day	CHWTSDF
2	6.1 & 6.2	Zinc Ash & Dross	2826 Kg/day	MPCB Authorized Re
Ĵ	34 1	ZnO	20 Kg/Day	processor
	5.1	Used/Spent Oil	1.54 Kg/Day	
6	12.3	Spent acid	14 m3/day	To authorized acid recovery plant

7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprenended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories, and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

8. General conditions:

(i) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no, of trees surviving as on 31st March of the year and no, of trees planted by September end.

1

ł

1

i

The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality, the rate of a scharge temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments are, ded for without previous written permission of the Board.

- The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- Separate orainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers dowr stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- The acc cant shall provide facility for collection of environmental samples and samples of trade and sevage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated coints and shall pay to the Board for the services rendered in this behalf. An inspection book shall be occered and made available to the Board's officers during their visit to the applicant.
- The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises
- 9. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 10. This consent is issued pursuant to the decision of Consent Committee Meeting of the Board neighbor 30.05.2012 & with the approval of the Chairman of the Board.
- 11. This consent is issued with the overriding effect of the consent granted by the Board vide No. BO/JD(APC)/EIC No.NG-4949-11/R/CC- 40 dated 29.11.2011.
- 12. The applicant shall submit the irrevocable BG of Rs. 5 Lakhs for O & M of pollution control system so as to achieve the consented standards within 15 days drawn in favour of RO,MPCB, Nagpur, valid for one year period.
- 13. The total gross capital investment of the industry is Rs. 66.85 Crore.

For and on Behalf of the Maharashtra Pollution Control Board.

Milind Mhaiskar, IAS) Member Secretary

Тο

l

į

ł

1

M/s. Shilpa Steel & Power Ltd.,

(Formerly known as M/s Shilpa Re-Rollers Pvt. Ltd.),

Plot No. B-209. MIDC Industrial Area, Butibori, Dist: Nagpur.

Coclutor

1. Regional Officer MPC Board, Nagpur 2) Sub Regional Officer, MPC Board, Nagpur-II.

They are directed to obtain the bank guarantee of Rs. 5.0/- Lakh from the industry and submit the compliance of consent conditions & directions issued to the industry within one month's ceriod with all monitoring results.

3) CAO/Cess Branch/Master file

Received Consent fee of -

Amount	D.D.No.	<u>Date</u>	<u>Drawn on</u>
Rs. 2,60,100/-	526421	10.01.2011	SBI Bank
Rs. 9.500/-	531030	19.10.2011	SBI Bank
Rs.600/-	531814	08.12.2011	SBI Bank
Rs.5.000/-	960308	18.06.2012	SBI Bank
~ ~			D U D M July Jor O D

Consent Fees received as per revised consent fee GR of Env Deptt, GoM, dated 25.8.2011. 4] Cess Branch, MPCB.