

MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068/24023516

Website: <http://mpcb.gov.in>

E-mail: apac@mpcb.gov.in



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

Red L.S.1

Consent No: BO/JD(APC)/EIC No. AD-9682--11/R/CC-979 Date: 06/07/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. High Technology Transmission System (I) Pvt. Ltd.,

K-226/1 & K-227, MIDC Area Waluj,

Dist - Aurangabad.

at the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to :- 31/12/2014

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Clutch Assembly	250000	Nos./M
2	Machining of Gears	60000	Nos./M
3	CVT	25000	Nos./M
4	Friction Plate	2083333	Nos./M
5	Aluminum Pressure Die Casting	200	T/M
6	Heat Treatment of MS Gears	40000	Nos./M
7	Brake Pad	100000	Nos./M
8	Brake Liner	750000	Nos./M

3. CONDITIONS UNDER WATER ACT:

a) The daily quantity of trade effluent from the factory shall not exceed **15.0 M³**

b) The daily quantity of sewage effluent from the factory shall not exceed **50.0 M³**.

iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sr.no	Parameter	Limits
1	pH	Between 5.5 to 9.0
2	Suspended Solids	Not to exceed 100 mg/l.

4	BOD 3 days 27 Deg. C	Not to exceed	100 mg/l
5	COD	Not to exceed	250 mg/l
6	Oil & Grease	Not to exceed	10 mg/l
7	Total Dissolved Solids	Not to exceed	2100 mg/l
8	Sulphates	Not to exceed	1000 mg/l.
9	Iron	Not to exceed	5.0 mg/l.

3. **Trade Effluent Disposal:** The treated industrial effluent shall be recycled to the maximum extent and remaining shall used on land for gardening. There shall not be any discharge outside the factory premises. Industry should not discharge any effluent in to local nalla.

4. **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1.	Suspended Solids	Not to exceed	100	mg/l.
2.	BOD 3 days 27o C.	Not to exceed	100	mg/l.

5. **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used for soil gardening plantation only.

Non-Hazardous Solid Wastes:

Sr. No.	Type of Waste	Quantity	Disposal
1.	Scrap MS Heavy	1.5 MT/M	Sale
2.	Non Metallic Scrap	6.0 MT/M	Sale
3.	Paper Waste	0.5 MT/M	Sale

6. **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the **Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003** there under

The daily water consumption for the following categories is as under:

1.	Domestic	...	55.0	CMD
2.	Industrial Processing	...	20.0	CMD
3.	Industrial Cooling	...	30.0	CMD
4.	Soil Culture - Gardening	...	0.0	CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT :**

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of emissions to the following standards:

Control Equipment:

1. Fume extraction system followed by scrubber of sufficient capacity shall be provided all the furnaces and any other source of gaseous emission.
2. Dust collector of sufficient shall be provided to all the particulate emission sources.
3. There shall not be any secondary (fugitive) emissions.

Standards for Emissions of Air Pollutants:

(i)	SPM/TPM	Not to exceed	150 mg/Nm ³
(ii)	SO ₂	Not to exceed	40 Kg/Day
(iii)	Acid Mist	Not to exceed	35 mg/l

(v) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	LPG	30	Kg/Hr.
2	HSD	100	Ltrs/Hr.
3	Furnace Oil	200	Ltrs/Hr.

(vi) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	DG Set (2x750 KVA)	16 each
2	DG Set 100 & 125 KVA	09 each
3	Acid scrubber	12
4	Dust Collector	12
5	Melting Furnace 1&2	11
6	Salt Quenching furnace 1 &2	5
7	Indo gas generator	5

(vii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2 etc. and these shall be painted/ displayed to facilitate identification.

(viii) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(ix) **Other Conditions:**

1. The industry should not cause any nuisance in surrounding area.
2. The industry should monitor stack emissions and ambient air quality

6. Conditions for D.G. Set

a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB(A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.

- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below.

Sr. N	Type Of Waste	Quantity	UOM	Disposal
1	20.2 Spent Solvent/Abs clean /ME	3910	Kg/M	CHWTSDF
2	20.3 Discarded containers/ Labels, liners empty paint spray bottles	60	Nos/M.	Authorised reprocessor
3	19.1 ETP Sludge	2300	Kg/M	CHWTSDF
4	19.2 Waste Residue containing oil	450	Kg/M	CHWTSDF
5	20.3 Spent Oil	1175	Ltr/M	Authorised reprocessor
6	20.4 Xylene Residue	700	Ltr/M	CHWTSDF
7	19.2 Process Residue	40	MT/M	CHWTSDF
8	20.1 Wastes residues (not made with vegetable or animal products)	15000	Kg/M	CHWTSDF
9	20.100.1 on Case skimming residues	9000	Lit/M	CHWTSDF
10	20.100.2 Dust particulates from wastewater gas treatment	20	T/M	Authorised reprocessor

Treatment: NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
 - a. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
 - b. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.
 - c. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

9. **Industry shall comply with following additional conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage / tree plantation.
- iii. Solid waste - The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The applicant shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form V as per the provisions of rule 14 of the Environment Protection (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and an pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Sewerage drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the

pipes, sewers down-stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

10. The Capital investment of the industry is Rs. 60.63 Crs.

11. This is issued with the approval of Consent Committee meeting held on 27/07/2012.

12. The applicant is hereby directed to submit resolution from Company's Board within one month period to the Board, stating that they have carried out modernization without obtaining permission from the M.P.C. Board and violated the Environmental laws and in future they will not do such violations. If industry authority fails to submit the said resolution within one month period, consent will be treated as cancelled.

13. Due to amalgamation of three different consents, this consent supersedes earlier consents granted by Board vide no.

(1) MPCB/RO/VABD/R/CC-81/926/09 dated 3/7/2009.

(2) BO/APAE/EIC No.AD-3392-09/O/CC31 dated 27/8/2010.

(3) BO/APAE/TB-2/EIC No. AD-5961-252 dated 2/12/2010.

14. Industry shall submit the operational Bank Guarantee of Rs. 5.0 (Five Rupees five laes) in favour of Regional officer Arangabad, with validity of one year, within 15 days from date of grant of consent.



(Milind Mhaskar, IAS)
Member Secretary

To,
M/s. High Technology Transmission System (I) Pvt. Ltd.,
K-226 I & K-227, MIDC Area Waluj,
Dist - Aurangabad.

Copy to:
RO, MPCB Aurangabad -SKO-MPCB Aurangabad
CAO Class Branch Master File
Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	100100/-	003076	26/12/2011	IDBI
2	200000/-	00210	16/6/2012	IDBI