

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 2402 4068

Email : jdwater@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Kapataru Point
02nd, 03rd & 04th floor
Opp. Cineplanet,
Near Sion Circle, Sion (E),

Mumbai- 400 022

Red/LSI

Consent No. BO/RO/JD (WPC)/EIC-PN-14026-12/R/CC-CAC- 528

Date: 16/07/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008. [To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

CONSENT is hereby granted to,
Lokmangal Sugars, Ethanol & Co-Generation Industries Ltd.,
(Sugar & Co-Generation Unit),
A/p – Bhandar Kavathe, Tal. – South Solapur,
Dist. – Solapur.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & T) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to 30.04.2013.
2. The Consent is valid for the manufacture of –

Sr	Products	Max. Qty.
1	Crystal Sugar	8000 MT/M
2	Co-Generation	15 MW
3	Molassess	3000 MT/M
4	Press Mud	3000 MT/M
5	Bagasses	22500 MT/M

3. CONDITIONS UNDER WATER ACT :

- (i) The daily quantity of trade effluent from the factory should not exceed 376 M³/day.
(i.e The effluent from sugar industry should not exceed – 190 M³/day and
Co-generation unit – 186 M³/day)
- (ii) The daily quantity of sewage effluent from the factory should not exceed 100 M³/day.

(iii) Trade Effluent:

Treatment: The applicant should operate comprehensive treatment system consisting of primary/secondary and/or tertiary treatment as is warranted with reference to influent quality and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

The Industrial effluent arising from various sections of Power Plant shall be given such treatment either collectively or individually as the site condition permits that the final quality of effluent shall have following characters standards.

1	pH	Between	5.5 to 9
2	Suspended Solids	Not to exceed	100 mg/l
3	BOD 3 days 27 Deg. C	Not to exceed	100 mg/l
4	COD	Not to exceed	250 mg/l
5	Oil & Grease	Not to exceed	10 mg/l
6	T.D.S.	Not to exceed	2100 mg/l
7	Sulphates	Not to exceed	1000 mg/l
8	Chlorides	Not to exceed	600 mg/l

- (iv) **Trade Effluent Disposal:** The treated industrial effluent shall be recycled/ reused to the maximum extent and remaining shall be used on land for gardening only. There shall not be any discharge directly or indirectly into the water body.
- (v) **Sewage Effluent Treatment:** The applicant should operate comprehensive treatment system as is warranted with reference to influent quality and maintain the same continuously so as to achieve the quality of treated effluent to the following standards:

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27 Deg. C.	Not to exceed	100	mg/l.

- (vi) **Sewage Effluent Disposal:** The treated sewage effluent should be soaked into soak pit which should be got cleaned periodically. Overflow, if any be used on land for gardening only within factory premises only.

- (vii) **Non-Hazardous Solid Wastes:**

Type of Waste	Quantity	Disposal
ETP Sludge	4.5 T/M	Used as manure
Boiler Ash	8.06 MT/M	Sale to brick manufacturers.

- (viii) **Other conditions:** The industry should monitor effluent quality regularly from MoEF approved laboratory.

4. **CONDITIONS FOR MOLASSES STORAGE:-**

- i) The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- ii) The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutch pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, non-lifting of molasses etc.
- iii) All the area on which molasses are stored and handled shall be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- iv) Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board at least 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near the tank.
- vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- vi) The industry shall monitor effluent quality regularly.

5. The applicant should comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under:
The daily water consumption for the following categories is as under:

i	Domestic	123	CMD
ii	Industrial Processing	800	CMD
iii	Industrial Cooling / Boiler	730	CMD
iv	Agriculture/Gardening	---	CMD

The applicant should regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. **CONDITIONS UNDER AIR ACT:**

- (i) The applicant should operate a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and maintain the same continuously so as to achieve the level of pollutants to the following standards:

A) Control Equipment:

i) ESP/Ventury scrubber of sufficient capacity shall be provided to Bagasse fired boiler and shall be operated and maintained properly.

ii) ESP/Bag filter/ Ventury scrubber/ Dust collector of sufficient capacity shall be provided to sugar bagging section.

Standards for Emissions of Air Pollutants:

1	SPM/TPM	Not to exceed	150 mg/Nm ³
2	SO ₂	Not to exceed	8.0 T/day

- (ii) The applicant should observe the following fuel pattern :-

Sr	Fuel Type	Quantity
1	Bagasse	806 MT/day

- (iii) The applicant should erect the chimney(s) of the following specifications :-

Sr.	Chimney attached to	Height in mt.
1	Bagasse Fired Boiler	71 mtrs.

- (iv) The applicant should provide ports in the chimney/(s) and facilitates such as ladder, platform etc. For monitoring the air emissions and the same should be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission should be designated by numbers such as S-1, S-2, etc. And these should be painted / displayed to facilitate identification.

- (v) The industry should take adequate measures for control for noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. And 10 p.m. And night time is reckoned between 10 p.m. And 6 p.m.

- (vi) Other Conditions:

1) The industry should not cause any nuisance in surrounding area.

2) The industry should monitor stack emissions and ambient air quality regularly from MoEF approved laboratory.

7. **CREP Conditions for Sugar Factory:-**

(A) Water Management:-

- (i) Operation of ETP Shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
- ii) Waste water generation shall be reduced to 100 liter per tone of cane crushed.
- iii) Industry shall achieve zero discharge into in land surface water bodies.
- iv) 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.

- (B) Emission Control: ESP/ Bag Filter/ Ventury Scrubber shall be installed to comply with standards for particulate matter emission to < 150 mg/Nm³.

8. **CONDITIONS UNDER HAZARDOUS WASTE (Management, Handling & Transboundary Movement) RULES, 2008:**

The applicant should handle hazardous wastes as specified below:

Sl.	Item No (Sch-I)	Type of Waste	Quantity	Disposal
1	5.1	Used/Spent Oil	1.3 MT/M	Mixed with Bagasse and burnt own boiler.

9. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information should be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it should be stopped.

10. **General Conditions:**

- (i) The applicant should bring minimum 33% of the available open land under green coverage/ plantation. The applicant should submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant should provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant should stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant should make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant should not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm should submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- (iv) The applicant should install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment should be maintained. The applicant should also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- (vi) Separate drainage system should be provided for collection of trade and sewage effluents. Terminal manholes should be provided at the end of collection system with arrangement for measuring the flow. No effluent should be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent should find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises should be allowed to mix with the effluents from the factory.
- (vii) The applicant should provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and should pay to the Board for the services rendered in this behalf. An inspection book should be opened and made available to the Board's officers during their visit to the applicant.
- (viii) The industry should ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant should maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

11. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the applicant.

12. The Industry shall comply with the hazardous Waste (Management, Handling & Trans Boundary Movement) Rules. 2008.
13. Industry shall submit fresh Bank Guarantee of Rs. 10.0 Lakhs to comply ETP Standards. The Bank Guarantees shall be submitted within 15 days at Regional Office Pune.
14. This Consent is issued pursuant to the decision of the Consent Appraisal Committee meeting of the Board held on 03/07/2012.
15. The total capital investment of the Industry is Rs. 221.81 Crores. (The Capital Investment of the Sugar Unit is Rs. 118.41 Crores and Co-Generation is of Rs.103.40 Crores)

For and on Behalf of the
Maharashtra Pollution Control Board,



(Milind Mhaiskar)
Member Secretary

To
M/s. Lokmangal Sugar Ethanol & Co- Generation Industries Ltd.,
A/p- Bhandar Kavathe,
Tal. - North Solapur, Dist.- Solapur.

Copy to: RO, MPCB, Pune - R.O shall submit quarterly monitoring reports for the compliance of conditions for which BG obtained.

SRO, MPCB, Solapur: - They are directed to collect the Bank Guarantee from industry within 15 days and ensure the compliance of consent conditions.

CAO / Cess Branch / Master File.

Received Consent fee of -

Amount	D.D. No.	Date	Bank
443638/-	000756	31.03.2012	Axis Bank
100/-	662443	03.04.2012	Lokmangal Co-Operative Bank