MAHARASHATRA POLLUTION CONTROL BOARD

Phone: 2402 0781/2401 0437

Fax

2402 4068

Email

jdwater@mpcb.gov.in

Visit At :

attp://mpcb.gov.in



Kapataru Point 02nd,03rd & 04th floor Opp. Cineplanet, Near Sion Circle, Sion (E),

Mumbai- 400 022

Red/L.S.I

Consent No: BO/JD (WPC)/EIC-PN-13944-12/E/CC-CAC-547

Date: 02/08/2012

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H &TM) Rules respectively].

CONSENT is hereby granted to

Karmayogi Shankarraoji Patil SSK Ltd., (Sugar & Cogen) At.- Mahatma Phulenagar (Bijwadi), Tal- Indapur, Dist- Pune Pune-413106

is sated in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Establish is granted for a period up to: Commissioning of the unit or 5 years whichever is earlier.
- 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM	
1	White sugar	10800	MT/M	
2	Power	18.59	MW	
By Produ	icts			
3	Molasses	3600	MT/M	
4	Press Mud	3600	MT/M	
5	Bagasse	25200	MT/M	

3. CONDITIONS UNDER WATER ACT:

- in The daily quantity of trade effluent from the factory shall not exceed 290.00M3.
- iii The daily quantity of sewage effluent from the factory shall not exceed 10.00M3.

mis Trade Effluent:

<u>Treatment</u>: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

SRO Pune 1-1 R-L 20537001

1	Н	Between	5.5 to 9
2	Suspended Solids	Not to exceed	100 mg/l
- 3	BOD 3 days 27 Deg. C	Not to exceed	100 mg/l
-1	COD	Not to exceed	250 mg/l
้อั	Oil & Grease	Not to exceed	10 mg/l
б	T.D.S.	Not to exceed	2100 mg/l
7	Sulphates	Not to exceed	1000 mg/l
-8	Chlorides	Not to exceed	600 mg/l

- Effluent Disposal: The treated effluent shall be recycled / reused to the maximum extent in the process and rest shall be used for irrigation within factory premises only. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100 mg/l.
-1	BOD 3 days 27o.C.	Not to exceed	100 mg/l.

- Sewage Effluent Disposal: The treated sewage effluent shall be soaked into soak pit which should be got cleaned periodically. Overflow, if any be used on land for gardening only within factory premises only.
- vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Waste	Quantity	UOM	Treatment	Disposal
1	ETP Sludg	e 5:00	MT/A		Used as
		4.14			mannure

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutcha pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, non-lifting of molasses etc.
- Which area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near the tank.

- contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- with the industry should monitor effluent quality regularly.

5. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

or Domestic purpose

100.00 CMD

Water gets Polluted &

Pollutants are Biodegradable ...

400.00 CMD

(iii) Water gets Polluted, Pollutants...

are not Biodegradable & Toxic ...

0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

300.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

i) ESP/ Wet scrubber of sufficient capacity shall be provided to bagasse fired boiler.

ni)Bag Filter/ Ventury scrubber/ Dust collector of sufficient capacity shall be provided to sugar bagging section.

b) Standards for Stack Emissions:

1) SPM

Not to exceed

150 mg/Nm3

2) SQ2

Not to exceed

1.5 T/Day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Bagasse	45180	MT/M
2	Diesel	80.00	Lit./Hr

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.		
1	Boiler(1&2)	40.00		
2	Boiler(3&4)	60.00		
3	DG Set (500 KVA)	4.00*		

(* above the roof of the building in which it is installed)

(iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/displayed to facilitate identification.

The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

7. CREP conditions for Sugar Factory:

A Water Management:

- Operation of ETP shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
- Waste water generation shall be reduced to 100 litres per tone of cane crushed.
- iii. Industry shall achieve zero discharge into in land surface water bodies.
- 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.
- (B) Emission Control: ESP/Bag filter/Venture scrubber shall be installed to comply with standards for particulate matter emission to < 150 mg/Nm3.

8. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- t. D.G. Set shall be operated only in case of power failure
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

9. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No	Ty	pe Of	Waste	Quantity	7	UOM		Disposal	
1	5.1	Used	/spent	5.00		Kg/Day		Mix with bags	asse &
į į	oil				1		1 1 1	Burn in own h	- 1

- Treatment: -
 - Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

10. General Conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities tor disposal to dumping ground.
- The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- The applicant shall not change or alter quantity, quality, the rate of discharge, tomperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Ni. Separate drainage system shall be provided for collection of trade and sewage effluents.
- xii. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xiii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 11. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the applicant.

- 12. The industry shall not take any effective steps for implementation of the project before obtaining Environmental Clearance as per EIA Notification, 2006 and Amendments thereto.
- 13. This Consent is issued pursuant to the decision of the Consent Appraisal Committee meeting of the Board held on 25/07/2012.
- 14. The Capital Investment of the industry is Rs. 129.00 Crs. (The total C.I of the Industry including the Exiting Sugar unit and Distillery unit is Rs.274.08Crs.)

For and on Behalf of the Maharashtra Pollution Control Board,

(Milind Mhaiskar) Member Secretary

To.

M.s. Karmayogi Shankarraoji Patil SSK Ltd (Sugar Expan. & Cogen) Mahatma Phulenagar (Bijwadi), Tal- Indapur, Dist-Pune Pune -413106

Copy to: RO, MPCB, SRO, MPCB, Pune-I: - They are directed to ensure the compliance of consent conditions.

CAO Cess Branch / Master File.

Received Consent fee of -

Sr. No. Amount(Rs.)	DD. No.	Date	Drawn On
1 258000/-	940657	01 Feb 2012	Bank of Maharashtra