# MAHARASHTRA POLLUTION CONTROL BOARD

Firene: 24010437/24014701/24020781

: 24024068/24023516 Website: http://mpcb.gov.in. E-Mail: idair@mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8, Opp. Sion Circle, Sion (East). Mumbai-400 022.

RED/LSI

Consent No. BO/JD(APC)/ EIC No. EIC No.NG-7136-12/R/CC/

MPCB/201210910064 Date 07 /09 /2011.

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution ) Acc 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management Handling & Transboundary Movement) Rules, 2008.

[To be referred as Water Act, Air Act and HW (MH & TM) Rules respectively].

CONSENT is hereby granted to

M/s Ordnance Factory, Ambajhari,

Dist-Nagpur.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(MH&TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to - 31.05.2013.

seent is valid for the manufacture of -

The Conse	nt is valid for the mandiacture of -	and the second s
Sr. No.	Product	Maximum Quantity
1	Defence Units	

#### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 5500.0 m<sup>3</sup>
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 500.0 m<sup>3</sup>
- (iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the qualit, of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	BOD 3 days 27 deg C	Not to exceed	100 mg/l
3	COD	Not to exceed	250 mg/l
4	Suspended solids	Not to exceed	100 mg/l
5	Oil & Grease	Not to exceed	10 mg/l
6	Sulphates	Not to exceed	1000 mg/l.
7	Chlorides	Not to exceed	600 mg/L
8	TDS	Not to exceed	2100 mg/l
9	Lead	Not to exceed	0.1 mg/l
10	Mercury	Not to exceed	0.01 mg/l
11	Zinc	Not to exceed	5.0 mg/l
12	Cyanide	Not to exceed	0.2 nig/l

- (iv) Trade Effluent Disposal: The treated effluent shall be reused/recycled in the process completely. Indsutry shall achieve the zero discharge by Oct-2013. There shall not be any discharge outside the factory premises.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment warranted with reference to influent quality operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27° C.	Not to exceed	100	mg/l.

#### General conditions: 8.

- The applicant shall bring minimum 33% of the available open land under green coverage: (i) plantation. The applicant shall submit a yearly statement by 30th September every year or available open plot area, no. of trees surviving as on 31st March of the year and no. on trees. planted by September end.
- The applicant shall provide for an alternate electric power source sufficient to operate as (ii) pollution control facilities installed by he appl cant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- The applicant shall make an application for renewal of the consent at least 60 days (iii) before the date of the expiry of the consent. The applicant shall not change or after quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- The firm shall submit MPCB, the Environmental Statement Report for the financial year (iv)ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September even year.
- The applicant shall install a separate meter showing the consumption of energy to: (V) operation of domestic and industrial effluent treatment plants and air pollution contro system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along witi Environmental statement.
- Separate drainage system shall be provided for collection of trade and sewage efficients (vi)Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- The applicant shall provide facility for collection of environmental samples and samples of (vii) trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officer. during their visit to the applicant.
- The industry shall ensure that fugitive emissions from the activity are controlled so as to (viii) maintain clean and safe environment in and around the factory premises.
- The applicant shall maintain good house keeping and take adequate measures for control of (ix)pollution from all sources so as not to cause nuisance to surrounding area / inhabitants
- This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- This is issued pursuant to the decision of Consent Appraisal Committee meeting or 10. the Board held on 21st August 2012.

(ii) The applicant shall observe the following fuel pattern:-

1110	, αρρίισα	In Shah ender to		
	S No.	Type of Fuel	Quantity	
i i			1910 Lit/day	
	1	LDO	1210 Lit/day	ì
!	• •	1.00		

(iii) The applicant shall erect the chimney(s) of the following specifications:-

S Ño.		Chimneys attached to	Height in Mtrs.	
	1.	Boiler -4 Nos.	30.0 each	
	2.	Furnace	20.0	
	3.	DG sets (1 x 63 KVA)	2.0 *	
	9	DG set (1x52 KVA)	2.0*	

(\* Above roof top of the building in which it is installed)

(iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted /displayed to facilitate identification.

The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during hight time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

1) The industry should not cause any nuisance in surrounding area.

2) The industry should monitor stack emissions and ambient air quality regularly.

# €. CONDITIONS UNDER HAZARDOUS WASTE (MH &TM) RULES, 2008:

i)The appl	licant shall handle hazardous wast	e as specified b	elow:-
Sr. No.	Type of HW	QTY.	Disposal
1	5.1 Spent/used oil	55 Mt/Year	By sale to authorized reprocesor/recycler
2	34.3 Chamical sludge from waste water treatment	3.65 MT/Year	CHWTSDF,Butibori
3	33.3 Discarded Containers /barrels/Liners contaminated with hazardous	Irrespective of any quantum	By sale to authorized reprocesor/recycler
3	/barrels/Liners contaminated	of any	

(ii) Treatment: - NIL

(iii) The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

(iv) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008.

(v) The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

(vi) It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management, Handling & Transboundry Movement) Rules, 2008 and shown & submitted to the Board as & when asked for.

7. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

- (vi) Sewage Effluent Disposal: The treated effluent shall be reused/recycled in the process completely. Industry shall achieve the zero discharge by Oct-2013. There shall not be any discharge outside the factory premises.
  - (vii) Non-Hazardous Solid Wastes: Nil

(viii) Other conditions: The industry shall monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under: The daily

water consumption for the following categories is as under:

Water consumption for the remaining	
Domestic	4800.0 CMD
Industrial processing generating Bio-	2500.0 CMD
Degradable waste water	en de la companya de La companya de la co
Industrial processing generating Non-	1430.0 CMD
Bio-Degradable waste water	
Industrial Boiler/Cooling etc.	250.0 CMD
Any other and gardening/firfighting	CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

## 5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

#### A) Control Equipment:

- (i) Fume extraction system followed by Dust collection system provided to any other sources of emission, shall be operate and maintain properly so as to achieve following air emission standards.
- (ii) There shall not any secondary (fugitive) emissions.

#### B) Conditions for D.G. Set:-

1] Noise from the D.G. Set should be controlled by providing an acoustic enclosure by treating the room acoustically.2] Incustry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

3] The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.4]Industry—should—make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.5]Installation of DC Set much be strictly in compliance with recommendations of DG Set manufactures.6] A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use. 7] D.G. Set shall be operated only in case of power failure.8] The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

## ©) Standards for Emissions of Air Pollutants:

i) The applicant shall observe the following fuel pattern:-

1	i	SPM TPM	Not to exceed	150	mg/Nm³
	11	SO2	Not to exceed	24.0	Kg/day

- 11. The applicant shall achieve the zero discharge by October-2013.
- The applicant shall submit the irrevocable bank guarantee of Rs.2.0/- Lacs drawn in favour of RO MPCB Nagpur within 15 days valid for one year period, towards operation and maintenance of Pollution Control system so as to achieve the standards prescribed in the consent and not to discharge treated effluent outside factory premises.
- 13. The total capital investment of industry is Rs.365.54/- Crore.

For and On Behalf of the Maharashtra Pollution Control Board

(Rajeev Kumar Mital,IAS) Member Secretary

To, M/s Ordnance Factory, Ambajhari, Dist-Nagpur.

Copy to:

1) Regional Officer, MPCB, Nagpur 2) Sub-Regional Officer, MPCB, Nagpur-II.

They are directed to forfeit the existing BG of Rs.50,000/- of the industry due to non-compliance of interim directions and consent conditions and obtain the tresh BG of Rs.2.0/- Lacs from the industry as per consent condition no. 12 and submit the performance report along with monitoring results within one month period and ensure the compliance of consent conditions.

3) Chief Accounts Officer, MPCB, Mumbai.

Received Consent fee of -

<u>Amount</u> <u>D.D.No.</u> <u>Date</u> <u>Drawn on</u> Rs.18,27,740/- 250958 19.04.2012 UCO Bank

4) Cess Branch, MPCB.