MAHARASHATRA POLLITION CONTROL BOARD

4010437/4020781

/4037124/4035273

24044532/4024068 /4023516



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

Mumbai - 400 022

enquiry@mpcb.gov.in Email

Phone :

Fax

Red/M.S.I/Recycler

Consent No: BO/MPCB/RO(HQ)/Kalyan /CE/B/CC-S71 Date: 10/09/2012

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules i nectively].

CONSENT is hereby granted to

M/s. Monarch Catalyst Pvt Lt A-94, F-1/2, MIDC Phase-I Dombivali (E), Thane-421203

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Establish is granted for a period up to Commissioning of 1. the Unit or 5 years whichever is earlier

[Subject to obtaining registration from MPCB as Non-ferrous Metal Waste reprocessor as per the provisions of HW (MH&TM) Rules, 2008]

is valid for the manufacture of -

$\frac{1. \text{ In}}{\text{Sr.}}$	Product Name	Maximum Quantity	
No.			
	Nickel Catalyst	600 MT/A	
		180 MT/A	
	Activated Alloy	24 MT/A	
3	Precious Metal Catalyst	1794 MT/A	
4	Sodium acuminate solution	24 MT/A	
5	Nickel Aluminum Alloy	1356 MT/A	
6	Aluminum Tryhdrate	12 MT/A	
7	Monolites (Zeolites)	12 MT/A	
8	Monolphos (Aluminophospahtes)		
9	Silver Chemicals	12 MT/A	

2. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 67.00 M³. (ii) The daily quantity of sewage effluent from the factory shall not exceed 3.00 M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

r				5.5 to 9.0
		-11	Retween	0.0 10 11
1		oH	Should not exceed 5 c	
2		Temperature	above the ambient	<i>4</i>
			temperature of the	
			receiving body	
			Not to exceed	10 mg/1
3		Oil & Grease	Not to exceed	100°mg/L
4		Suspended Solids	Not to exceed	0.2 mg/l.
5		Cyanide (as 'CN')	Not to exceed	50 mg/l.
6		Ammonical nitrogen (as N)	Not to exceed	1.0 mg/l.
7		Total residual chlorine (as Cl2)	Not to exceed	2.0 mg/l
8		Cadmium (as Cd)	Not to exceed	3.0 mg/l
$\frac{1}{9}$		Nickel (as Ni)	Not to exceed	5.0 mg/l
	0	Zinc (as Zn)	Not to exceed	0.1 mg/l.
	.1	Chromium as Cr Hexavalent	Not to exceed	
1	. 1	Total	Welling welling	3.0 mg/l.
	2	Copper (as Cu)	Not to exceed	0.1 mg/l.
	$\frac{12}{13}$	Lead (as Pb)	Not to exceed	3.0 mg/l.
	$\frac{13}{14}$	Iron (as Fe)	Not to exceed	10.0 mg/l.
		Total metal	Not to exceed	10.0 116/1
	15	Total motal	149 - Carl	

- (iv) Trade Effluent Disposal. The metal bearing industrial effluent shall be segregated and reused back into process and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises. The industry shall become member of CETP as and when proposed. Industry shall provide necessary facilities to recycle the entire industrial effluent back into the process in six months.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1) Suspended Solida (2) BOD 3 days 270 C. Not to exceed 100 mg/	 Suspended Solids BOD 3 days 270 C. 	Not to exceed Not to exceed		mg/l. mg/l.
---	---	--------------------------------	--	----------------

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

Solid Wastes:

(vii) N	on-Hazardous Solid W	astes.		Disposal	
Sr. N	Type Of Waste		Quantity 26 MT/A	Sale to scrap dealer a	f
1	Bags			decontamination	
2.	Liners		9.6 MT/A	1	
3.	Paper Bags		9.0 WIT/A		

		480 MT/A	Disposal for bricks n	nakı
4.	Coal dust	30 MT	& land filling]
5	Fly ash	<u> </u>		

(viii)Other Conditions: Industry should monitor effluent quality regularly.

3. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

5.00 CMD

100.00 CMD

0.00 CMD

- (i) Domestic purpose (ii) Water gets Polluted &
- Pollutants are Biodegradable ... (iii) Water gets Polluted, Pollutants
- are not Biodegradable & Toxic ... (iv) Industrial Cooling, spraying

0.60CMD in mine pits or boiler feed The applicant shall regularly submit to the Board the returns of water ... as specified under consumption in the prescribed form and pay the Cess Section 3 of the said Act.

CONDITIONS UNDER AIR ACT : 5.

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to (i) generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment: a.

Industry shall provide filter bag house dust collector of sufficient capacity to control the emissions.

Conditions for D.G. Set:-

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be The measurement of insertion loss will be done at provided. different points at 0.5 meters from acoustic enclosure/room and then average.
 - The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- A proper routine and preventive maintenance procedure for DG set f. should be set and followed in consultation with the DG

manufacturer which would help to prevent noise levels of DG set from deteriorating with use

- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding
- area due to operation of D.G. Set

Standa (i)	(1) SP W/ 11 W Not to	o exceed 50 mg/Nm ³ o exceed 129 Kg/Day to exceed 10 mg/Nm ³ ng fuel pattern:-
Sr. No. 1. 2. 3.	Type Of FuelQuantityCoal6.0HSD5000LPG25,000	UOM Ton/day Lit/Month Kg/M
(ii)	The applicant shall erect the chin specifications:-	
Sr. No. 1. 2. 3. 4. 5. 6. 7. 8.	Chimney Attached To Scrubber (SC 101/103)-CH-10 Incinerator (FUR-801)-CH-10 Spin flash drier Gas preherter (H 302/307)-CH-301 Scrubber (SC-501/502) -CH-501 Incinerator Coal fired boiler (SG0501)-CH-601 Thermopac boiler (TH-601/602)-CH-60 DG Set (CH-601/602/603) CH-603	Height in Mtrs. 20 Mtrs 10.00 Mtrs 10.00 Mtrs 20.00 Mtrs 18.00 Mtrs 18.00 Mtrs 30.00 mtrs 2 18.00 mtrs 18.00 mtrs 18.00 mtrs

The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

1. The industry is hereby permitted to accept 2000 MT/A spent Nickel catalyst containing nickel and 120 MT/A of spent catalyst containing noble metal subject to following :

- The industry shall transport hazardous waste through MPCB authorized (i)
- The industry shall follow manifest system strictly while transporting (ii)
- The industry shall inform the Board in its Form 4 returns regarding quantity (iii) acto accented by it during the year.

of hazardous	waste accepted by 10 m		manified helow
OI Hazar	Waste accepted of it in	wastes as	specified below.

	(iv)	The Indust	ry shall handle hazardous Type of waste	Quantity in Dispersion
Sr.	Category			MT/A
No.	Waste	as p		
		Sch.2	: Lue from	96 MT/A CHWTSDF
1.	-	B6	Process residue from	
1.			Nickel recovery	16.0 MT/A CHWTSDF
	010		ETP Sludge	16.0 MT/A CHWTSDF
2.	34.3	[-		
			Tank Bottom Sludge	1.2 MPCB Authorized
3.	3.3	-	Tank Bottom Shuge	recycler
_				1000 nos. MPCB authorized
	33.3	-	Discarded drums	Drum recycler.
4.	00.0			
		(ii) Truc	otment: - NIL	

Treatment: - NIL (ii)

- The authorization is hereby granted to operate a facility for collection, 1. storage, transport & disposal of hazardous waste.
- The industry should comply with the Hazardous Waste (M&H) Rules, 2. 2008.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.



Industry shall obtain registration from MPCB as Non Ferrous Metal Waste reprocessor having environmentally sound technology as per the provisions of Hazardous Waste (Management Handling & Transboundary Movement) Rules 2008.

- c. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- d. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste

(Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

7. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

- viif. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and

air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

Xi. Separate drainage system shall be provided for collection of trade and sewage effluents.Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

Neither storm water nor discharge from other premises shall be allowed to xii.

mix with the effluents from the factory.

- The Capital investment of the industry is Rs. 15 Crs (Expansion) + 44.44 Crs (Existing) = 59.44 crs (Total Investment) 8.
- This is issued subject to the decision taken in the 4th Consent Committee Meeting of the MPC Board held on dt: 30/05/2012 & 9. approval of Hon'ble Chairman of the MPC Board.

Member Secretary

To,

M/s. Monarch Catalyst Pvt Ltd A-94, F-1/2, MIDC Phase I, Dombivali (E), Thane-421203

Copy to:

1) Regional Officer, MPCB, Kalyan

2) Sub-Regional Office, MPCB, Kalyan-I

3) Chief Accounts Officer, MPCB, Mumbai. Received Consent fee of -

Received Cor		Date	Drawn On
	ount(ns.)	0.00/05/0011	Axis Bank
1 50,0	00010	20/07/0011	Axis Bank
2 50,	100/- 20012		