

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 2402 4068

Email : [jdwater@mpcb.gov.in](mailto:jdwater@mpcb.gov.in)

Visit At : <http://mpcb.gov.in>



Kapataru Point  
02<sup>nd</sup>, 03<sup>rd</sup> & 04<sup>th</sup> floor  
Opp. Cineplanet,  
Near Sion Circle, Sion (E),  
Mumbai- 400 022

Red/L.S.I

Date: 10/10/2012

Consent No: BO/JD (WPC)/PN-14749-12/R/CC/MPCB/2012/10/0170  
Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

CONSENT is hereby granted to

M/s. Brintons Carpet Asia(P)Ltd.  
G.No.414,415,416,Vill-Urawade,  
Tal-Mulshi, Pune-412108

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.12.2013.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Spinning of Yarn	261	MT/M
2	Dyed Yarn	175	MT/M
3	Weaving of Carpet	120000	Square Mtr./M

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 152.00 M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 54.00 M3.
- (iii) **Trade Effluent :**

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0	
2	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	30	mg/l.
4	COD	Not to exceed	250	mg/l.
5	Oil & Grease	Not to exceed	10	mg/l.
6	Chlorides	Not to exceed	600	mg/l.
7	Sulphates	Not to exceed	1000	mg/l.
8	T.D.S	Not to exceed	2100	mg/l.
9	Phenols	Not to exceed	1	mg/l.

(iv) **Trade Effluent Disposal:** The treated industrial effluent shall be recycled and reused to maximum extent and remaining shall be discharged on land for gardening and irrigation only. In no case effluent shall find its way in any land surface water, nalla, river of stream.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- |     |                   |               |     |       |
|-----|-------------------|---------------|-----|-------|
| (1) | Suspended Solids  | Not to exceed | 100 | mg/l. |
| (2) | BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	Sheared Fiber Waste	10.10	Ton/M	Authorized reprocessor/ scrap dealer
2	Waste paper cone	1000.00	Kg/M	Authorized reprocessor/ scrap dealer
3	Jacquard card (Hard Paper)	2.00	Ton/M	Authorized reprocessor/ scrap dealer
4	Broken glass Tubes	12.50	Kg/M	Authorized reprocessor/ scrap dealer
5	GI Wire	3.00	Ton/M	Authorized reprocessor/ scrap dealer
6	Yarn & Waster fiber	60.00	Ton/M	Authorized reprocessor/ scrap dealer
7	Carpet & Droplea waste	3.80	Ton/M	Authorized reprocessor/ scrap dealer
8	Clean Drum & carboys	117.00	No/M	Authorized reprocessor/ scrap dealer
9	Card Board	1.80	Ton/M	Authorized reprocessor/ scrap dealer
10	Card clothing	60.00	Kg/M	Authorized reprocessor/ scrap dealer
11	Wooden Pallet	4.40	Ton/M	Authorized reprocessor/ scrap dealer
12	MS Scrap	5.00	Ton/M	Authorized reprocessor/ scrap dealer
13	Plastic	757.00	Kg/M	Authorized reprocessor/ scrap dealer

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

**4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

- (i) Domestic purpose ... 60.00 CMD
- (ii) Water gets Polluted & Pollutants are Biodegradable ... 201.00 CMD
- (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ... 0.00 CMD
- (iv) Industrial Cooling, spraying in mine pits or boiler feed ... 37.50 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**5. CONDITIONS UNDER AIR ACT :**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
  - a. **Control Equipment:** Industry shall operate and maintain dust collector of sufficient capacity to control the emissions.

**6. Standards for Stack Emissions:**

- (i) SPM Not to exceed 150 mg/Nm<sup>3</sup>.
- (ii) SO<sub>2</sub> Not to exceed 900 kg/day
- (iii) SO<sub>2</sub> from process Not to exceed 50 ppm

(i) **The applicant shall observe the following fuel pattern:**

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	14.20	KL/D
2	HSD	6.10	KL/D

(ii) **The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler 4 TPH & Boiler 6 TPH	37.00
2	DG Set (380 KVA X 2 Nos.)	5.50 *
3	DG Set (380 KVA)	5.50 *
4	Latex Steamer	10.00
5	Latex Dryer	10.00
6	Dryer (Seller)	10.00
7	Dryer (Galvanin)	10.00

(\* above the roof of the building in which it is installed)

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

**7. Conditions for D.G. Set**

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f. D.G. Set shall be operated only in case of power failure
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

**8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:**

(i) The Industry shall handle hazardous wastes as specified below.

(ii)

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	23.1 Waste Residue	3.70	MT/M	CHWTSDF Ranjangaon
2	24.1 Textile chemical residues	18.50	Kg/M	CHWTSDF Ranjangaon
3	24.2 Chemical sludge from waste water treatment	19.00	MT/M	CHWTSDF Ranjangaon
4	33.2 Sludge from treatment of waste water	35.00	Kg/M	CHWTSDF Ranjangaon
5	33.3 Discarded containers / barrels / liners	116.00	Nos./M	CHWTSDF Ranjangaon
6	5.1 Used /spent oil	57.00	Ltrs./M	Auth. reprocessor
7	5.1 Used /spent oil	146.00	Kg/M	Auth. reprocessor
8	34.1 Flue gas cleaning residue*	60.00	Kg/M	CHWTSDF Ranjangaon
9	Used batteries	4.0	Nos./Y	Auth. reprocessor

**9. Industry shall comply with following additional conditions:**

- (i) The applicant should bring minimum 33% of the available open land under green coverage/ plantation. The applicant should submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant should provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant should stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- (iii) The applicant should make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant should not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm should submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- (v) The applicant should install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment should be maintained. The applicant should also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- (vi) Separate drainage system should be provided for collection of trade and sewage effluents. Terminal manholes should be provided at the end of collection system with arrangement for measuring the flow. No effluent should be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent should find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises should be allowed to mix with the effluents from the factory.
- (vii) The applicant should provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and should pay to the Board for the services rendered in this behalf. An inspection book should be opened and made available to the Board's officers during their visit to the applicant.
- (viii) The industry should ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant should maintain good house keeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

- (vii) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
10. The Industry shall comply with the hazardous Waste (Management, Handling & Trans Boundary Movement) Rules, 2008.
11. **The consent is issued with the overriding effect to the Consent No. BO/JD (WPC)/PN-8722-11/R/CC-CAC-91, Dt. 22/12/2011.**
12. The consent is issued pursuant to the decision of the Consent Appraisal Committee meeting held on dt.26/09/2012.
10. The Capital investment of the industry is Rs. 110.84 Crore. (C.I as per the consent referred at Sr. No. 11 is Rs. 102.13 Crs and C.I of the Expansion is Rs.8.57Crs.)

For and on Behalf of the  
Maharashtra Pollution Control Board,

  
(Rajeev Kumar Mital)  
Member Secretary

To,  
Brintons Carpet Asia(P)Ltd.  
G.No.414,415,416,Vill-Urawade,Tal-Mulshi.  
Pune -412108

Copy to:  
RO-Pune /SRO- Pune-II / CAO / Cess Branch / Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	50000	000040	13/06/2012	HDFC Bank

\* Received Consent fees as per Consent No. BO/JD(WPC)/PN-8722-11/R/CC-CAC-91, Dt. 22/12/2011 of:-

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	102139	021306	01/11/2010	HDFC Bank
2	60000	021982	06/01/2011	HDFC Bank
3	204278	022225	27/01/2011	HDFC Bank
4	240459	025426	01/12/2011	HDFC Bank