

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 2402 4068

Email : jdwater@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Kapataru Point
02nd, 03rd & 04th floor
Opp. Cineplanet,
Near Sion Circle, Sion (E),
Mumbai- 400 022

Red/L.S.I

Date: 09/10/2012

Consent No: BO/JD (WPC)/EIC-PN-11091-11/O/CC-CAC/MP(B)/2012/10/0122

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

.....
CONSENT is hereby granted to

M/s. Cadbury India Ltd.
Gat No. 532 & 533, Induri, Talegaon Dabhade
Pune, Maharashtra
Pune-410507

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.03.2013.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Milk Crumb, Chocolate and Confectionary	2537 (Exiting 1820 MT/M + Expansion 717 MT/M)	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 500.00M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 16.00M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l
3	BOD 3 days 27 Deg. C.	Not to exceed	30 mg/l
4	COD	Not to exceed	250 mg/l
5	Oil & Grease	Not to exceed	10 mg/l
6	T.D.S	Not to exceed	2100 mg/l
7	Chlorides	Not to exceed	600 mg/l
8	Sulphates	Not to exceed	1000 mg/l

(iv) **Trade Effluent Disposal:** The treated industrial effluent shall be recycled/ reused to the maximum extent and remaining shall be used on land for gardening only. In no case, at any time effluent shall find its way to any water body directly or indirectly.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment / Disposal
1	Corrugated boxes, outers, sugar bags, jumbo bags, plastic bags, PVS core, empty drums / cans, brocken plastic moulds, empty tins, aluminium foil, paper waste	45.00	MT/M	By Sale
2	Floor spillages (food waste)	8.00	MT/M	Mixed and converted in slurry & put into ETP
3	Bagasse boiler ash	28.00	MT/M	Sale to brick mfg
4	ETP biological sludge	0.80	MT/M	Use as manure
5	Fatty material from fat trap scum	0.47	MT/M	Dried and used in Boiler
6	Incinerator Ash (paper waste only)	0.1	MT/M	Land fill along with bagasse ash
7	Canteen waste	1.20	MT/M	Given to piggery farms

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i)	Domestic purpose	...	20.00 CMD
(ii)	Water gets Polluted & Pollutants are Biodegradable	...	480.00 CMD
(iii)	Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iv)	Industrial Cooling, spraying in mine pits or boiler feed	...	200.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

- a. **Control Equipment:** Industry shall provide ESP/ Bag Filter/ Venturi Scrubber /dust collector of sufficient capacity to bagasse fired boiler to control the emissions.

b. Standards for Emission of Air Pollutants:

- | | | | |
|------|--------------------------------|---------------|--------------------------|
| i. | SPM | Not to Exceed | 150 mg/Nm ³ . |
| ii. | SO ₂ | Not to Exceed | 37 Kg/Day. |
| iii. | SO ₂ (From Process) | Not to Exceed | 50 ppm. |

6. Standards for Stack Emissions:

- (i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	425.00	Kg/Hr
2	HSD	340.00	Ltr./Hr
3	Bagasse	1.46	MT/Hr

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler 1 (Bagasse / Briquette fired boiler), Boiler 2 (FO fired) Common Stack	44.00
2	DG Set (1000 KVA)	10.00*
3	DG Set (1000 KVA)	10.00*
4	DG Set (500 KVA)	10.00*
5	Incinerator	30.00

(* above the roof of the building in which it is installed)

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) **Other Conditions:**
- 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality Regularly.

7. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f. D.G. Set shall be operated only in case of power failure
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	5.1 Used /spent oil	135.00	Ltrs/M	Burnt in bagasse boiler
2	5.2 Wastes/residue containing oil	13.00	Kg/M	CHWTSDF Ranjangaon
3	5.2 Wastes/residue containing oil	10.00	Kg/M	Burnt in bagasse boiler
4	33.3 Discarded containers / barrels / liners	1.00	Drum/M	To authorized reprocessor
5	33.3 Discarded containers / barrels / liners	10.00	Kg/M	CHWTSDF Ranjangaon
6	31.1 Residues and wastes*	15.00	Kg/M	To authorized reprocessor

- (ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.


- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

9. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
 - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
 - iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
 - iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
 - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
 - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
 - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
 - viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
 - ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
 - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
 - xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
 - xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
10. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the applicant.
11. The Industry shall comply with the hazardous Waste (Management, Handling & Trans Boundary Movement) Rules, 2008.

12. This Consent is issued pursuant to the 'No Increase in Pollution Load' report, submitted by the industry vide letter no. ICT/CE/BNT/101, certified by Professor of U.I.C.T, Mumbai.
13. Industry shall submit the Bank Guarantee of Rs. 5.0 Lakhs to maintain the pollution load. The Bank Guarantee shall be submitted within 15 days at Regional Office Pune.
14. This consent is issued with the overriding effect to the consent granted by the Board vide Consent No. MPCB/PCI-III/EIC-PN-2397-08/CC-231, dt. 01.08.2008.
15. The Consent is issued pursuant to the decision of the Consent Appraisal Committee meeting of the Board held on 26/09/2012.
16. The Capital investment of the Unit is Rs. 106.64 Cr. (Rs.102.5 Cr+ Rs.4.15Cr) (Total C.I of the Industry is Rs.270.10 Crs).

For and on Behalf of the
Maharashtra Pollution Control Board,


(Rajeev Kumar Mital)
Member Secretary

To,
M/s. Cadbury India Ltd.
Gat No. 532 & 533, Induri, Talegaon Dabhade
Pune -410507

Copy to: RO, MPCB, Pune – RO to monitor regarding the condition of No Increase in pollution load mentioned in the report as per the consent committee decision.

SRO, MPCB, Pune -II – They are directed to collect the Bank Guarantee of Rs. 5.0 Lakhs from industry within 15 days and ensure the compliance of consent conditions.

CAO / Cess Branch/ Master File

Received Consent fee of –

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	15100/-	401667	12 Jun 2012	Royal Bank Of Scotland
Received Consent fee as per consent No. MPCB/PCI-III/EIC-PN-2397-08/CC-231, dt. 01.08.2008				
2	512625/-	327490	22 Feb 2008	ABN Amro bank