MAHARASHTRA POLLUTION CONTROL BOARD

Phone: 24010437/24014701/24020781 : 24024068/24023516 Fax Website: http://mpcb.gov.in. E-Mail: idair@mpcb.gov.in



KALPATARU POINT, 3rd Floor, Sion-Matunga Scheme Rd. No.8, Opp. Sion Circle, Sion (East), Mumbai-400 022.

RED/LSI

Consent No. BO/JD(APC)/ EIC No.NG-7507-12/R/CC/CAC-635 DateO9/10/2012 Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management Handling & Transboundary Movement) Rules, 2008. [To be referred as Water Act, Air Act and HW (MH & TM) Rules respectively].

CONSENT is hereby granted to

M/s. TAL Manufacturing Solutions Limited, Sector 3, Survey No. 215(Part) to 225 (Part) & 227 (Part) to 229 (Part) Village-Kalkuhi, MIHAN SEZ, Nagpur (Rural)-441108

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(MH&TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions

The Consent to Operate is granted for a period up to - 31.08.2013. 1.

The Consent is valid for the manufacture of -2.

	Product	Maximum Quantity
1	Aerospace Assemblies & Sub-assemblies (composites, sheet metal, metals & metal alloys)	500 Nos/Month
2	Aerospace Components (precision machined metal, composite & sheet metal components)	50.000 Nos/Month

CONDITIONS UNDER WATER ACT: 3.

- The daily quantity of trade effluent from the factory shall not exceed 152.0 m^3 (i)
- The daily quantity of sewage effluent from the factory shall not exceed 25.6 m³. (ii)
- Trade Effluent Treatment: The applicant shall provide comprehensive treatment system (iii) consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1)	pH	Between	5.5 to 9.0
2)	Suspended Solids	Not to exceed	100 mg/l.
3)	BOD 3 days 27°C	Not to exceed	100 mg/l.
4)	COD	Not to exceed	250 mg/l.
5)	Oil & Grease	Not to exceed	10 mg/l.
6)	TDS	Not to exceed	2100 mg/l.
7)	Nitrate as N	Not to exceed	10 mg/l.
8)	Phosphate as P	Not to exceed	05 mg/l.
9)	Fluoride as F	Not to exceed	10 nmg/l.

Trade Effluent Disposal: The treated effluent shall be reused/recycle to the maximum (iv)extent and remaining shall be used on land for gardening /plantation within own premises only

Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system (v)operate and as is warranted with reference to influent quality and maintain the same continuously so as to achieve the quality of treated effluent to the following standards. 400 (

(1) Suspended Solids Not to exceed	Çi	mg/i.
(2) BOD 3 days 27° C. Not to exceed	d 100	mg/l.

Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pill (vi)which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

:2:

11.1.181--4-0

(vii)	Non-Haz	ardous Solid Wastes: Type of waste	Quantity	Disposal
	1 2	Titanium Scrap Aluminium Scrap Composite Material Scrap	12 MT/M 17 MT/M	By sale By Sale
	3	 3.1 Scrap for Carbon UD Tapes t 3.2 Scrap for Carbon Fabric t 3.3 Scrap for Glass Fabric t 3.4 Scrap for Adhesive Film 3.5 Scrap for Bagging Film 3.6 Scrap for Breather 3.7 Scrap for Release Film 3.8 Scrap for Sealant Tape 	5.668 MT/M 0.183 MT/M 0.360 MT/M 0.415 MT/M 0.600 MT/M 2.304 MT/M 0.506 MT/M 0.138 MT/M 5.0 MT/M	By Sale By Sale By Sale By Sale By Sale By Sale By Sale By Sale By Sale
	4 5	Wooden Scrap Empty drums/carbuoys/cardboards	50 Nos/Month	By sale

boxes/plastic packing boxes

- The industry shall monitor effluent quality regularly. Other conditions:
- The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and Rules there under: The daily water consumption for the 4.

following categories is as under:	the second se
Domestic	32.0 CMD
Industrial processing generating Bio-	116.0 CMD
Degradable waste water	
Industrial processing generating Non-Bio-	CMD
Degradable waste water	
Industrial Boiler/Cooling etc.	480.0 CMD
Any other and gardening.	32.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR ACT: 5.

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the (i)same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment: A)

B)

- Bag filter of adequate capacity shall be provided to shot peening machine & abrasive i) blasting machine separately.
 - Scrubbers of adequate capacity shall be provided to tank line cleaning plant to control ii) the acidic/alkaline fumes.
 - Water curtain with baffle plates shall be provided to paint to limit the emission.
- Fume extraction system followed by dust collector of sufficient capacity shall be iii) provided to all sources of SPM/TPM so as to achieve the following standards. iv)
- v) There shall not any secondary (fugitive) emissions.

Standards for Emissions of Air Pollutants:

- 150 mg/Nm³ Not to exceed SPM/TPM (i)
 - 140 kg/day Not to exceed SO₂
- (ii)The applicant shall observe the following fuel pattern:-(iii)
 - Quantity. Type of Fuel Sr.No. 7.0 KL/ Day. HSD The applicant shall erect the chimney(s) of the following specifications:-1
- (iv)Height in Mtrs.
 - Chimney attached to Sr.No. 1.
 - 30 mtr above ground level Hot Water Generator 9.2 * mtr each
 - 2.
- D. G. Set (2100 KVA) (3 Nos)
 - (* above the roof height where the DG set is installed)

Conditions for DG Sets: -(C)

- 1. Noise from DG Sets shall be controlled by providing acoustic enclosure or by treating the room acoustically.
- 2. Applicant should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room shall be designed for minimum 25 dB(A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB(A) shall also be provided. The measurement of insertion loss shall be done at different points at 0.5 meters from acoustic enclosure/ room and then average.

- :3:
- 3. The Applicant should make efforts to bring down noise level due to DG Set, outside the premises, with ambient noise level requirements by proper setting and control measures
- 4. Installation of DG Set must be strictly in compliance with recommendations of DG set manufacturer:
- 5. A proper routine and preventive maintenance procedure for DG Set shall be set and followed in consultation with the DG manufacturers, which would help to prevent noise levels of DG Sets from deteriorating with use.
- 6. The DG set shall be operated only in case of power failure. The applicant shall make arrangement for regular electrical power.
- 7. The Applicant shall not cause any nuisance in the surrounding area due to operation of DG
- 8. In case of problems, the D.G. set shall not be operated until it is set back to satisfactory position.
- The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc monitoring the air emissions and the same shall be open for inspection to/and for use of a (vi) Board's Staff. The chimney(s) vents attached to various sources of emission shall be designate by numbers such as S-1, S-2, etc. and these shall be painted /displayed to facility. identification.
- The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to least (vii) than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

Other Conditions: (vii)

6.

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

CONDITIONS UNDER HAZARDOUS WASTE (MH &TM) RULES, 2008:

all handle hazardous wastes as specified below:

(i) The	applicant shall ha	andle hazardous wastes as specified	Ouentitu	Disposal
Sr.	Item No.	Type of Waste	Quantity	Dispusar
No.	as per Sch-I	Chemical Sludge from	150 MT/year	CHWTSDF
1.	34.3	Chemical Sludge from wastewater treatment	100 Millyour	
		Paint wastes & residues	0.1 MT/Year	CHWTSDF
2	21.1		24.0 KL/Year	CPCB/MPCB
3.	5.1	Used/Spent Oil	24.0 1121100	Authorized reproces
		Wester Institutes constaining Oil	24.0 MT/year	CHWTSDF
4.	5.2	Wastes/residues constaining Oil (oil soaked material inclusive of used cotton waste,oil soaked saw dust & used oil filter	24.0 10 11 19 00.	
5	33.3	Discarded containers & barrels contamionated with hazardous waste and chemicals	240 Nos/Year	CPCB/MPCB authors recyclers/reprocession
6		Discarded batteries	150 Nos/year	Returned to origination battery manufacturer.
L		i i i i i i i i i i i i i i i i i i i	allity for collection	storage_transport &

The authorization is here by granted to operate a facility for collection, storage, transpor disposal of hazardous waste. (ii)

Whenever due to any accident or other unforeseen act or even, such emissions occur apprehended to occur in excess of standards laid down, such information shall be forthwith Reporte 7. Board, concerned Police Station, office of Directorate of Health Services. Department of Edu Inspectorate of Factories and Local Body. In case of failure of pollution control equipments production process connected to it shall be stopped.

General conditions: 8.

- (i) The applicant shall bring minimum 33% of the available open land under green coverage plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, no. of trees surviving as on 31st March of the year and no. of trees planted by September end.
- (ii) The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant and operate the same in case of power failure to maintain compliance with the terms and conditions of the consent. In the absence of same, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

- (iii) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent. The applicant shall not change or alter quantity, quality the rate of discharge, temperature or the mode of the effluent/ emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- (iv) The firm shall submit MPCB, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992 before 30th September every year.
- (v) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. The applicant shall also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- (vi) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- (vii) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal of designated points and shall pay to the Board for the services rendered in this behalf. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- (viii) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 11. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 12. This is issued pursuant to the decision of Consent Appraisal Committee meeting of the Board held on 24th September, 2012.
- 13. The applicant shall submit the irrevocable bank guarantee of Rs.5,00,000/- drawn in favour of Regional Office, MPCB, Nagpur within 15 days valid up to consent validity period i.e up is 31.08.2013, towards operation & maintenance of Pollution control system and to achieve consented standards
- 14. Total Capital Investment of the project is Rs.185.91/- crore.

For and On Behalf of the Maharashtra Pollution Control Board (Rajeev Kumár Mital, IAS) Member Sectetary

To,

M/s. TAL Manufacturing Solutions Limited, Sector 3, Survey No. 215(Part) to 225 (Part) & 227 (Part) to 229 (Part) Village-Kalkuhi, MIHAN SEZ, Nagpur (Rural)-441108 Copy to:

1) Regional Officer, MPCB, Nagpur 2) Sub-Regional Officer, MPCB, Nagpur-II.

They are directed to obtain the bank guarantee of Rs.5.0/- Lacs from the industry as per the consent conditions No.13 and submit the performance report along with the monitoring results and compliance of consent conditions within one month period.

3) Chief Accounts Officer, MPCB, Mumbai

Received Consent fee of -AmountD.D.No.DateDrawn onRs. 7,43,640/-11909529.06.2012HDFC Bank4) Cess Branch, MPC Board, Mumbai.5) Master file.