

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 2402 4068

Email : enquiry@mpcb.gov.in

Visit At <http://mpcb.gov.in>



Kapataru Point  
02<sup>nd</sup>, 03<sup>rd</sup> & 04<sup>th</sup> floor  
Opp. Cineplanet,  
Near Sion Circle, Sion(E),  
Mumbai- 400 022

05/11/2012

Date: ~~10/10/2012~~

Red/L.S.I

Consent No: BO/JD(WPC)EIC No. KP-8536-11/R/CC-694

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Mohanrao Shinde SSK Ltd,  
Mohannagar, A/p-Arag, Tal-Miraj  
Dist- Sangli, Maharashtra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 30/11/2014.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Sugar	7500	MT/M
2	Molasses	3000	MT/M
3	Bagasse	32200	MT/M
4	Pressmud	3000	MT/M
5	Electricity	15	MW

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 270M<sup>3</sup>.  
(i.e The effluent from Sugar industry should not exceed - 250 M<sup>3</sup>/day and Co- generation unit -20 M<sup>3</sup>/day)
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 38 M<sup>3</sup>.

#### (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Not to exceed	5.5 to 9.0
3	Suspended Solids	Not to exceed	100 mg/l.
4	BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
5	COD	Not to exceed	250 mg/l.

6	Oil & Grease	Not to exceed	10 mg/l.
7	TDS	Not to exceed	2100 mg/l.
8	Chlorides	Not to exceed	600 mg/l
9	Sulphate	Not to exceed	1000 mg/l

(iv) **Effluent Disposal:** The treated effluent shall be used on land for gardening within factory premises only. In no case, at any time effluent shall find its way to any water body directly or indirectly.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated effluent shall be recycled to the maximum extent and remaining shall be used on land for gardening.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Boiler Ash	481	MT/M		Sale to brick manufacturers

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

#### 4. CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- (ii) The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutch pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, non-lifting of molasses etc.
- (iii) All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- (iv) Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near the tank.
- (vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- (vii) The industry should monitor effluent quality regularly.

**5. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

(i) Domestic purpose	...	40.00 CMD
(ii) Water gets Polluted & Pollutants are Biodegradable	...	500.00 CMD
(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iv) Industrial Cooling, spraying in mine pits or boiler feed	...	250.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**6. CONDITIONS UNDER AIR ACT:**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**a) Control Equipment:**

ESP/Bag filter/Wet scrubber/Dust Collector of sufficient capacity provided to bagasse fired boiler shall be operated and maintained properly.

ESP/Bag filter/Wet scrubber/Dust Collector of sufficient capacity provided to sugar bagging section shall be operated and maintained properly.

**b) Standards for Stack Emissions:**

1) SPM	Not to exceed	150	mg/Nm <sup>3</sup>
2) So <sub>2</sub>	Not to exceed	3.5	T/Day

- (ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Bagasse	1760	MT /Day

- (iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Bagasse Fired Boiler I & II	60
2	DG Set (320 KVA)	3.5 *
3	DG Set (625 KVA)	4.5*

\*- above the roof in which it is installed.

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

**(vi) Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

- (iv) The applicant should install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment should be maintained. The applicant should also submit a comparative statement of designed power and chemical consumptions vis-a vis actual power and chemical consumption along with Environmental statement.
- (iv) Separate drainage system should be provided for collection of trade and sewage effluents. Terminal manholes should be provided at the end of collection system with arrangement for measuring the flow. No effluent should be admitted in the pipes/sewers down- stream of the terminal manholes. No effluent should find its way other than in designed and provided collection system. Neither storm water nor discharge from other premises should be allowed to mix with the effluents from the factory.
- (vii) The applicant should provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and should pay to the Board for the services rendered in this behalf. An inspection book should be opened and made available to the Board's officers during their visit to the applicant.
- (viii) The industry should ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- (ix) The applicant should maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
11. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
12. The industry shall submit the Bank Guarantee of Rs. 5.0 Lakh in favor of the Regional Officer, Kolhapur within 15 days period for Operation and Maintenance of ETP and Air pollution control devices so as to achieve the consented standards
13. The industry shall submit the Bank Guarantee of Rs. 2.0 Lakh in favor of the Regional Officer, Kolhapur within 15 days period for providing necessary arrangement to cover the effluent collection system and to avoid the ingress of bagasse and other materials within six months period
14. Total Capital investment of the industry is Rs. 80.10 Cr
15. This Consent is issued pursuant to the decision of the Consent Committee meeting of the Board held on 17.10.2012 and with approval of Hon'ble Chairman of the Board.

For and on Behalf of the  
Maharashtra Pollution Control Board,

  
(Rajeev Kumar Mital)  
Member Secretary

To,  
M/s. Mohanrao Shinde SSK Ltd,  
Mohannagar, A/p-Arag, Tal-Miraj  
Dist- Sangli, Maharashtra

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	225000	057723	25 Oct 2011	Bank of India
2	75000	057742	04 Nov 2011	Bank of India
3	250000	836988	19 July 2010	SBI
4	150000	732466	17 Feb 2012	SBI