MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 022-24020781,24014701 Fax 022-: 24023516,24093814



Kalpataru Point, 2nd - 4th Floor Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Email jdwater@mpcb.gov.in

Visit At : http://mpcb.gov.in

Red/L.S.I

12/00611 Date<mark>:7</mark>/11/2012 Consent No.BO/JD (WPC)/RO Nagpur NG-7775-12/ R/CQ-Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Natural Growers Pvt. Ltd. Lakhandur Mini Indutrial Area, Plot No. 251,262, 266,280-83, Revenue survey No.12/25, Vill- Kinhala

Tal- Lakhandur, Dist-Bhandara

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to:30.09.2013 2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum	UOM
		Quantity	
1	Crystal White Sugar	220	MT/M
BY Product			
2	Molasses	990	MT/M
3	Bagasse	900	MT/M
4	Filter Cake	891	MT/M

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed $49.2M^3$.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 34.60M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pН	Not to exceed	6.5 to 9.0
3	Suspended Solids	Not to exceed	100 mg/l.

1

4	BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
5	COD	Not to exceed	250mg/l.
6	Oil & Grease	Not to exceed	10 mg/l.
7	Chlorides	Not to exceed	600 mg/l.
8	Sulphates	Not to exceed	1000 mg/l

- (iv) **Trade Effluent Disposal:** The treated effluent shall be used on land for gardening within factory premises only. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be used on land for gardening.

(vii) Non-Hazardous Solid Wastes:

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. CONDITIONS FOR MOLASSES STORAGE:

- (i) The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- (ii) The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutcha pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, nonlifting of molasses etc.
- (iii)All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- (iv)Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board atleast 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- (v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tonnes shall be displayed prominently near the tank.
- (vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- (vii) The industry should monitor effluent quality regularly.

5. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose	•••	43.30 CMD
(ii) Water gets Polluted &		
Pollutants are Biodegradab	le	379.30 CMD
(iii) Water gets Polluted, Polluta		
are not Biodegradable & To	xic	32.90 CMD
(iv) Industrial Cooling, spraying	5	
in mine pits or boiler feed	•••	$140.60 \mathrm{CMD}$

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Wet scrubber of sufficient capacity provided to bagasse fired boiler shall be operated & maintained properly.

b) Standards for Stack Emissions:

1)	SPM	Not to exceed	150	mg/Nm3
2)	SO2	Not to exceed	250 Kg/	'day

(ii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Bagasse	180.00	MT/Day
2	HSD	35.00	Ltrs/hr

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler	30.00
2	D.G. Set	4.00

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality

standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

7. CREP conditions for Sugar Factory:

(A) Water Management:

- i. Operation of ETP shall be started at least one month before starting of cane crushing to achieve desired MLSS. So as to meet prescribed standards from day one the operation of mill.
- ii. Waste water generation shall be reduced to 100 litres per tone of cane crushed.
- iii. Industry shall achieve zero discharge into in land surface water bodies.
- iv. 15 days storage capacity tank shall be provided for treated effluent to take care of no demand for irrigation.
- (B) Emission Control: ESP/Bag filter/Venture scrubber shall be installed to comply with standards for particulate matter emission to < 150 mg/Nm3.

8. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 65 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

9. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

r. No.	Type Of Waste			Disposal
	5.1 Used /spent oil	0.024	MT/day	Collected oil used in bagasse
				/ cane carrier chain as lube oil
	(ii) Treatment: -			
1				o operate a facility for collection
	storage, transport &	-		
2	•	ld comply	with the	Hazardous Waste (M&H) Rules
	2003.			
	emissions occur o down, such inforn Police Station, of Explosives, Inspe	or is apprenation shall fice of Dir ctorate of I	hended to ll be forth ectorate o Factories	ther unforeseen act or even, suc o occur in excess of standards lai with Reported to Board, concerne of Health Services, Department of and Local Body. In case of failur production process connected to
10. I	ndustry shall comply v	with follow	ving addi	tional conditions:
і. Т	he applicant shall main	ntain good	housekee	ping and take adequate measure
fe	or control of pollution	from all	sources	so as not to cause nuisance t
	urrounding area / inhab			
ii. T	The applicant shall bring	g minimun	n 33% of tl	he available open land under gree
	overage/ tree plantation			
s p	weepings, etc., be dispo	osed of scie shall take	entifically	te arising in the factory premises so as not to cause any nuisance permissions from civic authoritie
o c a	perate all pollution compliance with the term	ntrol facili ms and con uce or othe	ties instanditions of terwise, co	electric power source sufficient t illed by he applicant to maintai f the consent. In the absence, th ntrol production to abide by term ion levels.
v. Т				tity, quality, the rate of discharge emissions or hazardous wastes of

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents.Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 11. Industry shall submit performance Bank Guarantee of Rs 5.0 lakhs towards Operation & Maintenance of Pollution Control devices so as to achieve the consented standards, & bank Guarantee of Rs 2.0 Lakhs towards providing necessary arrangements to cover the effluent collection system and to avoid the ingress of bagasse and other materials within six months. The Bank guarantees valid upto 30.09.2013, shall be submitted within 15 days at Regional Office Nagpur.
- 12. The consent is issued pursuant to the decision of Consent Committee meeting of Board held on02/11/2012.
- 13. The Capital investment of the industry is Rs. 30.00 Crores

(Rajeev Kun ital) Member

To,

M/s Natural Growers Pvt. Ltd. Lakhandur Mini Indutrial Area , Plot No. 251,262, 266,280- 83, Revenue survey No.12/25, Vill- Kinhala Tal- Lakhandur,Dist- Bhandara,

Copy to :- RO Nagpur/SRO Bhandara :- They are directed to obtain Bank Guarantees from industry & ensure compliance of consent conditions and report accordingly.

CAO/Cess wing/Master file. Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	75000	956787	06 Aug 2012	SBI Bank
2	100	040056	17 Sep 2012	Bank of
				Maharashtra