MAHARASHATRA POLLUTION CONTROL BOARD

022 -22640345

Fax

022-22640345

Email

mpcb@mpcb.gov.in

Visit At:

http://mpcb.gov.in

MAHARASHTRA

Kalpataru Point, 2nd - 4th Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022

MU-3515/12 Infrastructure/Orange/L.S.I Consent No. BO/RO(HQ)/CR/CAC- 715

Date:)3/9**2**/2012

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

.............

CONSENT is hereby granted to;

M/s City Corporation Ltd. S No 173 177 182 184 187 to 200, 242 to 245 Village Sadesatara nali & S No 111 113 to 121 Village Manjari Tal:- Haveli Dist:- Pune

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to 30/04/2014.

2. The consent is valid for

The commercial project named as "Amanora Park Town Project" of M/s. City Corporation Ltd., Amanora Park Town Project (Phase-I) S.No.173,177,182,184,187 to 200, 242 to 245, village Sadesatara nali and S.No. 111, 113 to 121, village Manjari, Tal- Haveli, Dist. Pune, on total plot area of 3,57,280.00 Sq mtrs and total built up area of 4,02,399.00 Sq mtrs including services and utilities as per occupation certificate issued by local body.

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall be Nil.

(ii) The daily quantity of sewage effluent from the factory shall not exceed 750.00M3.

(iii) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

| 1 | pН | Not to exceed | 6.5 to 9.0 |
|---|------------------------|---------------|-----------------|
| 3 | Suspended Solids | Not to exceed | 100 mg/l. |
| 4 | BOD 3 Days 27 degree C | Not to exceed | 100 mg/l. |
| 5 | Fecal Coliform | Not to exceed | 500/100/1 mg/l. |
| 6 | Residual Chlorine | Not to exceed | 01 mg/l. |
| 7 | Detergent | Not to exceed | 01 mg/l. |
| 8 | Floating matters | Not to exceed | 10 mg/l |

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners etc. In no case, effluent shall find its way to any water body directly/indirectly at any time. The firm shall affix the separate meter for ensurance of 80 % recycling of treated sewage and keep the records of the same.

Project proponent shall operate STP for five years from the date of obtaining Occupation Certificate.

(vii) Non-Hazardous Solid Wastes:

| Sr. N | Type Of Waste | Quantity | UOM | Treatment | Disposal |
|-------|-------------------------------|----------|--------|--------------------------------|---|
| 1 | Biodegradable Solid waste | 1.00 | MT/Day | On-site Bio- Methanation | Bio gas used in canteen as fuel and stabilized Bio-Solids used as manure. |
| 2 | Non-Biodegradable Sc waste | 0.90 | MT/Day | Segregation | Sale after segregation to M/s Rochem Separation System Pyt. Ltd., Pune |
| 3 | Inert | 0.90 | MT/Day | Segregation | Sale after segregation to M/s Rochem Separation System Pvt.Ltd., Pune |
| 4 | STP Sludge | 200.00 | Kg/Day | | Used as manure |

(viii) Other Conditions:

- 1. All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- 2. There shall be no felling of trees whether on Forest, Government, Revenue or Private lands except as per prevailing Rules.
- 3. Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable.
- 4. Near the activities that are related to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- 5. In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.
- 6. The Applicant shall prepare management plan for water harvesting, roof-water reclamation, water/storm water conservation and implement the same before handling over of complex for occupation.
- 7. The Applicant shall segregate solid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000
- 8. Applicant shall be responsible to take adequate precautionary measures as detailed in this consent.
- 9. The applicant/generator shall be responsible for safe and scientific collection, transportation, treatment and disposal of Bio-Medical Waste as per the provisions made under the Bio-Medical Waste (Management & Handling) Rules, 1998. Any activity as defined under BMW (M & H) Rules has to obtain a separate Authorization from Maharashtra Pollution Control Board.

- 10. For disinfections of waste water ultra violet radiation shall be used in place of chlorination.
- 11. E-Waste shall be disposed to authorize re processor.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic ... 900.00 CMD

(ii) Water gets Polluted &
Pollutants are Biodegradable ... 0.00 CMD

(iii) Water gets Polluted, Pollutants
are not Biodegradable & Toxic
(iv) Industrial Cooling, spraying ... 0.00 CMD
The cooling of the cooling

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under

Section 3 of the said Act.

5. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Standards for Emissions of Air Pollutants:

(i) SPM/TPM Not to exceed 150 mg/Nm3 (ii) SO2 (DG Set) Not to exceed 3.0 Kg/day (i) The following measures shall be taken:

- Adequate mitigation measures shall be taken to control emissions of SO₂, NOx, SPM, and RSPM.
- b. Applicant shall achieve following Ambient Air Quality standards.

| 1. | SPM Not to Exceed (Annual Average) | 140 | μg/ m3 |
|----|--|-----|--------|
| | Not to Exceed (24 hours) | 200 | μg/ m3 |
| 2. | SO ₂ Not to Exceed (Annual Average) | 60 | μg/ m3 |
| | Not to Exceed (24 hours) | 80 | μg/ m3 |
| 3. | NOx Not to Exceed (Annual Average) | 60 | μg/ m3 |
| | Not to exceed (24 hours) | 80 | μg/ m3 |
| 4. | RSPM Not to Exceed (Annual Average) | 60 | μg/ m3 |
| | Not to Exceed (24 hours) | 100 | μg/ m3 |

(ii) The applicant shall observe the following fuel pattern:-

| Sr. No. | Type Of Fuel | Quantity | UOM |
|---------|--------------|----------|-----------|
| 1 | HSD | 760 | Litrs/hrs |

(iii) The applicant shall erect the chimney(s) of the following specifications:-

| Sr. No. | Chimney Attached To | Height in Mtrs. |
|---------|---------------------|-----------------|
| 1 | DG Set (400 KVA) | 4.00 |
| 2 | DG Set (200KVA) | 2.00 |
| 3 | DG Set (250 KVA) | 3.00 |
| 4 | DG Set (320 KVA) | 4.00 |
| 5 | DG Set (63.5 KVA) | 3.00 |

| 6 | DG Set (1010KVA) | 2.00 |
|---|---------------------|------|
| 7 | DG Set (1700 KVA) | 4.00 |
| 8 | DG Set (1500 KVA) | 4.00 |
| 0 | 1 DO Set (1500 KVA) | 4.00 |

(iv) Conditions for D.G. Set

1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less, than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.

4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.

 Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.

7. D.G. Set shall be operated only in case of power failure.

8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(v) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- (vi) The Applicant shall take adequate measures for control of noise levels from its own sources within the complex (residential cum Commercial) in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

| Type Of Waste | Quantity | UOM | Disposal |
|---|----------|-----|--|
| 5.1-Used /spent oil 34.4- Chemical sludge, oil & grease skimming residues | 100.00 | | To authorized reprocessor To authorized reprocessor |

7. Industry shall comply with following additional conditions:

i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31. March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 8. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the storage process connected to it shall be stopped.
- 9. The applicant shall comply with the conditions of Environmental Clearance granted by MoEF vide No. J.12011/1/22/2005/IA(CIE) dt. 27/10/2005.
- 10. The industry shall submit the bank guarantee of Rs. 10 Lakhs within 15 days from the date of issue of this consent at Regional Office Pune, for operation and maintenance of the sewage treatment plant and municipal solid waste processing plant
- 11. This consent shall not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deem fit necessary
- 12. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the applicant.



- 13. The consent is issued with the approval of Consent Appraisal Committee of the Board in its meeting held on 5th December 2012.
- 14. The Capital investment of the industry for the Phase(I) is Rs 80243 Lacs.

(Rajeev Kumar Mital, IAS) Member Secretary

To, M/s City Corporation Ltd. S No 173 177 182 184 187 to 200, 242 to 245 Village Sadesatara nali & S No 111 113 to 121 Village Manjari Tal:- Haveli Dist:- Pune

Copy to:

- a. RO-Pune /SRO-Pune-II
- b. CAO/Cess Branch/Master File

Received Consent fee of -

| Sr. No. | Amount(Rs.) | DD. No. | Date | Drawn On |
|---------|-------------|---------|-------------|---------------------------|
| 1 | 900000 | 978041 | 23 Apr 2012 | Oriental Bank of Commerce |
| 2 | 704871 | 978042 | 23 Apr 2012 | Oriental Bank of Commerce |