

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781  
/4037124/4035273  
Fax : 24044532/4024068 /4023516  
Email : apae@mpcb.gov.in  
Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga  
Scheme Road No. 8, Opp. Cine Planet Cinema,  
Near Sion Circle, Sion (E),  
Mumbai - 400 022

Red/L.S.I

Date: 09/01/2013

Consent No: BO/JD(APC)/EIC No.PN-15272-12/O/CC/CAC-760

Consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Bajaj Auto Ltd.  
Plot No. A-1, MIDC Chakan  
Mahalugegaon, Tal. Khed.  
Dist. Pune 410 501

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- The Consent to Operate is granted for a period up to 31/03/2015
- The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Motorized Two Wheelers	15,00,000	Nos/year
2	Jigs	1,500	Jigs/D
3	Incineration of Waste Paint	2,200	Kg/Day

### 3. CONDITIONS UNDER WATER ACT:

- The daily quantity of trade effluent from the factory shall not exceed 491.M<sup>3</sup>.
- The daily quantity of sewage effluent from the factory shall not exceed 530 M<sup>3</sup>

#### (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards

Sr.no	Parameter	Limits
1	pH	Between 5.5 to 9.0
2	BOD 3 days 27 Deg. C	Not to exceed 30 mg/l
3	COD	Not to exceed 250 mg/l
4	SS	Not to exceed 100 mg/l.
5	Oil & Grease	Not to exceed 10 mg/l
6	TDS	Not to exceed 2100 mg/l.
7	Chlorides	Not to exceed 600 mg/l.
8	Sulphates	Not to exceed 1000 mg/l.
9	Phosphate	Not to exceed 5 mg/l
10	Hexavalant Chromium	Not to exceed 0.1 mg/l
11	Total Chromium	Not to exceed 2 mg/l
12	Zinc	Not to exceed 5 mg/l.
13	Cyanide	Not to exceed 0.2 mg/l.
14	Copper	Not to exceed 3 mg/l.

(iv) **Trade Effluent Disposal:** The treated industrial effluent shall be recycled to the maximum extent and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- (1) Suspended Solids Not to exceed 100 mg/l.  
 (2) BOD 3 days 27o C. Not to exceed 100 mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening/ plantation only.

(vii) **Non-Hazardous Solid Wastes:**

S.No.	Type	Qty	UOM	Disposal
1	Canteen waste & garbage	900.00	MT/A	As manure / Sale to Piggeries
2	Grinding and buffing dust	436.00	MT/A	Secure landfill
3	Factory rubbish	2555.00	MT/A	By sale
4	MS turning boring off cuts	5419.00	MT/A	by sale
5	STP Sludge	140.00	MT/A	For garden inside he factory premises
6	Shot blasting	250.00	MT/A	By sale
7	Dust (Jig Stripping Plant)	15.00	MT/A	By sale
8	Waste /used sand (Jig stripping plant)	10.00	MT/A	Sale to auth. dealer

(viii) **Other Conditions:**

- i) The unit shall carry out monthly monitoring of treated domestic as well as industrial effluent and submit the report of the same to the Board regularly
- ii) The unit shall take necessary efforts for segregation of solid waste at source only and disposal salable waste regularly. The records showing waste segregation at source to be maintained.
- iii) The unit shall take necessary efforts regarding rain water harvesting every monsoons.

**4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

(i) Domestic	...	700.0 CMD
(ii) Industrial Processing	...	744.0 CMD
(iii) Industrial Cooling	...	357.0 CMD
(iv) Industrial Processing & floor washing	...	0.00 CMD
(iv) Agriculture / Gardening	...	350.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

**5. CONDITIONS UNDER AIR ACT :**

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

**6. Control Equipment:**

- i) Fume extraction system followed by Dust collection system of sufficient capacity should be provided to all sources of SPM/TPM shall be operated properly and continuously
- ii) Painting activity shall be carried out in an enclosed shed
- iii) There shall not be any secondary (Fugitive) emissions.

**Conditions for D.G. Set**

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.

- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

**Standards for Emissions of Air Pollutants :**

(i)	SPM/TPM	Not to exceed	50	mg/Nm <sup>3</sup>
(ii)	SO <sub>2</sub>	Not to exceed	200	mg/Nm <sup>3</sup>
(iii)	CO	Not to exceed	50	mg/Nm <sup>3</sup>
(iii)	HCL	Not to exceed	50	mg/Nm <sup>3</sup>

**C) Applicant shall comply with CPCB guidelines of emission standards for Hazardous waste incineration as under.**

Parameter	Emission standard	
Particulates	50 mg/Nm <sup>3</sup>	Standard refers to half hourly average value
HCl	50 mg/ Nm <sup>3</sup>	Standard refers to half hourly average value
SO <sub>2</sub>	200 mg/ Nm <sup>3</sup>	Standard refers to half hourly average value
CO	100 mg/Nm <sup>3</sup>	Standard refers to half hourly average value
	50 mg/ Nm <sup>3</sup>	Standard refers to daily average value
Total Organic Carbon	20 mg/ Nm <sup>3</sup>	Standard refers to half hourly average value
HF	4 mg/ Nm <sup>3</sup>	Standard refers to half hourly average value
NO <sub>x</sub> (NO and NO <sub>2</sub> expressed as NO <sub>2</sub> )	400 mg/ Nm <sup>3</sup>	Standard refers to half hourly average value
Total dioxins and furans	0.1 ng TEQ/Nm <sup>3</sup>	Standard refers to 6-8 hours sampling. Please refer guidelines for 17 concerned congeners for toxic equivalence values to arrive at total toxic equivalence
Cd + Th + their compounds	0.05 mg/ Nm <sup>3</sup>	Standard refers to sampling time anywhere between 30 minutes and 8 hours.
Hg and its compounds	0.05 mg/ Nm <sup>3</sup>	Standard refers to sampling time anywhere between 30 minutes and 8 hours.
Sb + As + Pb + Cr + Co + Cu + Mn + Ni + V + their compounds	0.5 mg/ Nm <sup>3</sup>	Standard refers to sampling time anywhere between 30 minutes and 8 hours.

**Note: All values corrected to 11% oxygen on a dry basis**

**Operating Standards:**

I. All the facilities shall be designed to achieve a minimum temperature of 1100°C in secondary combustion chamber and with a gas residence time in secondary combustion chamber not less than 2 (two) seconds.

II. The incineration facilities after initial operation of minimum one year, as per the guidelines and standards, can submit a proposal for relaxation in temperature and retention time requirement if it can be demonstrated that the flue gas standards and operation standards can be complied with at lower temperatures and residence times.

III. Incineration plants shall be operated (combustion chambers) with such temperature, retention time and turbulence, so as to achieve Total Organic Carbon (TOC) content in the slag and bottom ashes less than 3%, or their loss on ignition is less than 5% of the dry weight of the material.

IV. Guidelines published by the Central Board from time to time for common incineration facilities shall be referred for implementation.

V. All the project proposals submitted for establishment of the common incineration facilities shall be examined and cleared by the Task Force constituted by the Central Board.

VI. Notification of compliance: The operator of the incinerator shall undertake comprehensive performance test. Within 90 days of completion of comprehensive performance test, the operator shall issue a notification of compliance documenting compliance or non-compliance, as the case may be, for public information / notice.

(ii) The applicant shall erect the chimney(s) of the following specifications:-

S.No.	Stack No.	Stack Attached	Height
1	S1 & S2	Dg Set (3187 KVA 2 Nos)	35.00
2	S3	PTCED Boliers (3 Nos)	30.00
3	S4	Paint Shop boilers (3 Nos)	30.00
4	S5	Fluidized bed furnace	42.00
5	S6	Incinerator	40.00

7. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

8. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(iii) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 3) The D.G. Set shall be utilized as a standby power source and shall be operate only in case of power failure

9. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

S.No.	Hazardous Waste Category	Qty	Treatment	Disposal
1	21.1 Wastes and residues	741.00	MT/Year, Incinerator	Incinerator premises within
2	34.3 Chemical sludge from waste water treatment	344.00	MT/Year	MEPL
3	5.2 Wastes/residue	2059.00	MT/Year	Sale to auth. contractor

	containing oil			
4	33.3 Discarded containers / barrels / liners	450000.00	Nos/Year	Auth recycler
5	36.2 Ash from incineration of hazardous waste	130.00	MT/Year	MEPL
6	B4 Lead & Lead Compunds	6.00	MT/Year	sent to Auth. recycler
7	E- waste	20.00	MT/A	sent to Auth. recycler

(ii) Treatment: - NIL

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

**10. Industry shall comply with following general conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory

11. The Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.

12. This issued with approval of Consent Appraisal Committee meeting of the Board held on dtd. 27/12/2012.

13. This consent is issued in supersession of earlier consent vide No. BO/JD(APC)/EIC No. PN-12974-12/O/CC-CAC-444 dated 08/06/2012.

14. The applicant shall follow the Guidelines for Storage of Incinerable Hazardous Wastes by the Captive HW Incinerators issued by CPCB dated 11.11.2008.

15. The existing operational Bank Guarantee shall be valid up to 31/03/2015

16. The Total Capital investment of the industry is Rs. 447.71 Crs

(Rajeev Kumar Mital IAS)  
Member Secretary

To,  
M/s. Bajaj Auto Ltd  
Plot No. A-1, MIDC Chakan,  
Mahalugegaon, Tal. Khed.  
Dist. Pune 410 501

Copy to:

- 1) Regional Officer/Sub-Regional Officer, MPCB, Pune-They are directed to ensure the Compliance of consent conditions and submit the report one month period.
- 3) Chief Accounts Officer, MPCB, Mumbai

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	33000/-	891220	07/09/2012	CITI Bank