MAHARASHATRA POLLUTION CONTROL BOARD Phone : 022 - 22640345

Fax 022-22640345

Email : mpcb@mpcb.gov.in

Kalpataru Point, 2nd - 4th Fl. **Opp.** Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022

Visit At : http://mpcb.gov.in

> KN-6375/12 Infrastructure/Orange/L.S.I Consent No. BO/RO(HQ)/CO/CAC-786

Date: \q/01/2013

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, trol Boo Handling & Transboundry Movement) Rules 2008

CONSENT is hereby granted to

M/s. Lodha Dwellers Pvt. Ltd. Usarghar, Nilje Katai, Ghesar, Kalyan Dist. Thane -421204

located in the area declared under the provisions of the Water Act Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to 31/12/2014
- 2. The Consent is valid for -

The residential township project named as 'Casa Bella' of M/s. Lodha Dwellers Pvt. Ltd. Usarghar, Nilje Katai, Ghesar, Kalyan Dist. Thane -421204, Plot bearing S. No. 4/1/2/3, 165/1, Usarghar, Mije Katai, Gnesar, Galyan Dist. 1 nane -421204, Plot bearing S. No. 4/1/2/3, 105/1, 166/1A/1B/1C, 166/2, 166/3A/3B, 166/4, 168/0, 169/1 TO 4,5A,5B,6 TO 13, - 170/0,- 171/1 TO 5,- 172/1 TO 4,- 173/1,2, 174/1 TO 3, 125/1710 5, 176/1 TO 4, 5A,5B-177/1A,1B,1C,2A,2B-178/0-179/0-180/1,2,- 181/1,2,3,182/0-183/1A,1B,3 - 184/1P,2,3-185/1A,1B,2 TO 9/10A,10B,11 TO24 - 186/1A-1,1A-2,1C,1/4-2 TO5,187/0,-188/1,2,-189(7,2,190/1,2,3A,3B,-191/1,2A,2B-92/1A+8A(8A),1B(1B),1A+8A (8A), 1B(1B), 1C2(1C2),191/1C+2A(1C3),192/2B+3A(2B3),2/3(2C),2K+3D(2K4),B+A(3B7),3C7B(3C7),4/P(4A),4P(4 C),5/1(5A1),5/2(5A2),920(6)/9(9),193/1,2,3,4A,-201/1A, 1B, 2A1(1C), 2(2),-210/1,2,3A,3B, -214/1,2,- 215/0-216/1A 1PGC (DP2-217/00fNH, HE 7/1A 2A 2B 3A -8/1A 6A-1 7A 7B 8A 10-A 11C-13 14 15 /A C),5/1(5A1),5/2(5A2), 92/6(6)/9(9),193/1,2,3,4A,-201/1A, 1B, 2A1(1C), 2(2),-210/1,2,3A,3B, -214/1,2,-215/0-216/1A,1B,C, D2-217/0ofNILJE,7/1A,2A,2B,3A,-8/1A,6A-1,7A,7B,8A,10-A,11C-,13,14,15,/A, 1B,2-10/1,2,-174 TO 11,12A,12B,13 TO 22,-12/1,2-13/1,2,-14/0- 15/0,-16/0,-17-0,-18/1,2,3,-19/2 TO 6,-21/4A,83/1,2,844) TO 4,-109/1,2,-122/0, of KATAI, 12/3A, 4A,5,6,7,8A,9A,11A,12,13,14A,15A,16,-74/1,2A,2B,2C,3TO10,75/0,76/1/2A/3A/4A,5,6,7,8A,8/2,9,10,11-88/0,-89/2A,-105/P,-125/1, 2,3A, 3B,4, 59.5 (67,-137/1, 2,3 of USARGAR and 42, 44/1D, 56/2, 58/P, 58 / 1B /1, 58/2A, 58/2B, 58/4, 58/6B, 58/7B 59,60/1/2/3A/3B/3C,61/2,62/1B/2A/2B/2C/3P/3P A/3B /3C /3D /3E /3F /3G /3H/4A/4B/5A/5B, 63/1B1, 63/1B/2 ,63/2, 64/1, 65/1/2, 66/1/2, 66/3A/3B, 66/4, 66/5A/5B, 66/6/7, 67, 68, 74/P, 77/1/2/3/4/5/6, 79, 85/3, 87/1/2/5, 90/1/2/3, 91/1A/1B,92/1/2, 93, 94/0, 96/1/2, 97/1/2/3/4, 98, 99/1A/1B, 99/2A/2B/2C/2D/2E, 99/3A/3B, 100, 101/ 1A/1B/1C, 101/2, 102/1/2/3, 103, 104/1A, 105/1D, 106/3B, 107/2B/2C, 107/3A/3B/3C, 113/1A, 113/2, 116/P, 116/10, 117, 63/1, 64/2, 69, 70, 71, 72, 73, 74/1, 75, 76, 80, 91/1/1, 95/0, 116/P of GHESAR, on total plot area of 10, 62, 607.00 Sq mtrs and total construction area of 12222.169 Sq mtrs including services and utilities as per occupation certificate issued by local body.

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be Nil.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 7857.00M³.
- (iii) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	pH		
3		Not to exceed	6.5 to 9.0
-	Suspended Solids	Not to exceed	100 mg/l.
4	BOD 3 Days 27 degree C	Not to exceed	
5	Fecal Coliform	Not to exceed	100 mg/l.
6	Residual Chlorine	Not to exceed	500/100/1 mg/l.
7	Detergent	Not to exceed	01 mg/l.
8			01 mg/l.
	Floating matters	Not to exceed	10 mg/l

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners and remaining shall be discharged to Municipal sewer. In no case, effluent shall find its way to any water body directly/indirectly at any time. The firm shall affix the separate meter for ensurance of 80 % recycling of treated sewage and keep the records of the same.

Project proponent shall operate STP for five years from the date of obtaining occupation

(vii) Non-Hazardous Solid Wastes:

Su No T Oam				N
Sr. No. Type Of Waste	Quantity	UOM	Treatment	Disposal
1 Solid waste	36,831	Kg/day	Organic waste converter	Lisposal
				Used as manure 1

(viii)Other Conditions (during Construction Phase):

- 1. All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- 2. There shall be no felling of trees whether on Forest, Government, Revenue or Private lands except as per prevailing Rules.
- 3. Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable.4. Near the activities that are related to water (like activity of water parks, water sports) and/or in
- the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- 5. In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.
- The Applicant shall prepare management plan for water harvesting, roof-water reclamation, water/storm water conservation and implement the same before handling over of complex for occupation
- The Applicant shall segregate solid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000
- 8. Applicant shall be responsible to take adequate precautionary measures as detailed in this
- 9. The applicant/generator shall be responsible for safe and scientific collection, transportation, treatment and disposal of Bio-Medical Waste as per the provisions made under the Bio-Medical Waste (Management & Handling) Rules, 1998. Any activity as defined under BMW (M & H) Rules has to obtain a separate Authorization from Maharashtra Pollution Control
- 10. For disinfections of waste water ultra violet radiation shall be used in place of chlorination.
- 11. E-Waste shall be disposed to authorize re processor.

		on) Cess Act, 1977 (to				ules, 2003 ther
	The	daily water consumption	for the following cat	egories is a	s under:	
	(1)	Domestic		9826	5.00 CMD	
	(11)	Water gets Polluted &				
	(iii) V	Pollutants are Biodegrada Water gets Polluted, Pollu	ble Itants	0.00	CMD	
	8	are not Biodegradable & T	Foxic	0.00	CMD	
	(iv)]	Industrial Cooling, sprayi	ng	0.00	CMD	
	r ne preso	applicant shall regularly cribed form and pay the C	v submit to the Boa less as specified unde	ard the ret er Section 3	urns of water con of the said Act.	nsumption in the
5	5. CONDI	TIONS UNDER AIR	(Prevention & Co	ntrol of D	allution) ACT 1	ŪΩ1.
		applicant shall install a c	comprehensive contra	al evetern a	angisting of south	1
	40 10	warance with reference	e to generation of en	hre noizzin	operate and mail	ain the same
	contri	nuously so as to achieve adards for Emissions o	line level of pollutant	s to the follo	owing standards:	
	••• 5tal	i) SPM/TPM	Not to exceed	1.50	$\sim OO$	•
		ii) SO2 (DG Set)	Not to exceed	150 m		
	(ii) The f	following measures shall	he taken.		g/day	
	a.	Adequate mitigation m and RSPM.	easures shall be take	. T .		, NOx, SPM,
	b.	Applicant shall achieve	e following Ambient	Air Quality	standards.	
	1.	SPM Not to Exceed	(Annual Average)	140	μg/ m3	
	_	Not to Exceed (24 hou	· · · · · · · · · · · · · · · · · · ·	200	μg/ m3	
	2.	SO2 Not to Exceed	(Annual Average)	60	µg∕ m3	
	•	Not to Exceed (24 hou	rs)	80	μg/ m3	
	3.	NOx Not to Exceed	(Annual Average)	60		
		Not to Exceed (24 hou	rs (Condige)	80	μg/ m3 μg/ m3	
	4.	RSPM Not to Exceed	(Annual Average)	60	μg/ m3	
		Not to Exceed (24 hour	rs)	100	μg/ m3	
					P.8	
	(iii) The a	pplicant shall observe th	he following fuel par	ttern:-		
	Sr.	No. Type Of Fuel	Quantity UOM			
			30.00 Ltrs/h			
	11.a.	J				
		pplicant shall erect the o	chimney(s) of the fo	llowing spe	cifications:-	
	Sr.	No. Chimney Attache	d To Height in A	//		
	1	DG Sets	ed To Height in N 4.00	ttrs. above	roof top	
		tions for D.G. Set	/ 1 111			
	1.	Noise from the D.G. So by treating the room acc	et should be controll	ed by provi	ding an acoustic e	nclosure or
		of fround the room act	JUSHCATIV.			
		Industry should providenclosure/ acoustic treat	ment of the room sh	re for cor	trol of noise. The	ne acoustic
		enclosure/ acoustic treat insertion loss or for mee	ting the ambient noi	ould be des	igned for minimun	1 25 dB (A)
		A suitable exhaust muf	flow with insention 1	se standard	, whichever is on	nigher side.
		The measurement of ins	nei with insernon in	NSS OF 25 4	$R(\Delta)$ chall a_{1-1}	

- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(vi) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- (vii) The Applicant shall take adequate measures for control of noise levels from its own sources within the complex (residential cum Commercial) in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.

(viii) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the are emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- c) Construction material shall be carried in enclosed vehicles during constriction activities.

(ix) Conditions for Utilities like Kitchen, Eating Places etc:

. The kitchen shall be provided with exhaust system chimney with oil catcher connected to chimney through ducting.

The toilet shall be provided with exhaust system connected to chimney through ducting.

- 3. The air conditioner shall be vibration proof and the noise shall not exceed 68 dB (A).
- 4. The exhaust hot air from A.C. shall be attached to Chimney at least 5 mtrs. higher than the nearest tallest building through ducting and shall discharge into open air in such way that no nuisance is caused to neighbors.
- (x) The Applicant shall take adequate measures for control of noise levels from its own sources within the complex (residential cum Commercial) in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.
- (xi) Construction equipments generating noise of less than 65/90 db(A) are permitted.
- (xii) No construction work is permitted during nighttime.
- 6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:
 - (i) The Industry shall not generate any hazardous wastes.

7. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures for control of i. pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board station the terminal or designated points and shall pay to the Board for the services rendered in this benalf. vii. The applicant shall make an application for renewal of the consent at least 50 days before the date
- of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992. ix. As inspection book shall be opened and made available to the Board's officers during their visit to
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent frequency plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- Whenever due to any accident or other unforeseen act or even, such 8. emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the storage process connected to it shall be stopped.
- The applicant shall comply with the conditions of Environmental Clearance 9. granted by Environment Dept., Govt.f Maharashtra, vide No. SEAC-009/CR.145/TC.2 dt.17/07/2010.
- The industry shall submit the bank guarantee of Rs. 10 Lacs within 15 days from 10. the date of issue of this consent at Regional Office Kalyan for operation and maintenance of the sewage treatment plant and municipal solid waste processing plant.
- The applicant shall submit the affidavit in prescribed format regarding part of 11. built up area under present consent being part of Environmental Clearance, within fifteen days from date of issue of this consent.
- 12. This consent shall not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deem fit necessary

	13. The Board reserves the right to amend or add any conditions in the consent and the same shall be binding on the applicant
	o percent
	14. The consent is issued with the approval of Consent Appraisal Committee of the Board in its meeting held on 8 ^h January 2013.
	15. The Capital investment of the industry is Rs. 14000 Lacs
	(Rajiv Kumar Mital, IAS)
	Member Secretary
	To, M/s. Lodha Dwellers Pvt. Ltd.
	Usarghar, Nilje Katai, Ghesar, Kalyan
	Ust. Thane, -421204
	Copy to: a. RO- Kalyan /SRO-Kalyan-I
	b. CAO/Cess Branch/Master File
	Received Consent fee as – Sr. No. Amount(Rs) DD No. Date
	Sr. No.Amount(Rs.)DD. No.DateDrawn On128072042681528 Aug 2012Retak Mahindra Bank Ltd.
	Boole Wallhura Bank Ltd.
	20/12
	~~~~
	×(0)
	Maharashtra
	10 ²
	101
	~ <i>VSI.</i>
RO Kal	lyan/I/O/L/85769000
	6