MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: <u>http://mpcb.gov.in</u> E-mail: apae@mpcb.gov.in



Kalpataru Point, 2nd - 4th Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Date: 18/02/2013

Red/L.S.I

Consent No: BO/JD(APC)/EIC No. PN-15228-12/CC/(Ac-1496

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Godrej & Boyace Mfg. Ltd., Gat No.600, 601, 605, A/p- Wing, Tal- Khandala, Dist- Satara 412 801

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to -30/09/2014.

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Refrigerators (using non- ODS chemicals)	75000	Nos/M
2	Spares of Refrigerators	10000	Nos/M
3	Washing Machine	25000	Nos/M
4	Spares of washing machine	10000	Nos/M
5	Injection moulded	100000	Nos/M
	components		

3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 65.0 M³.
(ii) The daily quantity of sewage effluent from the factory shall not exceed 65.0 M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sr.no	Parameter		Limits
1	рН	Between	5.5 to 9.0
2	BOD 3 days 27 Deg. C	Not to exceed	30 mg/l
3	COD	Not to exceed	250 mg/l
4	SS	Not to exceed	100 mg/l.
5	Oil & Grease	Not to exceed	10 mg/l
6	TDS	Not to exceed	2100 mg/l.
7	Chlorides	Not to exceed	600 mg/l.
8	Sulphates	Not to exceed	1000 mg/l.
9	Phosphate	Not to exceed	5 mg/t

- (iv) **Trade Effluent Disposal:** The treated industrial effluent shall be reused to the maximum extent and remaining treated effluent shall use on land for gardening.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
 - Suspended Solids Not to exceed 100 mg/l.
 BOD 3 days 270 C. Not to exceed 100 mg/l.
- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

S.No.	Туре	Qty	UOM ·	Disposal
1	Plastic Scrap	400	MT/A	By Sale
2	Wood	200	MT/A	By Sale
3	Scrapped Foamed Cabinets/Doors	15000	Nos./Y	By Sale
4	Drums 🔮 🚺	9	MT/A	By Sale
5	Sheet Metal	400	MT/A	By Sale
6	Other M.S.Scrap	300	MT/A	By Sale
7	Corrugated Boxes	300	MT/A	By Sale
8	Paper/polythene Bags	50	MT/A	By Sale
9	Other Packing Material	400	MT/A	By Sale
10	Cast Iron Scrap	50	MT/A	By Sale

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

	90.00 CMD
	80.00 CMD
	45.00 CMD
•••	0.00 CMD
	····

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:

- 1. Fume extraction system followed by Dust collection system of sufficient capacity should be provided to all sources of SPM/TPM shall be operated properly and continuously
- 2. Fume extraction system followed by wet scrubber shall be provided to phosphating section and operate regularly.
- 3. There shall not be any secondary (fugitive) emissions.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

i.

Standards for Emissions of Air Pollutants:

(i)	SPM/TPM	Not to exceed	150	mg/Nm³
(ii)	SO2	Not to exceed	20.78	3 Kg/Day

(i) The applicant shall observe the following fuel pattern:-

S.No.	Fuel Type	Qty.	UOM
1	HSD	850	Lit/Day
2	LDO	105	Lit/Day
3	Briquettes	4	MT/Day
4	SKO	540	Lit/Day

(ii) The applicant shall erect the chimney(s) of the following specifications:-

S.No.	Stack Attached	Height
. S.NO.		
[1	Water Drying & Powder Curing Oven	22.00
10	Die Casting Machine	24.00
2	Fire Hydrant Machine	6.00
3	Powder Curing Oven	30.00
4	Water Drying Öven	30.00
5	DG Set (500 KVA)	24.00
6	Washer Powder Curing Oven	24.00
7	Hot Water Generator	24.00
8	Pretreatment Tunnel (3 Nos)	14.00
9	DG Set (1010 KVA x 2 Nos)	30.00

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i)	The Industry	shall handle	hazardous wastes a	s specified below
(*/	ric induoury	onan nanaio	manataoas mastes a	o opcontica peron

S.No.	Hazardous Waste Category	Qty	UOM	Disposal
1	5.1 Used /spent oil	9000	Lit/Year	By sale to Auth.reprocessor/re cycles

2	5.2 Wastes/residue containing oil	1700	Kg/Year	By sale to Auth.reprocessor/re cycles
3	12.5 Phosphate sludge	2500	Kg/Year	To CHWTSDF
4	33.1 Chemical-containing residue from decontamination and d	4000	Kg/Year	To CHWTSDF
5	32.2 Corrosive wastes arising	1500	Kg/Year	To CHWTSDF
6	33.3 Discarded containers / barrels / liners	7500	Kg/Year	By sale to Auth.reprocessor/re cycles
7	34.4 Chemical sludge, oil and grease skimming residues	25000	Kg/Year	
8	21.1 Wastes and residues	20000	Kg/Year	By sale to Auth.reprocessor/re cycles
9	36.2 Ash from incineration of hazardous waste (Hanger Burning Ash)	1500	Kg/Year	
10	Non ferrous Scrap	20000	Kg/Year X	By sale to Auth.reprocessor/re cycles
11	31.3 E –Waste	10000	Kg/Year	By sale to Auth.reprocessor/re cycles

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
- 2. The industry should comply with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008.
- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008 and shown & submitted to the Board as & when asked for.

8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power sources ufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

is The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- 9. This is issued with the approval of Consent appraisal committee meeting held on 31/01/2013.
- 10. You shall submit Bank Guarantee of Rs. 10/- Lakh in favor of Regional Officer Pune within 15 days against operation & maintenance of pollution control system. The Bank Guarantee shall be valid up to 30/09/2014.
- 11. The Capital investment of the industry is Rs.131.787/-Crs.

(Rajeev Kumar M Member

To,

M/s. Godrej & Boyace Mfg. Ltd., Gat No.600, 601, 605, A/p-Wing, Tal-Khandala, Dist-Satara.

Copy to:

RO- MPCB- Pune /SRO-MPCB-Satara - They are directed to obtain the BG of Rs. 10/- Lakhs from the industry & submit the detail report of pollution control System within 1 month period.

CAO/Cess Branch/Master File Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Re 527148/-	684658	08/09/2012	SBI Bank
	1 13.027 1407		00,00,2012	
	Second Second			
	an constantino de la constantino de la Constantino de la constantino de la cons			
1. P				
	S .			
and the second s	%			