

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 24010437/24020781/24014701

Fax : 24023516/24024068/24044531

Email : enquiry@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Kalptaru Point, 2nd, 3rd & 4th Floor,

Opp. Cine Planet,

Near Sion Circle, Sion (E),

Mumbai - 400 022

RED/LSI

Consent No: BO/JD(APC)/CE/EIC No. RD -2518-13/CC - ¹⁹⁰⁷ ~~Date: /03/2013~~ DT.04/03/13

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. P.S. Steel Tubes Ltd
S. No. 644(A), 644 (B), 660, 661, 685, 686,
687, 688, 689, 690, 691, 694/3,
Village: Khanav, Tal. Khalapur,
Dist. Raigad, Pin-410203.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Establish is granted for a period up to commissioning of the unit or 5 years whichever is earlier
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Galvanized Steel Tube / Precision Steel Tube	1,25,000	MT/A
2	Zinc Dross [By-Product]	216	MT/A

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 5.0 M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 5.0 M³.
- (iii) **Trade Effluent :**

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	6 to 9.0
2	Oil & Grease	Not to exceed	10 mg/l
3	Suspended Solids	Not to exceed	100 mg/l.
4	Total metal	Not to exceed	10 mg/l
5	Nickel (as Ni)	Not to exceed	3.0 mg/l
6	Hexavalent Chromium as Cr	Not to exceed	0.1 mg/l.
7	Total Chromium as Cr	Not to exceed	2 mg/l.
8	Copper as Cu	Not to exceed	3 mg/l.
9	BOD 3 days 27 Deg. C.	Not to exceed	100 mg/l.
10	COD	Not to exceed	250 mg/l.
11	TDS	Not to exceed	2100 mg/l.
12	Zinc (as Zn)	Not to exceed	5.0 mg/l
13	Lead (as Pb)	Not to exceed	0.1 mg/l.
14	Iron (as Fe)	Not to exceed	5.0 mg/l.

(iv) **Trade Effluent Disposal:** The treated effluent shall be 100% recycled in the process and **Industry shall achieve Zero Liquid Discharge**. There shall not be any discharge outside the factory premises and in no case trade effluent shall find its way into nearby stream /river. Industry shall send spent acid generated from process to Acid Recovery Plant.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27° C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Metal Scrap	50.00	MT/M	---	Sale to authorized party
2	Wooden Scrap	1.00	MT/M	---	Sale to authorized party
3	Garbage	0.20	MT/M	---	Manure / MSW site

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under.

The daily water consumption for the following categories is as under:

i	Domestic purpose	7.0 CMD
ii	Industrial Processing	6.0 CMD
iii	Industrial Cooling. Boiler	2.0 CMD
iv	Agriculture / Gardening	1.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Control Equipment:

1. Scrubber of sufficient capacity provided to metal cleaning process and operated and maintained properly so as to achieve following standards.
2. Industry shall provide adequate air pollution control equipments to control air emissions at all sources of secondary emissions.
3. Industry shall provide Dust Collector, bag filter and adequate exhaust system to control air emissions.
4. Adequate fume extraction system followed by dust collector of sufficient capacity shall be provided at all dust generating locations and operated properly.
5. There shall not be any secondary (fugitive) emissions.

b. Standards for Emissions of Air Pollutants:

i	SPM/TPM	Not to exceed	150 mg/Nm ³
ii	NO _x	Not to exceed	100 ppm
iii	Acid Mist	Not to exceed	35 mg / Nm ³
iv	SO ₂	Not to exceed	147.9 Kg / Day.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- g. D.G. Set shall be operated only in case of power failure the applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

7. Standards for Stack Emissions:

- (i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	40,000	Liters /Month
2	HSD	2500	Litrs/Day.

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1.	GP line Furnace	30
2	GP line Fume exhaust	17
3	Galvanizing section dust collector	17
4	Pickling Line scrubber	17
5	DG Set (1000 KVA)	5 mtrs. above building height

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(v) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The industry shall handle hazardous wastes as specified below:

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1.	5.1 Used/Spent Oil	0.20	MT/M	Sale to Authorized Recycler/Reprocessor approved by CPCB/SPCB
2.	5.2 Waste Residue containing Oil	0.20	MT/M	Sale to Authorized Recycler/Reprocessor approved by CPCB/SPCB
3.	34.3 Chemical Sludge from WWT	0.20	MT/M	to CHWTSDF
4.	Spent Acid	3.0	KL/M	Send to Acid Recovery Plant

(ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

9. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

10. The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.
11. Industry has submitted a copy of distance certificate issued by Executive Engineer, Raigad Irrigation Division dated 23.07.2010 stating that proposed unit is located 11,200 meters away from Balganga River.
12. The applicant shall obtain the consent to Operate before starting the commercial production.
13. The Consent is issued subject to the decision taken in the meeting of the Consent Committee of the board held on 15.02.2013 and the approval of Hon'ble Chairman of the Board.
14. The total Capital investment of industry is Rs.80.55 Crores.

For and On Behalf of the
Maharashtra Pollution Control Board,

(Rajeev Kumar Mital, IAS)
Member Secretary

To,
M/s. P.S. Steel Tubes Ltd.
S. No. 644(A), 644 (B), 660,661,685,686,
687,688,689,690,691, 694/3,
Village: Khanav, Tal. Khalapur,
Dist. Raigad, Pin-410203.

Copy to:

- a. RO- Raigad / SRO-Raigad-I, MPCB, Navi Mumbai.
- b. CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	1,25,100	022196	26/12/2012	Axis Bank