

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781
/4037124/4035273
Fax : 24044532/4024068 /4023516
Email : enquiry@mpcb.gov.in
Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga
Scheme Road No. 8, Opp. Cine Planet Cinema, Near
Sion Circle, Sion (E),

Mumbai - 400 022

Red/LSI

Date: 25/03/13

Consent No. BO/AS(T)/TNE/CAC-2493

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Trans boundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s .Seya Industries Ltd.
Plot No. D-16, MIDC
Tarapur, Tq. Palghar, Dist. Thane.

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Establish is granted for a period up to: Commissioning of unit Or 5 year which ever is earlier
2. The Consent is valid for the manufacture of -

<u>Sr.No.</u>	<u>Product</u>	<u>Maximum Quantity</u>
1	Caustic Soda,	8370 MT/M
2	Chlorine Gas	6820 MT/M
3.	Hydrogen Gas	2343600 Nm ³
4	Monochloro Benzene	7500 MT/M
By-products		
1	Dichloro Benzene(PDCB & ODCB),	3600 MT/M
2	Hydrochloric Acid(30 %)	11850 MT/M
3	Hydrochloric Acid(32 %)	2170 MT/M
4	Sodium Hypochlorite(AS12%NaOCI)	310 MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 120 M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 07 M3.
- (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 8.5
2	BOD 3 days 27 Deg	Not to exceed	100 mg/l
3	COD	Not to exceed	250 mg/l
4	Suspended Solids	Not to exceed	100 mg/l
5	Oil & Grease	Not to exceed	10 mg/l
6	Total dissolved Solids	Not to exceed	2100 mg/l
7	Sulphates	Not to exceed	1000 mg/l
8	Chlorides	Not to exceed	600 mg/l
9	Phenolics (C6H5OH)	Not to exceed	1.0 mg/l
10	Sulphide (as S)	Not to exceed	2.0 mg/l
11	Phenol and Phenolic Compound as C6 H5 OH	Not to exceed	1.0 mg/l
14	Nitrate (as NO3)	Not to exceed	50.0 mg/l

(iv) **Trade Effluent Disposal:** Nil

The treated trade effluent shall be recycled/ reused 100 % In no case the effluent shall find its way outside the factory premises leading to local Nullah /River.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- | | | | | |
|-----|-------------------|---------------|-----|-------|
| (1) | Suspended Solids | Not to exceed | 100 | mg/l. |
| (2) | BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The sewage shall be treated in the trade effluent treatment plant.

(vi) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Waste	Quantity	UOM	Treatment	Disposal
---------	------------	----------	-----	-----------	----------

.....NIL.....

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- | | | | | |
|-------|---|-----|------|-----|
| (i) | Domestic purpose | ... | 10 | CMD |
| (ii) | Water gets Polluted & Pollutants are Biodegradable | ... | 120 | CMD |
| (iii) | Water gets Polluted, Pollutants are not Biodegradable & Toxic | ... | | CMD |
| (iv) | Industrial Cooling, spraying in mine pits or boiler feed | ... | 1369 | CMD |
| (v) | Gardening | ... | 05 | CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment: 1) The heater stacks are excluded from TPM monitoring.

2) **Hydrocarbon:** The emission from various sources in the factory shall be so restricted as to limit the ambient level of non methane hydrocarbon in the factory premises to 0.24 ppm on 24 hours average basis. The emission shall not contain constituents in excess to the tolerance limit as laid down hereunder

b) Standards for Emissions of Air Pollutant:

(i)	SPM/TPM	Not to exceed	150 mg/Nm ³
(ii)	SO ₂ (DG set)	Not to exceed	192 Kg/day.
(iii)	SO ₂ (coal Boiler)	Not to exceed	528 kg/day
(iv)	HCL	Not to exceed	35 mg/Nm ³
(v)	Chlorine	Not to exceed	15 mg/Nm ³

(ii) The applicant shall observe the following fuel pattern -

Sr.No.	Type of Fuel	Quantity
1	Coal	2200 Kg/Hr.
2	Diesel /CNG	400 Ltr /hr

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr.No.	Chimney attachment	Height in Mtrs.
1	Boiler .	40
2	D.G. Set (3000 KVA)	06
3	Scrubber	20

(iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

(v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

Standards for Emissions of VOC Pollutants (depends on emission)

Sr. No.	Petrochemical process / compounds	Maximum emission limit (mg/Nm ³) dry basis.
1	MA, PA, Phenol	20
2	Ethyl benzene (EB), Styrene, Toulene, Xylene, Aromatics, EG, PG	100
3	Non-methane HC (paraffin), Acetone, olefins	150

c. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The applicant shall handle hazardous wastes as specified below:

Sl.	Item No. as per Sch-I	Type of Waste	Quantity	Disposal
1	16.2	Waste from Brine purification	15 MT//Day	CHWTSDF
2	34.03	ETP sludge	3 MT/day	CHWTSDF

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M&H) Rules, 2003.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

7. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- xiii. If CETP does not work for achieving standards & problem of pollution occurs, industry shall voluntarily stop the production or total effluent shall be reused.
- xiv. The consent should not be construed as any exemption from obtaining necessary NOC from other Govt. agencies as may be deemed fit necessary.
- xv. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
- xvi. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.

8. Specific conditions

- i. Applicant shall not take any effective steps before obtaining Environmental Clearance as per EIA Notification 2006.
- ii. The industry shall recycle 100% treated effluent to achieve Zero Discharge.
- iii. The industry shall strictly follow the gaseous emissions limit of Chlorine from Hypo Tower - 15 mg/ Nm³, HCl- 35 mg/ Nm³, and Chlorine alarm system shall be adjusted to 1 ppm.
- iv. This Consent is issued pursuant to the decision of CAC meeting of the Board dtd. 12.03.2013.
- v. The industry shall obtain consent to operate before starting commercial production.
- vi. The Capital investment of the industry is Rs 12481/- Crs .

(Rajeev Kumar Mital, IAS)
Member Secretary

To,
M/s .Seya Industries Ltd.
Plot No. D-16, MIDC,
Tarapur, Tq. Palghar, Dist. Thane.
Copy for information to:-
Regional Officer MPCB Thane
Sub-Regional Officer MPCB Tarapur-I
Chief Account Officer MPCB Mumbai
Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	249620	0049737	16.11.12	HDFC