

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l
3	BOD 3 days 27 deg. C.	Not to exceed	100 mg/l.
4	COD	Not to exceed	250 mg/l.
5	Oil & Grease	Not to exceed	10 mg/l.
6	TDS	Not to exceed	2100 mg/l.
7	Chlorides	Not to exceed	600 mg/l
8	Sulphates	Not to exceed	1000 mg/l
9	Phosphate	Not to exceed	5 mg/l
10	Chromium	Not to exceed	2 mg/l 🐁
11	Nickel	Not to exceed	3 mg/l 📃
12	Zinc	Not to exceed	5 mg/l 🛛 🔨 🔪
13	Mercury	Not to exceed	0.01mg/l
14	Lead	Not to exceed	0.1 mg/l

- (iv) **Trade Effluent Disposal:** The treated effluent shall be used on land for gardening within factory premises only. In no case, at any time effluent shall finds its way to any water body directly or indirectly.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

pended Solids 3 days 27 deg. C.	Notro exceed	100 mg/l 100 mg/l.
		100 mg/l.
L Dhasakata		
i Phosphate 🛛 👝 🖡	Not to exceed	5 mg/l.
l Nitrogen	Not to exceed	100 mg/l.
	Not to exceed	2100 mg/l.
eriology	Not to exceed	MPN/100 ml 500
I Residual Chlorine	Not to exceed	1 mg/l.
		I Nitrogen Not to exceed Not to exceed eriology Not to exceed

(vi) SewagerEffluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be cleaned periodically. Overflow, if any, shall be used on land for gardening/plantation only.

## (vii) Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	NOU	Treatment	Disposal
1	Steel Scrap	5.00	MT/M		Sale to authorized party

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

ł	Domestic purpose	200 CMD
li	Industrial Processing	150 CMD
lit	Industrial Cooling. Boiler	1400 CMD
iv	Agriculture / Gardening	CMD

The daily water consumption for the following categories is as under:

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

#### 5. CONDITIONS UNDER AIR ACT :

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

#### a. Control Equipment:

- I. Dust Collection system of sufficient capacity shall be provided to source of SPM/TPM.
- II. Adequate fume extraction system followed by dust collector of sufficient capacity shall be provided at all dust generating locations and operated properly.
- III. There shall not be any secondary (fugitive) emissions.

# b. Standards for Emissions of Air Pollutants:

		-	
Ī	SPM/TPM	Not to exceed	150 mg/Nm3
ii	SO <sub>2</sub>	Not to exceed	6769 Kg / Day.
	0		

## 6. Conditions for D.G.S

a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.

Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.

- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- g. D.G. Set shall be operated only in case of power failure the applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set. Standards for Stack Emissions:

••			
Sr. No.	Type Of Fuel	Quantity	UOM
1	FO	62	KL/D
2	LDO	60	KL/D
3	HSD	. 02	KL/D
4	LPG	5	T/D
		0	

(i) The applicant shall observe the following fuel pattern:

(ii) The applicant shall erect the chimney(s) of the following specifications:-

1	Sr. No.	Chimney Attached To	Height in feet.
	1.	RPE7*	158
	2. 5	SRM 7"	130
	32	RHF 14"	195
	A	WBF 14"	138
	5.	AUST 7"	110
	6.	AUST 14"	175
	7.	DG (125 KVA)	60
	8.	Thermopac	80
	9 OCTG Scrubber		35

(iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents

attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

(iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

### (v) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area. 💊
- 2) The industry should monitor stack emissions and ambient air quality regularly.

# 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

Sr. No.	Туре	Of Waste	Quantity	UOM	Disposal
1.	12.9 ETP	Sludge	5.30	MAN	CHWTSDF
2.	12.5 Pho	sphate Sludge	150	Kg/M	CHWTSDF
3.	12.3 Pick	ling Sludge	Cootx	Kg/M	CHWTSDF
4	Coolant s	ludge	15	T/A	CHWTSDF
5	21.1 Proc Residue Sludge	varnish	2000	Kg/M	CHWTSDF
6		/Spent Oil	300	Liter/M	Sale to Authorized Recycler / Reprocessor

(i) The industry shall handle hazardous wastes as specified below:

(ii) Treatment NI

The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.

Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

- 8. Industry shall comply with following general conditions:
  - i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
  - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
  - iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
  - iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
  - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
  - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
  - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
  - viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
  - As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
  - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.
- 10. Industry shall submit the Bank Guarantee of Rs. 5/- Lakhs validity of one year period in the Board within one month period towards operation and maintenance of ETP/STP so as to achieve consent standards / and compliance of the same.
- 11. The Consent is issued subject to the decision taken in the meeting of the Consent Appraisal Committee of the board held on 12.03.2013.
- 12. The total Capital investment of industry is Rs. 182.83 Corers.

For and On Behalf of the Maharashtra Pollution Confrol Board,

> (Rajeev Kumar Mital, IAS) Member Secretary

To, M/s. Maharashtra Seanless Ltd.

Pipe Nagar, Vill: Sokeli, NH-17, B.K.G. Road, Tal. Roha, Dist Raigad Copy to:

- RO Rabad / SRO- Raigad, MPCB, Navi Mumbai. – They are instructed to obtain B.G.O. Rs.5 Lakhs from industry and submit the Compliance report of the industry within one month period.

a. CAO/Cess Branch/Master File

Received Consent fee of –

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	3,65,000	467000	24/07/2012	State Bank of Patiala
2	14,89,200	467034	31/07/2012	State Bank of Patiala

Industry has paid consent fees of Rs.18, 54,200/- in the Board for 5 years period. Remaining fees Rs .7, 57,205 is balance with the Board.