MAHARASHTRA POLLUTION CONTROL BO

Tel: 24010437/24020781/24014701 Fax: 24024068 / 24023516 Website: <u>http://mpcb.gov.in</u> E-mail: <u>ast@mpcb.gov.in</u>



Kalpatani Porn., 2 Opp. Cine Planet C Near Sion Circle, Si Mumbai-400 022.

Red/L.S.I

Date: 2014-13

tm

Consent No: BO/AST/RO-KN/EIC No KN-6424-13/R/CC- 2910

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Reneval of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively

CONSENT is hereby granted to

M/s. U. P. Twiga Fiberglass Einner Plot No. N-40, ADDL MIDC, Ambarbart Dist. Thane-421506

located in the area declared under the provisions of the Water Act. Ain ac Authorization under the provisions of HW(M&H) Rules and amendments is subject to the provisions of the Act and the Rules and the Orders that m made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 30.06.2015

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum	Quantity
1	Fiberglass wool insulation	834 Mt/m.	

- 3. CONDITIONS UNDER WATER ACT:
- (i) The daily quantity of trade effluent from the factory shall not exceed 120.00 m³.
 (100% treated effluent shall be recycled in process so as to achieve zero discharge)
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 22.00
- (iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive consisting of primary / secondary and/or tertiary treatment as reference to influent quality and operate and maintain the sa as to achieve the quality of the treated effluent to the following

1	pH	Between 55 to 90
2	Suspended Solids	Not to exceed 100 mg/1
3	BOD 3 Days 27 °C	Not to exceed
4	COD	Not to exceed 250 mg/L
5	Oil & Grease	Not to exceed 10 mg/
6	TDS	Not to exceed 2100 mg/l.
7	Chlorides	Not to exceed 600 mg/l.
8	Sulphates	Not to exceed 1000 mg/1

SRO Kalyan II/I/R/L/86020000

(iv) Trade Effluent Disposal: The treated trade effluent shall be never achieve zero discharge as per their letter dtd. 21.07.20.2.405 mc effluent shall find its way outside the factory premises or to local mall

(v) Sewage Effluent Treatment: The applicant shall provide co treatment system as is warranted with reference to influent quality and maintain the same continuously so as to achieve the grafit effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soak soak pit, which shall be got cleaned periodically. Overflow, if any, shall be us on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

iii)Other Conditions: Industry should monitor effly

The applicant shall comply with the provisions of Control of Pollution) Cess Act, 1977 (to be eferred amendment Rules, 2003 there under

- The daily water consumption for the following categories is as 25.00 CMD
 - Domestic purpose (i)
 - (ii) Water gets Polluted & Pollutants are Biodegradable
 - (iii) Water gets Polluted, Pollutan
 - are not Biodegradable (iv) Industrial Cooling spiny
 - in mine pits or boiler feed
 - (v) Agriculture/Gardening

0.00 CMD 135.00 CMD

120.00 CN

40.00 CMD

The applicant shall regularly submit to the Board the returns of wat consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT:**

The applicant shall install a comprehensive control sys onsisting of control equipments as is warrantee of generation of emission and operate and man continuously so as to achieve the level of politic BHA standards:

a. Control Equipment:

- 1) Fume extraction system followed by dust collection system include cyclone, bag house provided to weighing, mixing section and Serie of sufficient capacity shall be provided to glass fibres, oven operate properly and continuously.
- 2) There shall not be any secondary (fugitive) emissions.

Conditions for D.G. Set b.

Noise from the D.G. Set should be controlled by providing a. acoustic enclosure or by treating the room acoustically.

- b. Industry should provide acoustic enclosure for control of mase acoustic enclosure/ acoustic treatment of the room state designed for minimum 25 dB (A) insertion loss or for meetine ambient noise standards, whichever is on higher side. A super exhaust muffler with insertion loss of 25 dB (A) shall also provided. The measurement of insertion loss will be done different points at 0.5 meters from acoustic enclosure/room accurate average.
- c. The industry shall take adequate measures for control of triss levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DC set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in complia recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance should be set and followed in consumanufacturer which would help to prever from deteriorating with use
- g. D.G. Set shall be operated only in case of power fa
- h. The applicant should not cause any nusance i area due to operation of D.G. Set

(ii) Standards for Stack Emissions

1	SPM/TPM	Not to exceed	150	mentruite
2	SO ₂ (Boiler)	Not to exceed	7	Kg/da
3	SO ₂ (DG Set)	Not to exceed	0.4	Kg/da

Sun

(iii)

The applicant shall observe the following fuel pattern:-

*	*	
Sr. No.	Type Of Fuel	Quantity
1.	HSD	20.00 Lits/day.
2	Propane	320.00 Kg/hr.
N		

The applicant shall erect the chimney(s) of the specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Batch house	16.00
2	Meter house	20.00
3	Suction hood & oven	35.00
4	D.G. set 1010 KVA	6.50 *
5	D.G. set 1240 KVA (2 nos.)	7.00 *
/+ 1		

(* Above the roof of the building in which it is installed)

2. The applicant shall provide ports in the chimney/(s) and facilities sich as ladder, platform etc. for monitoring the air emissions and the same sea the open for inspection to/and for use of the Board's Staff. The chimney, very attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification t

The industry shall take adequate measures for control of 3. own sources within the premises so as to maintain amount standard in respect of noise to less than 75 dB(A) during cay time an during night time. Day time is reckoned in between 6 a.m. night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding are
- 2) The industry should monitor stack emissions and ambient air qualit Regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDEING **TRANSBOUNDRY MOVEMENT) RULES, 2008:**

The Industry shall handle hazardous wastes as specified belo (i)

S	r. No.	Category	Type Of Waste	Quantity	Disposal
1		34.3	ETP Sludge	3 Mt/m.	
2			Waste Glass Wool	100 Kg/1	

- (ii) Treatment: - NIL
- The authorization is hereby granted to ope 1. storage, transport & disposal of hazardous maste
- $\mathbf{2}$. The industry should comply with the mazardous 2003.
- Whenever due to any accident or other unforeseen act or even emissions occur or is apprehended to occur in excess of standards laid such information should be forthwith Reported to Board, concerned Station, office of Directorate of Health Services, Department of Explo Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it should stopped.

8. Industry shall comply with following additional conditions:

- The applicant shall maintain good housekeeping and take adequate measures i. for control of pollution from all sources so as not to cause nuisance surrounding area / inhabitants.
- The applicant shall bring minimum 33% of the available open and under an ii. coverage/tree plantation.
- iii.
- Solid waste The non hazardous solid waste arising in sweepings, etc., be disposed of scientifically so as not it pollution. The applicant shall take necessary cermissions
- for disposal to dumping ground.
- The applicant shall provide for an alternate electric power source operate all pollution control facilities installed by he applicant iv. In the abs compliance with the terms and conditions of the consent applicant shall stop, reduce or otherwise, control production to abule & conditions of this consent regarding pollution levels.
- The applicant shall not change or alter quantity, quality, the mate temperature or the mode of the effluent / emissions or hazardous w control equipments provided for without previous written permissi Board.
- vi. The applicant shall provide facility for collection of environmental samples an samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

- vii. The applicant shall make an application for renewal of the cense days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every Environmental Statement Report for the financial year ending 3 the prescribed Form-V as pre the provisions of rule 14 of the hin (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's effice during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall be admitted in the way other than in designed and provided collection. System, Neither storm water nor discharge from other premises structure at a way other the flow the factory.

The consent should not be construed as any exemption from octain its necessary NOC from other Govt. agencies as may deemed in threes sy

- The industry shall also comply with the Industry specific notified under Environment Protection Act
- 11. This Board reserves the right to revoke, amend or add any condit in this consent and the same shall be binding on the Applicant.
- 12. This Consent is issued pursuant to the decision of taken in 20th CC meeting the on 15.3.2013 of the Board.

13. The Capital investment of the industry is Rs. 64.74Crore.

(Rajeev Kumar Mits) Member Secretary

M/s. U. P. Twiga Fiberglass Limited Plot No. N-40, ADDL MIDC, Ambernath Dist, Thane-421506

Copy to: 1) Regional Officer, MPCB, Kalyan & 2) Sub Regional Office Kalyan-II– They are directed to ensure the compliance of consent conditions 3) Chief Accounts Officer, MPCB, Mumbai 4] Cess Branch, MPCB 5 Mar

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	300000	556847	30 Nov 2012	SBI Bank
2	30000	557210	21 Dec 2012	SBI Bank
				经济的 化化化物 新教师 机制造 化化物制造 化化物

10.