MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: mpcb@vsnl.net



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Near Sion Circle, Sion (E)

Mumbai-400 022.

Red/L.S.I

Date:06 /04/2013

Consent No:BO/JD(APC)/EIC No. PN-14815-12/O/CC Price

Consent to Operate under Section 26 of the Water (Prevention & Connock Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Connock Pollution) Act, 1981 and Authorization / Renewal of Authorization with Rule 5 of the Hazardous Wastes (Management, Handling & Transform Wovement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules per pertively

CONSENT is hereby granted to

M/s.Ultra Engineers (Unit IV) Sector No.10,Plot No 58, PCNTDA, Bhosari,Pune-26

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to: 28/02/2014
- 2. The Consent is valid for the manufacture of -

	6067 - 67	1 187.04		346	170 (1)	ichtellie, souli ditteatifete fitt.	100 Hall 144
S.No	Product Name		Total			UOM	
1	Wind Mill Parts and Devices,		60		1 1	No/Month	
	Oil & Gas Components			188		No/Month	7770 (1470)

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 3 0 M
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 4 M

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

Sr.no	Parameter		Limits
1	рH	Between	5.5 to 9.0
2	ВФО	Not to exceed	30 mg/l
3	COD	Not to exceed	250 mg/l
4	Oil & Grease	Not to exceed	10 mg/l
5	Suspended Solids	Not to exceed	100 mg/l
6	TDS	Not to exceed	2100 mg/l
7	Sulphate	Not to exceed	11000 mg/J
8	Chloride	Not to exceed	600 me/
9	Phosphate	Not to exceed:	5 0 mg/1

- (iv) Trade Effluent Disposal: The treated industrial effluent shall be recy for maximum extent and remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall be recy for the maximum extent and remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall use on land for a remaining treated effluent shall be recycled to the remaining treated efficient shall be recycled to the remaining treated effluent shall be recycled to the remaining treated efficient shall be recycled to the remaining treated ef
- (v) Sewage Effluent Treatment: The applicant shall provide compreh is treatment system as is warranted with reference to influent quality and or rain and maintain the same continuously so as to achieve the quality of treated or her to the following standards.

(1)	1	Suspended Solids	Not to exceed	100 mg/l.
(2)		BOD 3 days 27o C.	Not to exceed	100 mg/l. 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

			do, 198. 40.		
	S.No.	Type	Qty	UOM	Disposal
	1	Metal scrap	1.0	MT/M	Sale
13.			2015/06/2 26/2 46	21.11 23.14	THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.

(viii) Other Conditions: Industry should monitor effluent quality regularly

4. The applicant shall comply with the provisions of the Water (Prevent in Second of Pollution). Cess Act, 1977 (to be referred as Gess Vet and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic	•••		5.0 CMD	
(ii) Industrial Processing	• • • •		4.0 CMD	
(iii) Industrial Cooling	•••	į.	0.0 CMD	
(iv) Agriculture / Gardening	•••		$0.0~\mathrm{CMD}$	

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT:**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
- a. Control Equipment: -
- Fume extraction system followed by dust collector system of sufficient capacity shall be provided to shot blasting section and all sources of SPM/TPM operated property continuously
- 2. There shall not be any secondary fugitive emission

b. Conditions for D.G. Set:.

- i) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- ii) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum? dB (A) insertion loss or for meeting the ambient noise standards, which we on higher side. A suitable exhaust muffler with insertion loss of 25 B shall also be provided. The measurement of insertion loss will be done different points at 0.5 meters from acoustic enclosure/room and the law as
- iii) The industry shall take adequate measures for control of noise lever from its own sources within the premises in respect of noise to less than dB(A) during day time and 70 dB(A) during the night time. Zave me is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m.
- iv) Industry should make efforts to bring down noise level due to DG set, putside industrial premises, within ambient noise requirements by proper sitting and control measures.
- v) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- vi) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- vii) D.G. Set shall be operated only in case of power failure
- viii) The applicant should not cause any nuisance in the sumpuncting area line operation of D.G. Set

6. Standards for Emissions of Air Pollutants:

(i) SRM/TPM Not to exceed 150 mg/Nm (ii) So2 Not to exceed 19 kg/day

The applicant shall observe the following fuel pattern:

18 18 18 18 18 18 18 18 18 18 18 18 18 1		1 19	 - 18 中側側側
Sr. No. Typ	e Of Fuel	Quantity	UOM
1 Die	esel	40	Lit/M

i) The applicant shall erect the chimney(s) of the following specifications:-

Sr. N	o. Chimney Attached To Height in Mtrs.		
1	D.G. Set (250 KVA) 3.5 mtr above roo	ftop	

The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by number su as S-1, S-2, etc. and these shall be painted/ hisplayed to facilities identification.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below

Sr. N. Type Of Waste	Quantity	UOM	Disposal
1 34.3 Chemical sludge	05	KG/Month	diwosdf 14
from waste water treatment			

(ii) Treatment: - NIL

- 1. The authorization is hereby granted to operate a facility for collection states transport & disposal of hazardous waste.
- 2. The industry should comply with the HAZARDOUS WASTE (MANAGEMENT) HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008.
- a. Whenever due to any accident or other unforeseen act or even, such emissions accurred or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Least Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the HAZARDOUS WASTE (MANAGEMENT HAND) & TRANSBOUNDRY MOVEMENT) RULES, 2008 and shown & submitted Board as & when asked for.

8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate mersure control of pollution from all sources so as not to cause nuisance to surrounding teaminabitants.
- ii. The applicant shall bring minimum 33% of the available open land under gree coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises sweepings, etc., be disposed of scientifically so as not to cause any nuisence pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environments sandle as samples of trade and sewage effluents, air emissions and hizzardus was as Board staff at the terminal or designated points and shall pay to the Board services rendered in this behalf.

vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

viii. The firm shall submit to this office, the 30th day of September every year the Environmental Statement Report for the financial year ending 31st March prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection (Second Amendment) Rules, 1992.

As inspection book shall be opened and made available to the

their visit to the applicant.

The applicant shall install a separate electric meter showing the consum energy for operation of domestic and industrial effluent treatment dan pollution control system. A register showing consumption of themicals treatment shall be maintained.

Xi. Separate drainage system shall be provided for collection of trade at effluents. Terminal manholes shall be provided at the end of collection arrangement for measuring the flow. No effluent shall be admitted in sewers down- stream of the terminal manholes. No effluent shall find its than in designed and provided collection System.

xii. Neither storm water nor discharge from other premises shall be allowed to mis

the effluents from the factory.

9. This is issued with approval of Consent Committee meeting of the Board held dtd. 15/03/2013.

10. You shall submit Bank Guarantee of Rs. 5/ Lakhs in favor of Regional Officer Pune within 15 days towards Operation & maintenance of pollution control system. The Bank Guarantee shall be valid up to one year period.

11. The Capital investment of the industry is Rs. 40,15/-Cr

Member

To. M/s.Ultra Engineers (Unit IV), Sector No.10, Rlot No 58, PCNTDA, Bhosari, Pune-26

RO-MPCB Pune /SRO-MPCB PC- They are directed to ensure compliance of consent condition & obtain the BG of Rs. 5/- Lakh from the industry & submit the report within 1 month period.

Received Consent fee of -

S.No.	Bank Name	DD. No.	DD. Dt.	Amount
1	Kotak Mahindra Bank Ltd.	423939	07/07/2012	50000/+
2	Kotak Mahindra Bank Ltd.	488210	27/06/2012	96250/-
3	Kotak Mahindra Bank Ltd.	499743	26/07/2012	74000/-

Copy to: