MAHARASHTRA	POLLUTION	CONTROL	BOAF
	and the second se		<u> </u>

Tel: 24010437/24020781/24014701 Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: mpcb@vsnl.net



Kalpataru Point, 2<sup>nd</sup> - 4<sup>th</sup> Fl. Opp. Cine Planet Cinema, Near Sion Circle, Sion (E) Mumbai-400 022.

Date: 06 /04 /2013

# Red/L.S.I

Consent No:BO/JD(APC)/EIC No. PN-16344-18/0/CC

Consent to operate under Section 26 of the Water (Prevention & Con Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Con Pollution) Act, 1981 and Authorization / Renewal of Authorization Rule 5 of the Hazardous Wastes (Management, Handling & Transbo Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respect

CONSENT is hereby granted to

M/s. Maschio Gaspardo India Ryt. Ltd. Plot No. F-27, MIDC Rahjangaon, Village Karegaon, Tal. Shirur, Dist. Pune 41,210

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to operate is granted for a period up to 28/02/201

2. The Consent is valid for the manufacture of –

1 mail and an		
Sr. No. Product Name	Maximum Quantit	
1 Rotavators		
(Agriculture equipments)	2000	Nos/Month

# 3. CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 60. 0 M<sup>3</sup>
(ii) The daily quantity of sewage effluent from the factory shall not exceed 16.40 M<sup>3</sup>

**Trade Effluent :** Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

	T.
e nsi ve	
perate	
ffuent	
<b>使</b> 性 新原 性	
d in a	12 12
d in a sed on	
d in a sed on	
sed on	
sed on	
ised on osal e	
sed on sal e	
ised on osal e	
sed on sal e	
sed on sal e trol	
ised on osal e e e e e e e e e e e e e e e e e e e	
sed on sal e trol	
ised on osal e e e e e e e e e e e e e e e e e e e	
ised on osal e e e e e e e e e e e e e e e e e e e	

i) Fume extraction system followed by Dust collection system of should be provided to all sources of SPM/TPM shall be open continuously 

i. i.

- ii) The industry shall take all necessary precautions to control noise pollution in the industrial activities and also nuisance due to vibration generated due to hammering operations. The industry shall take suitable acoustic measures including shielding enclosures noise barriers etc. to control the noise levels within norms stipulated to avoided nuisance in the surrounding
- iii) There shall not be any secondary (Fugitive) emissions.

#### **Conditions for D.G. Set**

Noise from the D.G. Set should be controlled by providing or by treating the room acoustically.

Industry should provide acoustic enclosure for control of noise. The correction enclosure/ acoustic treatment of the room should be designed for minimum 25 (A) insertion loss or for meeting the ambient noise standards which we is higher side. A suitable exhaust muffler with insertion loss of 25 de as shall a be provided. The measurement of insertion loss will be done at different points 0.5 meters from acoustic enclosure/room and then average.

The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckored between 6 a.m. to 10 p.m and night time is reckored between 10 p.m to 6 a.m.

d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.

Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

A proper routine and preventive maintenance procedure for DC set show and followed in consultation with the DG manufacturer which would prevent noise levels of DG set from deteriorating with use

D.G. Set shall be operated only in case of power failure

The applicant should not cause any nuisance in the surrounding area operation of D.G. Set

Standa	ards for	Emissions of	Air Pollutants:
839 C	(i)	SPM/TPM	Not to
	(ii)	So2	Not to
	(iii)	Acid Mist	Not to

Pollutants:		
Not to exceed	150	mg/Nm <sup>3</sup>
Not to exceed	28	Kg/day
Not to exceed	150	mg/Nm <sup>3</sup> Kg/day mg/Nm <sup>3</sup>

due

(i)

C.

g.

h.

The applicant shall observe the following fuel pattern:

					and the second		
	Sr.	No.	Type Of	Fuel	Quantity	UOM	
		1	HSI		60.0	Lit/hr	
SRO Punell//R/L/8135	58000		er en				

## The applicant shall erect the chimney(s) of the following specification

. No.	Chimney Attached To	Height in Mtrs.
1	Shot Blasting	1.0 above roof
2	Scrubber to degreasing	1.0 above roof
3	Paint booth	1.0 above roof
4	DG set (500 KVA)	4.5 above roof
5	Powder Coating Booth	1.0 above roof
6.	DG Set (250 KVA)	3.5 above roof

ii) The applicant shall provide ports in the chimney/(s) and facilitation and the same superior inspection to/and for use of the Board's Staff. The chimney(s) vents attached sources of emission shall be designated by numbers such as S-1, S-2, the shall be painted/displayed to facilitate identification.

#### (vi) Other Conditions:

 $\mathbf{Sr.}$ 

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regular

## CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING TRANSBOUNDRY MOVEMENT) RULES, 2008.

(i) The Industry shall handle hazardous wastes as specified below.

			A			그는 이 이 이 이 아이가 있는 것이 있어. 이 아이가 있는 것이 아이가 있었다. 것이 아이가 있는 것이 아이가 있었다. 것이 아이가 있는 것이 아이가 있는 것이 아이가 있는 것이 아이가 있는 것이 아이가 있었다. 것이 이 아이가 있었다. 것이 아이가 있었다. 것이 아이가 않았다. 것이 것이 아이가 있었다. 것이 아이가 있었다. 것이 아이가 있었다. 것이 것이 있었다. 것이 것이 것이 있었다. 것이 것이 있었다. 것이 것이 있었다. 것이 것이 것이 않았다. 것이 것이 있었다. 것이 것이 것이 있었다. 것이 것이 있었다. 것이 것이 있었다. 것이 있었다. 것이 있었다. 것이 것이 있었다. 것이 있었다
	Sr. N	Typ	e Of Waste	Quantit	UOM	Disposal
:	1	12.2	Akali residues	5.0	KG/M	CHWTSDF
	2	34.3	Chemical sludge from WWT	100	KG/M	CHWTSDR
	3	21.1	Waste and residue	10	KG/M	<b>OHWESDE</b>
-11			· · · · · · · · · · · · · · · · · · ·			HERERE FERTER EFFERTER ET TE STERRE FERTER ER

### (ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection transport & disposal of hazardous waste.

2. The industry should comply with the HAZARDOUS WASTE (MANAGEM HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008

Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down sind information shall be forthwith Reported to Board, concerned Police Section office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments the production process connected to it shall be stopped.

b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office. It shall be ensured that the Hazardous waste is handled, managed & displayed of strictly in accordance with the HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008 and shown & submitted to the Board as & when asked for.

#### 8. Industry shall comply with following additional conditions:

The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area inhabitants.

The applicant shall bring minimum 33% of the available pper coverage/ tree plantation.

- iii. Solid waste The non hazardous solid waste arising in the factory prosweepings, etc., be disposed of scientifically so as not to cause and rule pollution. The applicant shall take necessary permissions from the autori disposal to dumping ground.
  - The applicant shall provide for an alternate electric power source sufficient ic operate all pollution control facilities installed by he applicant to minimum compliance with the terms and conditions of the consent. In the absence rid applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge temperature or the mode of the effluent emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage affluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board environmental services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every yes Environmental Statement Report for the financial year ending 31<sup>st</sup> March prescribed Form-V as pre the provisions of rule 14 of the Environment Prov (Second Amendment) Rules, 1992.

ix. As inspection book shall be opened and made available to the Board's officers their visit to the applicant.

x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- Xi. Separate drainage system shall be provided for collection of trade and sware effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. This is issued with approval of Consent Committee meeting of the Board had dtd. 15/03/2013.

10.You shall submit Bank Guarantee of Rs. 5/ Lakhs in favor of Region. Pune within 15 days towards Operation & maintenance of polyuter system. The Bank Guarantee shall be valid up to one year period.

11. The Capital investment of the industry is Rs. 59.79-Crs

Member Secretary

### To,

M/s. Maschio Gaspardo India Pvt. Ltd. Plot No. F-27, MIDC Ranjangaon, Village Karegaon, Tal. Shirur, Dist. Pune 41 210

Copy to:

RO- MPCB Pune /SRO-MPCB Pune-II- They are directed to ensure the compliance of consent condition & obtain the BG of Rs. 5/-11 and from the industry & submit the report within 1 month period Received Consent file of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	Rs. 50,000/	000564	18/12/2012	HDFC Bank
2	Rs. 50,000/-	131498	05/01/2012	HDFC Bank

SRO PuneII//R/L/81358000