MAHARASHATRA POLLUTION CONTROL

24020781 / 24010437 Phone

24024068 / 24044532 Fax

Email mpcb@vsnl.net

Visit At: http://mpcb.gov.in



Kalpataru Point, 2nd, 3rd & 4th Opp. Cineplanet, Near Sion Circ Sion (E), Mumbai-400022

EIC No: MU-4656-13

Infrastructure Project/Orange/LSI

Consent No. MPCB/ROHQ/Mumbai/CE/CC/ 2903

Consent to Establish under Section 25 of the Water (Prevention Pollution) Act, 1974 & under Section 21 of the Air (Prevention) Pollution) Act, 1981 and Authorization / Renewal of Authorization Rule 5 of the Hazardous Wastes (Management, Handling) Movement) Rules 2008

CONSENT is hereby granted to,

M/s.Space Developer, Slum Rehabilitation Project

CTS No. 351, 351/1 to 351/110, 575, 575/1 to 9,

Villagae Kanjur Marg, Quarry Road, Off. LBS Marg

Bhandup (W), Mumbai

located in the area declared under the provisions of the Water Act. Air act and Authorization under the provisions of TWMM&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Establish is valid up to Commissioning of the Broject 5-years whichever is earlier

For development of and plot as new construction activities for construction Slum Rehabilitation Project of M/s. Space Developer at CTS No. 351, 351/110, 575, 575/1 to 9, Villagae Kanjur, Quarry Road, Off LBS Bhandup (W), Mumbai on Total plot area of 4470.28 sq.mtrs. & Prapased BUA (As per FSI) is 12474.70 sq.mtrs and Total BUA of 21,189.88 sq.n including it ilities of the project as per construction commencement certific issued by local body.

- CONDITIONS UNDER WATER ACT:
- The daily quantity of sewage effluent from construction project shall not exceed (i) 200.0 M³
- Sewage Effluent Treatment: The applicant shall provide comprehensive treatment (ii) system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

		7741 1 1978 W - ALIE
pH	Not to exceed	6.5 to 9.0
Suspended Solids	Not to exceed	100 mg
BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
Fecal Coliform	Not to exceed	500/100/1 mg/l.
Residual Chlorine	Not to exceed	01 mg/l.
Detergent	Not to exceed	01 mg/l.
Floating matters	Not to exceed	10 mg/l
	Suspended Solids BOD 3 Days 27 degree C Fecal Coliform Residual Chlorine Detergent	Suspended Solids BOD 3 Days 27 degree C Fecal Coliform Residual Chlorine Detergent Not to exceed Not to exceed Not to exceed

(iii) Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting, cooling of Air conditioners, gardening and rest shall be discharged into sewer line of local body. In no case, effluent shall find its way to any water body directly/indirectly at any time.

[The project proponent authorities should opt environmenta frequent technologies like ozonation, UV treatment etc by replacing chloring to the state of the state

(iv) Non-Hazardous Solid Wastes:

Sr. No	Type of Segregated solid waste	Quantity Kg/D	Treatment	Lispusa
1.	Wet Garbage	536	Treated in Organia Waste Converter	Use as Manure
2.	STP Sludge	30	Composting	
3.	Dry Garbage	231	•	Will be Handed over to MCGM

3. Other Conditions (during Construction Phase):

1. All activities shall be in resonance with the provisions of Indian Forest Act. 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.

2. This Consent to Establish is issued only for New Construction Development

Construction Project purposes.

3. No quarrying activities shall be commenced in the area unless appropriate permissions are obtained for a limited quarrying material results in construction of local residential housing and traditional road near material provided that such quarrying is not done on Forest Larges and material is not exported to the outside area.

There shall be no felling of trees whether on Forest, Government, Revenue

er Private lands except as per prevailing Rules.

Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable.

6. Near the activities that are related to water (like activity of water parks water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be

less than 5 mg/liter.

7. In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.

8. The Applicant shall prepare management plan for water harvesting, roof water reclamation, water/storm water conservation and implement the balbefore handling over of complex for occupation.

- 9. Applicant shall provide fixtures for showers, toilet, flushing and drinking should be of low flow either by use of aerators or pressure reducing or sensor based control.
- 10. The Applicant shall draw plans for the segregation of solid was biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e. vermicomposting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic commercial, and garden wastes, but does not include hazardous and medical wastes. The activities of bio-composting and engineered lands shall be as per the Municipal Solid Waste (M&H) Rules 2000.

 11. Applicant shall be responsible to take adequate precautionary in a second
- detailed in this consent.
- 12. The applicant/generator shall be responsible for safe and scient transportation, treatment and disposal of Bio-Medical Wiscons provisions made under the Bio-Medical Waste (Management & F provisions made under the Bio-Medical Waste (Manage Rules, 1998. Any activity as defined under BMW W obtain a separate Authorization from Maharashtra Polition Control
- 13. For disinfections of waste water ultra violet radiation shall be used in pla of chlorination.
- 14. Vehicles hired for construction activities should be operated only dia peak hours.
- 15. Ready mixed concrete used in building construction should apply separate for consent from the Board.
- 16. Applicant, during the construction stage shall provide
 - a. Septic tank and soak pit of adequate capacity for the domestic effluent generated due to workers residing at site.
 - b. Proper loading and arloading of construction material, excavated material and its proper disposal as per MSW (M&H) Rules 2000
 - Cutting of trees is not permitted, however in unavoidable condition necessary permission from the local body shall be obtained.
 - d. Green cel of 33% of the open space shall be developed.
- 17. E-Waste shall be disposed to authorized re processo
- The applicant shall comply with the provisions of the Wat & Control of Pollution) Cess Act, 1977 (to be referred as amendment Rules, 2003 there under,
 - The daily water consumption for the following categories is as under
 - (i) Domestic 233.0 CMD
 - (ii) Water gets Polluted &
 - Pollutants are Biodegradable
 - (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...
 - (iv) Industrial Cooling, spraying

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

- CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT 1981:
 - (i) The Applicant may install 2-nos of diesel generating sets (DG Sets) of capaci 320 KVA and 380 KVA and shall be equipped with comprehensive c system as is warranted with reference to generations of emissions and maintain the same continuously so as to achieve the the following standards:

a. Standards for Emissions of Air Pollutants:

(i) SPM/TPM

Not to exceed

150 mg/Nm3

(ii) SO2 (DG Set)

Not to exceed

-- Kg/day

(ii) The following measures shall be taken:

- a. Adequate mitigation measures shall be taken to control emissions of SO2, NOx, SPM, and RSPM.
- b. Applicant shall achieve following Ambient Air Quality standards.
- 1. SPM Not to Exceed (Annual Average) 140
 Not to Exceed (24 hours) 200

140 μg/ m3 200 μg/ m3

2. SO2 Not to Exceed (Annual Average) 60

 $\mu g/m3$

 $\mu g/m3$

Not to Exceed (24 hours) 80

60 μgr **n**n

3. NOx Not to Exceed (Annual Average)
Not to Exceed (24 hours)

8Ö **I 'uz' n** 3

4. RSPM Not to Exceed (Annual Average)
Not to Exceed (24 hours)

100 μg/m3

The applicant shall observe the following fuel pattern

Sr. No.	Type Of Fuel	Quantity
1	HSD	14 Kg/Hr

(iii) The applicant shall erect the chimney(s), of the following specifications:-

	Sr. No.	Chimney Attached To	Height above	the roof of
			building in which	it is installed
:	1.	320 KVA	3.5 Mtrs	each T
	2.	380 KVA	3.5 Mtrs	each

(iv) Conditions for D.G. Set:

- 1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by freating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient up standards, whichever is on higher side. A suitable exhaust with insertion loss of 25 dB (A) shall also be provided measurement of insertion loss will be done at different points in the interest from acoustic enclosure/room and then average.
 - The industry shall take adequate measures for control denoted bevels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the dight time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to the set outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding are due to operation of D.G. Set.

(v) Other Conditions:

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney's vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions
- c) Construction material shall be carried in enclosed vehicles during construction activities.

(vi) Conditions for Utilities like Kitchen, Eating Places etc:

- 1. The kitchen shall be provided with exhaust system chimney with oil catcher connected to chimney through ducting.
- 2. The toilet shall be provided with exhaust system connected no culmusthrough ducting.
- 3. The air conditioner shall be vibration proof and the noise states exceed 68 dB (A).
- 4. The exhaust hot air from A.C. shall be attached to Chimbe and a mtrs. higher than the nearest tallest building things cutting shall discharge into open air in such way that he musance is caused to neighbors.
- (vii) The Applicant shall take adequate measures for control of noise evels from its own sources within the complex (residential cum Commercial) in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.
- (viii) Construction equipments generating noise of less than 65/90 db(A) are permitted.
- (ix) No construction work is permitted during nighttime.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The applicant shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste Quantity UOM Disposal The applicant shall not generate any type of Hazardous Waste

- The applicant shall certify that the bricks used in construction are manufactured using the ash from Thermal Power stations if it is within a radius of 1 dike from Thermal Power Plant and submit the names of bricks manufactured. The art ican shall use fly ash based material/products as per the provisions of a said Notification of 14.09.1999 and as amended on 27.08.2003.
- 8. The applicant shall obtain Consent to Operate from Manarashtra Pollution Control Board before commissioning of the project
- 9. The applicant shall adopt environment friendly technology in development of the project.
- 10. The applicant shall take the proper remediation measures to ensure that the ground water and soil contamination is prevented and follow due diligence at the construction stage.
- 11. Energy conservation measures like installation of solar panels for lighting the area outside the building should be integrated part of the project design.
- 12. The applicant shall use fly ash based material/products as per the movie on fly ash Notification of 14.09.1999 and as amended on 27.08.2003

lumbai III/I/O/L/87624000

- 13. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
- 14. The applicant shall provide Environmental friendly road transportation by adopting mechanical type closed trucks for transportation of minerals & metals construction debris with effect from 1/04/2012.
- 15. The applicant shall comply with the conditions stipulated in Environment Clearance granted by GOM, vide no: SEAC2211/CR-97/TC-2, dt: 4/01/2013.
- 16. This is issued pursuant to the decision of <u>Consent Committee</u> of the Board in its meeting held on <u>15th March</u>, <u>2013</u>.
- 17. The applicant shall submit Bank Guarantee of Rs. 5 Lakhs towards compliance of Consent conditions and EC Conditions at Regional Office Mumbai within 15-days.
- 18. The Capital investment of the project is Rs. 54.19 Cr.

(Rajeev Kuman Mir.1) Member\Secretain

To, M/s.Space Developer, Slum Rehabilitation Project, CTS No. 351, 351/1 to 351/110, 575, 575/1 to 9 Villagae Kanjur, Quarry Road, Off. LBS Marg, Bhandup (W), Mumbai

Copy to-

- Regional Officer, MPCB, Mumbai He is directed to obtain necessary Bank Guarantee from the applicant and ensure compliance of consent conditions
- 2. Sub Regional officer, Mumbai-III MPCB.
- Chief Accounts Officer, Mumbai, MPCB.

Received consent fee of:

Sr. No. Amount	DD. No.	Date	Drawn On
Rs. 1,00,000/-	899383	07/12/2012	Bank of Baroda
2. Rs. 100/-	899384	07/12/2012	Bank of Baroda

4. Cess Branch, MPCB, Mumbai.

5. Master file.