MAHARASHATRA POLLUTION CONTROL

24020781 / 24010437 Phone

Fax 24024068 / 24044532

Email mpcb@vsnl.net

Visit At : http://mpcb.gov.in

EIC No: MU-4385-12

Infrastructure Project/Orange/LSI Consent No. MPCB/ROHQ/Mumbai/CE/CC 28

Consent to Establish under Section 25 of the Water (Prevention & Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Rule 5 of the Hazardous Wastes (Management, Handling & Transbound Movement) Rules 2008 Movement) Rules 2008

CONSENT is hereby granted to,

M/s.Mumbai Housing & Area Development Board, (A MHADA Unit), Redevelopment of transit camp into Transit, EWS, MIG Type tenements, At CTS No.145,Gavanpada, Mulund(E),Mumbai-81

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Establish is valid up to Commissioning 5-years whichever is earlier.

The Consent is valid for development of land /Plot as new construction Act for Redevelopment of transit camp into transit, EWS, MIC T tenements Project named as M/s.Mumbai Housing & Area Development Board, (A MHADA Unit), at CTS. No. 145, Gavanpada, Mulund(E), Mumbai -81 on total plot area of 18,614.00Sq.mtrs & Total BUA of 43,846.23sq.mtr including utilities of the project as per construction commencement cent issued by local body.

2. **CONDITIONS UNDER WATER ACT:**

- The daily quantity of sewage effluent from construction project shall not exceed 399,0 M³.
- Sewage Effluent Treatment: The applicant shall provide comprehensive treatment (ii) system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.



Kalpataru Point, 2nd, 3rd & 4th Opp. Cineplanet, Near Sion Circle Sion (E), Mumbai-400022,

(i)

1	pH	Not to exceed	6.5 to 90
2	Suspended Solids	Not to exceed	100 mg/1
3	BOD 3 Days 27 degree C	Not to exceed	100 mg/l
4	Fecal Coliform	Not to exceed	500/100/1 mg/l.
5	Residual Chlorine	Not to exceed	01 mg/l.
6	Detergent	Not to exceed	01 mg/l.
7	Floating matters	Not to exceed	10 mg/l

Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting, cooling of Air conditioners, gardening and rest shall be discharged into sewer line of local body. In no case, effluent shall find its way to any water body directly/indirectly at any time.

[The project proponent authorities should opt environmental fitten is technologies like ozonation, UV treatment etc by replacing chloring of the

(iv) Non-Hazardous Solid Wastes:

Sr.No	Type of Segregated solid waste	Quantity Kg/D	Treatment Disposal
1.	Dry Garbage	1106	NOT MCCM
2.	Wet Garbage	1659	Composting Used As Manuage

Other Conditions (during Construction Phase):

1. All activities shall be in resonance with the provisions of Indian Forest Act 1927 (16 of 1927), Forest (Conservation) Act. 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.

2. This Consent to Establish is issued only for New Construction/Developing Construction Project purposes.

- 3. No quarrying activities shall be commenced in the area unless appropriate permissions are obtained for a limited quarrying material required for construction of local residential housing and traditional road maintenance work, provided that such quarrying is not done on Forest Lance and the material is not exported to the outside area.
- 4. There shall be no felling of trees whether on Forest, Government Free or Private lands except as per prevailing Rules.

5. Extraction of Groundwater for the project shall require prior permits on the State Ground Water Authority or other relevant authorities, applicable.

Near the activities that are related to water (like activity of water parks) water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.

In order to ensure that the water from this project do not enter into ultride environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.

- 8. The Applicant shall prepare management plan for water harvesting, roofwater reclamation, water/storm water conservation and implement the same before handling over of complex for occupation.
- 9. Applicant shall provide fixtures for showers, toilet, flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.

10. The Applicant shall draw plans for the segregation of solid wastes biodegradable and non-biodegradable components. The biodegrad material shall be recycled through scientific in-house composting of ever

composting facility within premises) with the approval of loca

SRO Mumbai IV/I/O/L/85895000

(iii)

3.

proper demarked area shall be identified for collection & storage properly which, shall be finally disposed off at approved Municipal Soli Waste landfill site of local body environmentally acceptable location an method. It is clarified that the term solid waste includes domestic commercial, and garden wastes, but does not include hazardous and bio medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000

11. Applicant shall be responsible to take adequate precautionary measures as detailed in this consent.

12. The applicant/generator shall be responsible for safe and scientific collection transportation, treatment and disposal of Bio-Medical Waste as ner th provisions made under the Bio-Medical Waste (Management & Rules, 1998. Any activity as defined under BMW (VI& H) Rules obtain a separate Authorization from Maharashtra Pollution Congol

13. For disinfections of waste water ultra violet radiation shall be used to but of chlorination.

14. Vehicles hired for construction activities should be operated only peak hours.

15. Ready mixed concrete used in building construction should apply set for consent from the Board.

16. Applicant, during the construction stage shall provide

- a. Septic tank and soak pit of adequate capacity for the effluent generated due to workers residing at site.
- b. Proper loading and unloading of construction material, exca material and its proper disposal as per MSW (M&H) Rules 2000.
- c. Cutting of trees is not permitted, however in unavoidable conditions necessary permission from the local body shall be obtained.

 \mathbf{CMD}

d. Green belt of 33% of the open space shall be developed.

17. E-Waste shall be disposed to authorized re processor.

The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and 4. amendment Rules, 2003 there under,

The daily water consumption for the following categories is as under 499.0IOMD

- Domestic (i)
- (ii) Water gets Polluted &
- Pollutants are Biodegradable ...
- (iii) Water gets Polluted, Pollutants

are not Biodegradable & Toxic ... (iv) Industrial Cooling, spraying

The applicant shall regularly submit to the Board the returns of water onsumption in the prescribed form and pay the Cess as specified ection 3 of the said Act.

CONDITIONS UNDER AIR (Prevention & Control of Pollution) 5. 1981:

- (i) The Applicant may install 1-nos of diesel generating sets (DG Sets), of capacity 1010 KVA and shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
 - **Standards for Emissions of Air Pollutants:**

(i) SPM/TPM (ii) SO2 (DG Set) Not to exceed Not to exceed (iii)The following measures shall be taken:

a. Adequate mitigation measures shall be taken to control emissions SO2, NOx, SPM, and RSPM. b. Applicant shall achieve following Ambient Air Quality standards $\mu g/m3$ SPM Not to Exceed (Annual Average) 140 1. Not to Exceed (24 hours) 200 $\mu g/m3$ SO₂ Not to Exceed (Annual Average) 60 $\mu g/m3$ 2.80 Not to Exceed (24 hours) $\mu g/m3$ NOx Not to Exceed (Annual Average) 60 $\mu g/m3$ 3. Not to Exceed (24 hours) 80 RSPM Not to Exceed (Annual Average) 4. Not to Exceed (24 hours) (iv) The applicant shall observe the following fuel patter Quantity **Type Of Fuel** Sr. No. 100 Ke/Hr HSD 1 (v)The applicant shall erect the chimney(s) of the following specifications:-Chimney Attached To Height above the roof of Sr. No. building in which it is installed 1010 KVA 6.5 Mtrs each

(vi)Conditions for D.G. Set:

- 1. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient moise standards, whichever is on higher side. A suitable exhaust minifier with insertion loss of 25 dB (A) shall also he provided measurement of insertion loss will be done an different point meters from acoustic enclosure/room and then average The ondustry shall take adequate measures for control

levels from its own sources within the premises in respect of

- less than 75 dB(A) during day time and 70 dB(A) during the his time. Day time is reckoned between 6 a.m. to 10 p.m and night mine
- reckoned between 10 p.m to 6 a.m.
- Industry should make efforts to bring down noise level due to outside industrial premises, within ambient noise requirem proper sitting and control measures.
- Installation of DG Set must be strictly in compliance v recommendations of DG Set manufacturer.
- A proper routine and preventive maintenance procedure for DG set 6. should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- D.G. Set shall be operated only in case of power failure.
- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

vii)Other Conditions:

The applicant shall provide ports in the chimney (s) a)|| ladder, platform etc. for monitoring the air emission be open for inspection to/and for use of the Board's Staff. The binney (s) vents attached to various sources of emission shall be design red by numbers such as S-1, S-2, etc. and these shall be painted/ displayer to facilitate identification.

- b) Water spraying shall be done on ground to avoid fugitive emissions
- c) Construction material shall be carried in enclosed vehicles during construction activities.

(viii)Conditions for Utilities like Kitchen, Eating Places etc:

- 1. The kitchen shall be provided with exhaust system chimney with oil catcher connected to chimney through ducting.
- 2. The toilet shall be provided with exhaust system connected to chimne through ducting.
- 8. The air conditioner shall be vibration proof and the noise stall exceed 68 dB (A).
- 4. The exhaust hot air from A.C. shall be attached to Chimne Say that mtrs. higher than the nearest tallest building through the proshall discharge into open air in such way that no musant act recorneighbors.

(ix)The Applicant shall take adequate measures for control of noise evers from its own sources within the complex (residential cum Commercial) in espect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 pm. and Neghtime is reckoned between 10 p.m. to 6 a.m.

(x) Construction equipments generating noise of less than 65/90 db(A) are permitted.

(xi)No construction work is permitted during nighttime.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The applicant shall handle hazardous wastes as specified below.

- Sr. No.Type Of WasteQuantityUOMDisposalThe applicant shall not generate any type of Hazardous Waste
- 7. The applicant shall certify that the bricks used in construction are manufactured using the ash from Thermal Power stations if it is within a radius of 100 k of finance of bricks manufacturer. The applic shall, use fly ash based material/products as per the provisions of the Notification of 14.09.1999 and as amended on 27.08.2003.
- 8. The applicant shall obtain Consent to Operate from Manaras Pollution Control Board before commissioning of the project.
- 9. The applicant shall adopt environment friendly technology in development of the project.
- 10. The applicant shall take the proper remediation measures to ensure that the ground water and soil contamination is prevented and follow due diligence at the construction stage.
- 11. Energy conservation measures like installation of solar panels for lighting the area outside the building should be integrated part of the project design.
- 12. The applicant shall use fly ash based material/products as per fly ash Notification of 14.09.1999 and as amended on 27.08.2003.

(i)

- 13. This Board reserves the right to amend or add any conditions in this consult at the same shall be binding on the Applicant.
- 14. The applicant shall provide Environmental friendly road transportation by adopting mechanical type closed trucks for transportation of minerals & metals construction debris with effect from 1/04/2012.
- 15. The applicant shall comply with the conditions stipulated in <u>Environment</u> <u>Clearance</u> granted by GOM, vide no: <u>SEAC-2009/CR.22/TC.2</u>, dt: 17/10/2010.
- 16. The applicant are hereby directed to submit resolution form company's Board within one month period stating that you have started construction activity without obtaining consent from the Board and violated the provisions of Environmental laws and in future you will no do such violations. If applicant fails to submit the above such resolution within one month period consent will be treated as cancelled, but conshall submit a separate Bank guarantee of Rs. 20 Lakis and compliance of the same.
- 17. The applicant shall submit <u>Bank Guarantee of Rs. 5 Lakhs</u> towards compliance of consent conditions at Regional Office, MPCB, Mumbai within <u>15-days</u>.
- 18. This is issued pursuant to the decision of <u>Consent Committee</u> of the Board in its meeting held on <u>15th March, 2013.</u>

(Rajeev

19. The Capital investment of the project is Rs. 76.54 Cr.

(F M/s.Mumbai Housing & Area Development Board, (A MHADA Unit), Redevelopment of transit camp into transi EWS,MIG Type Tenements, CTS No.145, Gavanpada, Mulund(E),Mumbai 81

Copy to-

1.

2.

3.

- Regional, Officer, MPCB, Mumbai He is directed to obtain necessary Guarantee from the applicant and ensure compliance of consent conditions Sub Regional officer, Mumbai-IV, MPCB,
- Chief Accounts Officer, Mumbai, MPCB,

Sr. No. Amount DD. No.

Received consent fee of:-

Sr. No.	Amount	DD. No.	Date	Drawn On	
1.	Rs. 1,00,100/-	147245	29/11/2012	Bank of Maharashtra	
2.	Rs. 25,000/-	147307	1/12/2012	Bank of Maharashtra	

Cess Branch, MPCB, Mumbai.

5. Master file.

SRO Mumbai IV/I/O/L/85895000