

# MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781  
/4037124/4035273  
Fax : 24044532/4024068 /4023516  
Email : enquiry@mpcb.gov.in  
Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga  
Scheme Road No. 8, Opp. Cine Planet Cinema, Near  
Sion Circle, Sion (E),  
Mumbai - 400 022

Red/M.S.I

Date: 23/04/2013

Consent No: BO/AS(T)/O/EIC NO.PN-16400-13/CC- 3514

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Tata Johnson Control Automotive Ltd.  
Plot No. 1, S.No 235/245, Hinjewadi,  
Tal.- Mulshi, Dist- Pune, Maharashtra

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.01.2016
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Polymerized Polyurethane Foam (Only by mixing and polymerization activity)	12500	Nos./M
2	Seat	50000	Sets /M
3	Trim	50000	Sets /M
4	Foam } Without Chemical processing and painting	30000	Sets /M

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall be NIL.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 50.00M<sup>3</sup>.

(iii) Trade Effluent : NIL

(iv) Trade Effluent Disposal: N.A

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27° C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	Scrap Fabric Material	30000.00	Kg/M	Sale to authorised part
2	Scrap plastic, polythene and cotton boxes	10000.00	Kg/M	
3	Scrap wooden pallets and plankss	1000.00	Kg/M	
4	MS scrap	5000.00	Kg/M	
5	Waste Scrap	5000.00	Kg/M	

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. **The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

- (i) Domestic purpose ... 72.5 CMD
- (ii) Water gets Polluted & Pollutants are Biodegradable ... 6.00 CMD
- (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ... 0.00 CMD
- (iv) Industrial Cooling, spraying in mine pits or boiler feed ... 1.00CMD
- (v) Agricultural / Gardening ... 10.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT:**

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. **Control Equipment:**

- i. Air pollution control system of adequate capacity should be provided to limit emissions and also to any other sources of emissions.
- ii. Industry shall provide dust collector of sufficient capacity to control the emissions.

b. **Standards for Emissions of Air Pollutants:**

- (i) SPM/TPM Not to exceed 150.0 mg/Nm<sup>3</sup>
- (ii) SO<sub>2</sub> Not to exceed 80.0 kg/day

6. **Standards for Stack Emissions:-**

- (i) **The applicant shall observe the following fuel patten:-**

Sr. No.	Type Of Fuel	Quantity	UOM
1	HSD	3840.00	Lit/day

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	DG Set (380 KVA)	4.00
2	DG Set (500 KVA)	5.00
3	DG Set (100 KVA)	10.00
4	Fire Hydrant Pump	10.40
5	Welding exhaust	11.00

- (iii) Emissions standards for VOCs (General) from Process Vents:-

Sr. No.	Petrochemical process/ Compounds	Maximum emission Lin (mg/Nm <sup>3</sup> ), Dry basis
1	MA, PA, Phenol	20
2	Ethyl benzene (EB), Styrene, Toluene, Xyle Aromatics, EG, PG	100
3	Non-Methane HC (paraffin), Acetate, Olefins	150

The industry should phase out the Ozone Depleting Substances (ODS) as per ODS Rules 2000 and should be informed to MPCB within a period of 3 months.

**Guidelines for Fugitive Emission Control:-**

1. Fugitive Emissions over reactors, formulation areas, centrifuges, chemical loading, transfer areas etc. are yet to be collected through hoods and ducts by induced drafts and controlled by scrubber / dust collector.
  2. Usually scrubbers installed for channelized emissions are used for fugitive emissions to control also and sometimes dedicated scrubbers are provided. This practice may be permitted as long as tall gas concentrations are within the prescribed limits.
  3. In addition, organic gaseous emissions (odour & toxic) be routed to activated carbon beds (adsorption) or to thermal oxidizer and for dust emissions cyclones / bag filters are to be provided.
  4. Emphasis be given to solvent management / solvent loss prevention.
  5. Enclosures to chemical storage area, collection of emissions from loading of raw materials, in particulars, solvents through hoods and ducts by induced drafts, and controlled by scrubber / dust collector or to be ensured.
  6. Vapour balancing, nitrogen blanketing ISO tanks etc. to be provided; besides special care needs to be taken for control in respect of odorous chemicals.
- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70

dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly

**7. Conditions for D.G. Set :-**

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG-Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

**8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:**

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	3.3 Sludge & filters contaminated with oil	25.00	Nos/M	CHWTSDF
2	5.1 Used /spent oil	650.00	Lit/Month	CHWTSDF
3	5.2 Waste / residue containing oil	50.00	Kg/M	CHWTSDF
4	33.1 Chemical containing residue from decontamination	150.00	Kg/M	CHWTSDF
5	33.3 Discarded containers / barrels / liners	1530.00	Nos/ M	Sale to authorized reprocessor

(ii) Treatment: - NIL

9. Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

**10. Industry shall comply with following additional conditions:**

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30<sup>th</sup> day of September every year, the Environmental Statement Report for the financial year ending 31<sup>st</sup> March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.

- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
11. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
12. This consent is issued as per the decision taken in the meeting of the Consent Committee of the Board held on 05/04/2013.
13. Industry shall submit the Bank Guarantee of Rs 3 lakhs towards decontamination of contaminated drums before its disposal to the party other than CHWTSDF in favour of "Regional Officer, MPCB, Pune" within 15 days.
14. This is issued as per the power delegated by office order dated 09/04/2013.
15. The Capital investment of the industry is Rs. 57.30 Crores (Existing C.I. Rs. 52.98 Crores + Expansion Rs. 4.32 Crores)

*(P. K. Mirashe)*  
 (P. K. Mirashe)  
 Assistant Secretary (Technical)

To,  
 M/s Tata Johnson Control Automotive Ltd.  
 Plot No. 1, S.No 235/245, Hinjewadi,  
 Tal.- Mulshi, Dist- Pune, Maharashtra

Copy to :

- 1) RO, Pune /SRO, Pune II  
 -- They are directed to obtain the the Bank Guarantee of Rs 3 lakhs towards decontamination of contaminated drums before its disposal to the party other than CHWTSDF within 15 days and ensure the compliance of consent conditions.

- 2) CAO/Cess Branch/Master file.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	300100/-	182539	18 Dec 2012	Corporation Bank
2	18000/-	182540	18 Dec 2012	Corporation Bank