

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 220424068

Email : jdwater@mpcb.gov.in



Kalpataru Point
02nd, 03rd & 04th floor
Opp. Cineplanet
Near Sion Circle, Sion (E),
Mumbai- 400 022

Visit At : <http://mpcb.gov.in>

Red/LSI

Date: 30/05/2013

Consent No: BO/JD(WPC)/EIC No PN- 14718 -12/R/CC-4646

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

CONSENT is hereby granted to

Shriram SSK Ltd. (Distillery)

Nira Vally Arkshala Vibhag, At. Phaltan, Tal. Phaltan, Satara
Satara-415523

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.08.2016.
2. The Consent is valid for the manufacture of -

| Sr. No. | Product Name | Maximum Quantity | UOM |
|---------|--------------------|------------------|------|
| 1 | Industrial Alcohol | 750 | KL/M |
| 2 | ENA | 150 | KL/M |
| 3 | Fuse Oil | 1.5 | KL/M |

(The distillery should remain closed during rainy season i.e from 10th June to 10th Sept. every year.)

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 265.00M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 25.00M³.
- (iii) Trade Effluent :

Treatment: The applicant will provide comprehensive treatment consists of bio-methanisation / reboiler is as primary followed by well designed aerobic composting. The arrangement shall be leaked proof and no effluent or leakages/seepages shall find its way into environment thereby causing pollution of surface/ground/generated water.

Conditions for Aerobic Composting:

- i. The spent wash should be stored in impervious tanks. The spent wash tanks should have proper lining with HDPE and should be kept in proper condition to prevent ground water pollution. As per the CPCB recommendation and undertaking given by the company, storage should not exceed 30 days capacity.

ii. Applicant shall ensure availability of adequate filler material such as press mud, bagasses, agricultural, biological waste as required for effective composting system.

iii. Composted material shall meet the following specifications—

| | |
|-------------|---------------|
| Moisture | ... 30 to 35% |
| C/N | ... Below 17 |
| Nitrogen | ... 1.5 to 2% |
| Phosphorous | ... 1.5 to 2% |
| Potassium | ... 3 to 4% |

iv. The composting site shall be prepared as per the guideline. Composting shall be such that it includes mechanical mixing and spraying of spent wash along with mechanical aeration to ensure thorough composting. Hand/ manual spraying of spent wash shall not be permitted.

v. The compost leachate (1 gr. of compost mixed with 100 ml. of distilled water and filtered) Filterate shall conform to the following limit.

| | | |
|-----------------------|---------------|------------|
| pH | Between | 7.5 to 8.0 |
| BOD 3 days 27 Deg. C. | Not to exceed | 30 mg/l. |

vi. A pucca leak proof guard pond of 30 days holding capacity as per (i) above shall cope up with the effluent discharge during short term process disturbances. In case of prolonged disturbance in effluent treatment and disposal system, distillery shall be shut down and shall not be restarted without rectifying the system.

vii. The composting site/pits shall be made leak proof by proper lining. A catch drain shall be provided around the composting site to collect the storage pond for application on compost depots. Arrangements for overturning of compost material in windrows and spraying of spent wash shall be made to ensure appropriate aeration and uniform distribution of spent wash.

viii. In case of composting in open fields, the application of spent wash shall stop by end of April, so that compost is ready and the site is cleared of the composted manure before monsoon (i.e. 31st May). The manure shall be collected and stored on a raised platform with suitable rain cover so that the compost manure is not washed away by rain/runoff.

ix. Characteristic of soil, ground water and effect on crop yield should be monitored in the area where compost is used as manure and results thereof shall be compiled and reported in the Environment statement to be submitted every year.

x. The test wells shall be provided around the compost site for ground water monitoring. The well water quality has to be maintained at 2006 level.

xi. Top pullover impervious sheets shall be provided for entire compost yard, press mud and compost storage so as to cover the same during untimely rains and idles period.

xii. The operation of distillery should be restricted to 270 days in a year and that it will not operate during rainy season.

(iv) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

| | | | |
|-----------------------|---------------|-----|-------|
| (1) Suspended Solids | Not to exceed | 100 | mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

| Sr. No. | Type Of Waste | Quantity | UOM | Treatment | Disposal |
|---------|---------------|----------|----------|---------------|-------------|
| 1 | Yeast Sludge | 500.00 | Kg/Annum | Mixed Compost | By sale |
| 2 | Compost | 18360.46 | MT | | Used manure |

(viii) Other Conditions: Industry should monitor effluent quality regularly.

4. CONDITIONS FOR MOLASSES STORAGE:

- i) The molasses shall be properly collected and stored in steel tanks which shall be absolutely leak proof. At no stage of handling of molasses, there shall be leakage or spillage.
- ii) The capacity of tanks for storage of molasses shall be such that at no time the molasses shall be required to be stored in kutchha pits. Adequate space storage capacity shall be available to take care of bumper production of sugar, non-lifting of molasses etc.
- iii) All the area on which molasses are stored and handled should be provided with drain for diverting the spills to the treatment plant/ molasses tank. Suitable arrangements for accidental discharges of molasses from the tanks shall be provided to contain the same within factory premises.
- iv) Destruction of molasses and its disposal shall not be done without specific permission in writing from the authorized officer of the Board, intimation of intention to destroy or dispose of the molasses shall be given to the Board at least 15 (fifteen) days in advance by registered post under intimation to the Sub-Regional officer and Regional officer of the Board under whose jurisdiction the factory is situated.
- v) The storage tanks shall be kept in good conditions all the year round with adequate maintenance. The tanks size and capacity per cm, height, total capacity in tones shall be displayed prominently near the tank.
- vi) The above conditions shall be in addition to and not in derogation of the provisions contained in the "Bombay Molasses Rules, 1955" and "Maharashtra Molasses Storage and Supply Regulation, 1965".
- vii) The industry should monitor effluent quality regularly.

5. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- | | | |
|---|-----|------------|
| (i) Domestic purpose | ... | 30.00 CMD |
| (ii) Water gets Polluted & Pollutants are Biodegradable | ... | 265.67 CMD |
| (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic | ... | 0.00 CMD |
| (iv) Industrial Cooling, spraying in mine pits or boiler feed | ... | 67.33 CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) **Control Equipment:** Industry shall Operate and maintain Dust collector provided of sufficient capacity to achieve consented standards.

b) **Standards for Stack Emissions:**

- 1) SPM Not to exceed 150 mg/Nm³
- 2) SO₂ Not to exceed 180 Kg/Day

(ii) **The applicant shall observe the following fuel pattern:-**

| Sr. No. | Type Of Fuel | Quantity | UOM |
|---------|--------------|----------|----------------------|
| 1 | Bagasse | 2.50 | MT/Day |
| 2 | Methane Gas | 9165 | Nm ³ /Day |

(iii) **The applicant shall erect the chimney(s) of the following specifications:-**

| Sr. No. | Chimney Attached To | Height in Mtrs. |
|---------|---------------------|-----------------|
| 1 | Boiler | 30.00 |
| 2 | DG Set (380KVA) | 4.00 * |

(* above the roof of the building in which it is installed)

(iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2 etc. and these shall be painted/ displayed to facilitate identification.

(v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

7. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f. D.G. Set shall be operated only in case of power failure
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

| Sr. No. | Type Of Waste | Quantity | UOM | Disposal |
|---------|----------------------------|-----------------------|-----|--|
| 1 | 20.3 Distillation residues | As and when generated | | Mixed with press mud & converted to Bio-compost. |

(ii) Treatment: -

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M, H & TM) Rules, 2008.
 - a. Whenever due to any accident or other unforeseen act or even such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
 - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.

9. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
10. The Board reserves the right to amend or add any condition in this consent and same shall be binding on the applicant.
11. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
12. The industry shall submit the fresh Bank Guarantee of Rs. 2.0 Lakh towards continuous compliance of CREP Norms. The Bank Guarantee shall be valid upto the consent validity and submitted in favor of the Regional Officer, Pune within 15 days period.
13. The consent is issued as per the decision of Consent Committee meeting held on 06.05.2013.
14. The Capital investment of the Distillery Unit is Rs. 8.33 Crs. (Total C.I of the Industry including Sugar is Rs. 26.02 Crs.)

For and on Behalf of the
Maharashtra Pollution Control Board,

(Rajeev Kumar Mital, IAS)
Member Secretary

To,
M/s. Shriram SSK Ltd. (Distillery)
(Nira Vally Arkshala Vibhag,)
At. Phaltan, Tal. Phaltan, Satara
Satara -415523

Copy to:

Regional Officer, MPCB, Pune / Sub-Regional Officer, MPCB, Satara

– They are directed to collect the Bank Guarantees from industry within 15 days and ensure the compliance of the consent conditions.

CAO / Cess wing

Received Consent fee of -

| Sr. No. | Amount(Rs.) | DD. No. | Date | Drawn On |
|---------|-------------|---------|-------------|----------|
| 1 | 40000 | 745861 | 27 Jun 2012 | SBI Bank |
| 2 | 5250 | 673373 | 23 May 2013 | SBI Bank |

* The previous balanced fees of Rs. 60,000/- is utilized from the fees submitted by the industry i.e Rs.80,000/- Submitted vide D.D No.015489 dt.10.06.2010 of DDC Bank, Satara & Rs.20,000 Submitted vide DD No.015484 dt.07.06.2010 of DDC Bank, Satara.