MAHARASHATRA POLLUTION CONTROL BOARD

Phone:

24020781 / 24010437

Fax

24024068 / 24044532

Email

Visit At :

http://mpcb.gov.in



Kalpataru Point, 2nd, 3rd & 4th Floor, Opp. Cineplanet, Near Sion Circle, Sion (E), Mumbai-400022.

Orange/L.S.I

Consent No: BO/RO (HQ)/NM-3670-12/AMD/C-5045 Date:

11/06/2013

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. APM Terminals India Pvt. Ltd. 5/18, Sector-6, Dronagiri Warehousing Complex, Navi Mumbai,,Maharashtra-400707

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to Operate is granted for a period up to: 30/11/2013.
- 2. The Consent is valid for the manufacture of -

S	Product Name	·1.7	marayiy.
200		waximum.	
1	Container Yard (Container Freight Station)	- Quantity	
1	Container Freight Station)	,	ļ
	All types of Cargo warehousing complex		
	(Handling of all types of Containerized /non		
	containerized Cargo & storage, which & inside		
	company premises including handling &		
्र	storage of Chemicals)		

This consent is granted subject to condition that at no time threshold quantities should be exceeded the limit prescribed under the MSIHC Rules 1989 & the temporary stack storage should not store the containers beyond the statutory period & should ensure that the containers are not damaged, so as to prevent any sort of spillage or overflow or discharge of any chemicals outside the containers. The containers shall not open at all.

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 0.00M3.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 5.00M3.

(iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

	T T		
1	pH	Between	5.5 to 9.0
2	Temperature	Should not exceed 5 c above the ambient temperature of the	3.5 (0 9.0
		receiving body	
3	Oil & Grease	Not to exceed	10 mg/4
4	Suspended Solids	Not to exceed	100 mg/l.
5	Cyanide (as 'CN')	Not to exceed	0.2 mg/l.
6	Ammonical nitrogen (as N)	Not to exceed	50 mg/l.
7	Total residual chlorine (as Cl2)	Not to exceed	1.0 mg/l.
8	Cadmium (as Cd)	Not to exceed	2.0 mg/l
9	Nickel (as Ni)	Not to exceed	3.0 mg/l
10	Zinc (as Zn)	Not to exceed	5.0 mg/l
11	Chromium as Cr Hexavalent Total		0.1 mg/l.
12	Copper (as Cu)	Not to exceed	3.0 mg/l.
13	Lead (as Pb)	Not to exceed	0.1 mg/l.
14	Iron (as Fe)	Not to exceed	3.0 mg/l.
15	Total metal	Not to exceed	10.0 mg/l.

- (iv) Trade Effluent Disposal: The metal bearing industrial effluent shall be segregated and reused back into process and remaining treated effluent shall use on land for gardening. There shall not be any discharge outside the factory premises. The industry shall become member of CETP as and when proposed. Industry shall provide necessary facilities to recycle the entire industrial effluent back into the process in six months.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

Suspended Solids Not to exceed 100 mg/l.
(2) BOD 3 days 270 C. Not to exceed 100 mg/l.

- (vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.
- (vii) Non-Hazardous Solid Wastes:

Sr. No: Type Quantity UOM Treatment Disposal Waste

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

9.00 CMD

(ii) Water gets Polluted &

Pollutants are Biodegradable ...

0.00 CMD

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...

 $0.00~\mathrm{CMD}$

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

0.00CMD

The applicant shall regularly submit to the Board the returns consumption in the prescribed form and pay the Cess Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment:

Industry shall provide dust collection system of sufficient capacity to control the emissions

6. Conditions for D.G. Set

a. Noise from the D.G. Set should be controlled by providing an

acoustic enclosure or by treating the room acoustically.

b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

- The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. Standards for Stack Emissions:

(i) SPM/TPM

Not to exceed

 50 mg/Nm^3

(ii) SO₂

Not to exceed

10 Kg/Da

(i) The applicant shall observe the following fuel pattern:

1 Discol 1200.00	No. Type Of Fu	l Quantity	MEMUOME	
1 Diesei 320.00 Tr/day	Diesel	320.00	/ Dtr/day	SCH PAR

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chinney At	tached To	Height in Mars.	
1	D.G. Set		05 above roof	

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

Öther Conditions: '

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

8. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Wast Quantity UOM Disposal

- (ii) Treatment: NIL.
- 1. The authorization is hereby granted to operate a facility for collection, storage & disposal of hazardous waste.
- 2. The industry should comply with the Hazardous Waste (MH & TM) Rules, 2008.
 - a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
 - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
 - c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (MH & TM) Rules, 2008 and shown & submitted to the Board as & when asked for.
- 9. Industry shall comply with following additional conditions:
 - The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
 - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
 - iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 10. The industry shall not exceed the quantity of containers beyond the threshold quantity mentioned in the MSIHC Rules. 1989 and shall comply with other Environmental norms.
- 11. The industry shall strictly adhere to the provision of MSIHC Rules 1989 & EIA notification-2006.
- 12. The project proponent shall furnish the Bank Guarantee of Rs.05 lakhs within 15 days from the date of issue of said consent, ensuring the compliance as per consent conditions. The Bank Guarantee will be valid for a period of operation of the stack terminal facility.

- 13.Industry shall implement the notification issued by Ministry of Environment & Forest, Govt. of India. Dated 18th March 2008 for storage of volatile liquids.
- 14. This consent is issued with overriding effect to the consent granted earlier vide no- BO/MPCB/RO (HQ)/HSMD/44/10: Dated-3/5/2010.
- 15. This consent is issued pursuant to the decision of Consent Committee Meeting of the Board held on 06.05.2013 & under taking submitted by you vide letter datd-5/6/2013 (FTS no.130607 FT-138).
- 16.You shall not exceed the thresh hold limits/quantity prescribed/laid down under the Manufacture, Storage and Import of Hazardous Chemicals Rules, 1989 for which an Environment Clearance is required at any time.
- 17. You shall not open any container at the site without any statuary permission & only limited for the particular case to case permission granted to you by taking all precautionary measures to ensure that no spillage /over flow etc. caused, giving rise to any violation of the conditions of the Rules.
- 18. You shall take all precautionary measures & safety measures as per the permission granted by the Directorate Industrial Safety & Health or any other statuary Authority.

19. The Capital investment of the industry is Rs. 57.93Crs.

(Rajeev Kumar Mital, IAS) Member Secretary

To,

M/s. APM Terminals India Pvt. Ltd.

5/18 Sector 6, Dronagiri Warehousing Complex,

Navi Mumbai-400707.

Copy to

- 1) Regional Officer, MPCB, Navi Mumbai/Sub-Regional Officer-, MPCB, Navi Mumbai-III- They are directed to check compliance as per consent conditions.
- 3) Chief Accounts Officer, MPCB, Mumbai

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drown Ox
1	75100	415645	25 Jun 2011	HSBC Bank
2	1,25000/-	DR no-6986059		HODE BAIK