


MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 nd - 4 th Floor
Fax: 24024068 / 24023515		Opp. Cine Planet Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: pci2@mpcb.gov.in		Mumbai-400 022.

Red/L.S.I

Date: 17/07/2013

Consent No: BO/AST/RO-KN/EIC No KN-6481-13/E/Amnd/CC- 5998

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Filtra Catalysts & Chemicals Ltd.
N-59, MIDC Addl. Ambernath,
Tal. Ambernath, Dist. Thane

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:


1. The Consent to Establish is granted for a period up to Commissioning of the unit or Five years whichever is earlier.
2. The Consent is valid for the manufacture of -

Sl. No.	Product Name	Maximum Quantity	UOM
1	Metal Coating Chemicals	150	Mt/m.
2	Fertilizer Additives	100	Mt/m.
3	Fuel Oil Additives	100	Mt/m.
4	Cleaning Chemicals,	20	Mt/m.
5	Plastic Additives	05	Mt/m.
6	Foaming & Defoaming Agents	10	Mt/m.
7	Assembly of Candle Filters	500	Nos./m.
8	Assembly of Engineering Items / Systems	10	Nos./m.
9	Oil & Gas Additives	170	Mt/m.
10	Catalysts Pilot Plant Facility	2	Mt/m.
11	In-House R & D Unit	--	--
12	Copper Chrome Catalyst	03	Mt/m.
13	Alumina Catalyst	03	Mt/m.
14	Miscellaneous Catalyst	05	Mt/m.
15	Polyster Resins	100	Mt/m.
16	Polyols	170	Mt/m.

(By Mixing, Stirring and Filtration process only)

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 10 m³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 3 m³.

 1

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	6.5 to 8.5
2	Suspended Solids	Not to exceed	100 mg/l.
3	Oil & Grease	Not to exceed	10 mg/l.
4	BOD (3 days 27 °C)	Not to exceed	100 mg/l
5	COD	Not to exceed	250 mg/l.
6	Total Dissolved Solids	Not to exceed	2100 mg/l.
7	Sulphates	Not to exceed	1000 mg/l.
8	Chlorides	Not to exceed	600 mg/l.

(iv) **Trade Effluent Disposal:** The treated trade effluent shall be recycled/reused to the maximum extent and excess if any shall be discharged to CETP. In no case, trade effluent shall find its way outside factory premises.

(iv) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

– NA –

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i)	Domestic purpose	...	5.00 CMD
(ii)	Water gets Polluted & Pollutants are Biodegradable	...	15.00 CMD
(iii)	Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iv)	Industrial Cooling, spraying in mine pits or boiler feed	...	21.00 CMD
(v)	Agriculture/Gardening	...	0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment:

1. Scrubber of adequate capacity shall be provided to limit the process emissions.

Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

Standards for Stack Emissions:

- (i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Furnace Oil	100.00	Lit/hr.
2	LPG	100.00	Lit/d.

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler	30.00
2	D.G. (300 KVA)	3.00 *

(* above the height of building where the DG set is installed)

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) **Other Conditions:**
- 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.


Sr. No.	Item No. of HW as per Schedule-I	Type of Waste	Quantity	Disposal
1.	5.1	Waste oil	1200 Kg/A.	Sale to Authorised reprocessor.
2.	33.3	Discarded containers/barrels/line	100 Nos/A.	CHWTSDF
3.	34.2	Spent Ion Exchange Resins containing toxic metals	50 Lit/A.	CHWTSDF
4.	34.3	Chemical sludge from waste water treatment	4.2 Mt/A.	CHWTSDF
5.	35.1	Filters & Filter material	100 Kg/A.	CHWTSDF
6.	35.3	Spent carbon from purification process	1.0 Mt/A.	CHWTSDF

(ii) Treatment: - NIL

1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of hazardous waste.
2. The industry should comply with the Hazardous Waste (M,H & TB) Rules, 2008.
 - a. Industry shall obtain registration from CPCB as a re-refiner of Used oil having environmentally sound technology as per the provisions of Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008 before commencement of production.
 - b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
 - c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Wastes

7. Whenever due to any accident or release of gases or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emissions and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organizations as require under the law.
8. **Industry shall comply with following additional conditions:**
 - i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
 - ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
 - iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
 - iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
 - v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
 - vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
 - vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
 - viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
 - ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
 - x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
 - Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
 - xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

09. The consent should not be construed as any exemption from obtaining necessary NOC from other Govt. agencies as may deemed fit necessary.
10. The industry shall also comply with the Industry specific standards notified under Environment Protection Act.
11. This consent is issued with the overriding effect of the earlier consent granted vide no. BO/JD-PAMS/RO-KN/EIC No. KN-5923-12/E/Cc-66 dated 27/04/2012.
12. Industry shall obtain Consent to Operate before starting actual production.
13. This consent is issued pursuant to the decision of 6th CC meeting of 2013 (Part-I) held on 28.06.2013 of the Board.
13. The Capital investment of the industry is Rs. 28.00 Crore.


 (V. M. Motghare)
 Member Secretary

To,
 M/s. Filtra Catalysts & Chemicals Ltd.
 N-59, MIDC Addl. Ambernath,
 Tal. Ambernath, Dist. Thane

Copy to: 1) Regional Officer, MPCB, Kalyan & 2) Sub-Regional Officer, MPCB, Kalyan-II- They are requested to ensure the compliance of consent conditions.
 3) Chief Accounts Officer, MPCB, Mumbai 4] Cess Branch, MPCB. 5] Master file.

Received Consent fee of -

Sl. No.	Amount (Rs.)	DD. No.	Date	Drawn On
1	25000/-	970766	02/05/2013	Kotak Mahindra Bank Ltd.