

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 24020781 / 24010437

Fax : 24024068 / 24044532

Email : mpcb@vsnl.net

Visit At : <http://mpcb.gov.in>



Kalpataru Point, 2nd, 3rd & 4th Floor,
Opp. Cineplanet, Near Sion Circle,
Sion (E), Mumbai-400022.

EIC No: PN-12358-11

Infrastructure Project/Orange/LSI

Consent No. MPCBHQ/ROHQ/Pune/CO/CC/CC-7067 Date: 23/08/2013

Consent to Operate Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

.....
CONSENT is hereby granted to,

M/s.Baramati Hi-Tex Park Ltd.,
E- 1/2, MIDC Baramati Ind. Area,
Tal- Baramati, Dist- Pune.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31/03/2014.

2. The Consent is valid for the Textile Park project named as M/s.Baramati Hi-Tex Park Ltd., E- 1/2, MIDC Baramati Ind. Area, Tal-Baramati, Dist- Pune for the textile- Weaving, garmenting, packaging, knitting activities only without dyeing / bleaching / processing / sizing activities on total plot area of 2,40,000 Sq.mtrs, & total construction BUA of 30,011.99 Sq. mtrs which is constructed before 1.12.2009 including utilities of Textile Park.

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of sewage effluent from the factory shall not exceed 880.0 M3.
- (ii) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	pH	Not to exceed	6.5 to 9.0
2	Suspended Solids	Not to exceed	100 mg/l.
3	BOD 3 Days 27 degree C	Not to exceed	100 mg/l.
4	Fecal Coliform	Not to exceed	500/100/1 mg/l.
5	Residual Chlorine	Not to exceed	01 mg/l.
6	Detergent	Not to exceed	01 mg/l.
7	Floating matters	Not to exceed	10 mg/l
8	COD	Not to exceed	250mg/l

- (iii) **Sewage Effluent Disposal:** The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting & cooling of Air conditioners and remaining shall be discharged to Municipal sewer. In no case, effluent shall find its way to any water body directly/indirectly at any time.

Project proponent shall operate STP for five years from the date of obtaining Occupation Certificate.

(iv) **Non-Hazardous Solid Wastes:**

Sr.No	Type of Segregated solid waste	Quantity (Kg/Day)	Treatment	Disposal
1.	Wet Garbage	--	Composting	Use as Manure
2.	STP Sludge	---		
2.	Dry Garbage	---	..	Send to authorized Party

4. Other Conditions: -

- All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable;
- Near the activities that are related to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of local body.
- The Applicant shall draw plans for the segregation of solid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e vermi-composting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000.
- Applicant shall be responsible to take adequate precautionary measures as detailed in this consent.
- For disinfections of waste water ultra violet radiation shall be used in place of chlorination
- The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under,**

The daily water consumption for the following categories is as under:

(i) Domestic	...	1500.00 CMD
(ii) Water gets Polluted & Pollutants are Biodegradable	...	0.00 CMD
(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iii) Industrial Cooling, spraying	...	0.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

6. CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

- (i) The Applicant may install of diesel generating sets (DG Sets), and shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. Standards for Emissions of Air Pollutants:

- (i) SPM/TPM Not to exceed 150 mg/Nm³
(ii) SO₂ (DG Set) Not to exceed --- Kg/day

- (ii) **The applicant shall observe the following fuel pattern:-**

Sr. No.	Type Of Fuel	Quantity
1.	--	

- (iii) **The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Chimney Attached To	Height in Mtrs.
1.	--	--

- (iv) **Conditions for D.G. Set**

- Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- D.G. Set shall be operated only in case of power failure.
- The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

- (v) **Other Condition**

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by

numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.


b) Water spraying shall be done on ground to avoid fugitive emissions.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
--		--	--	--

8. The applicant shall adopt environment friendly technology in development of the project.
9. This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.
10. Applicant shall not take any effective steps for the construction started after 1.12.2009 i.e. more than the prescribed in consent order, prior to obtaining Environmental Clearance. Applicant shall submit a separate Bank guarantee of Rs. 2.0 Lakhs against compliance of the same.
11. **Every individual industry proposed to be located in Textile Park area shall obtain Consent to Establish and Consent to operate separately from Maharashtra Pollution Control Board.**
12. The applicant shall submit **Bank Guarantee of Rs. 5.0 Lakhs** towards the compliance of consent conditions at **Regional Office, MPCB, Pune within 15-days.**
13. This is issued pursuant to the decision of **Consent Committee** of the Board in its meeting held on **2nd August, 2013.**
14. The **Capital investment** of the total project is **Rs. 111.12 Crores.**


(V.M.Motghare) 28/8/13
Member Secretary

To,
M/s.Baramati Hi-Tex Park Ltd.,
E- 1/2, MIDC Baramati Ind. Area
Tal- Baramati, Dist- Pune.

Copy to-

1. Regional Officer, MPCB, Pune - He is directed to obtain necessary Bank Guarantee from the applicant and ensure compliance of consent conditions
2. Sub Regional officer-I, MPCB,Pune.
3. Chief Accounts Officer, Mumbai, MPCB,