MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701

Fax: 24024068 / 24023516

Website: http://mpcb.gov.in

E-mail: mpcb@vsnl.net



Kalpataru Point, 2nd - 4th Fl.

Opp. Cine Planet Cinema,

Date: 23/08/2013

Page 1 of 4

Near Sion Circle, Sion (E)

Mumbai-400 022.

Orange/L.S.I

a

Consent No: BO/JD(APC)/EIC No. PN-17165-13/0-CC-7084

Consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. RPK India Pvt. Ltd., 🕻

Plot No. 1A, Gat No. 1122 (P),1129 (P),1140,1295,1296,

Shirwal, Tal Khandala, Dist. Satara 412 801

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1. The Consent to operate is granted for a period up to 28/02/2014
- 2. The Consent is valid for the manufacture of -

	3,00,000 Nos/Year
1Tension Springs2Compression Springs	2,00,00,000 Nos/Yea
3 Toression Springs	1,20,00,000 Nos/yea

(Without any surface & chemical treatment)

3 CONDITIONS UNDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall be NIL

(ii) The daily quantity of sewage effluent from the factory shall not exceed 8.0 M3.

- (iii) Trade Effluent : N.A.
- (iv) Trade Effluent Disposal: N.A.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l.

SRO Sataral/1/R/L/48433000.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

	land for gardening /]						
(vii) No	n-Hazardous Solid	Wastes:					
Sr. No Type Of Waste wei Quantity W UOM W. Treatment & Disposal							
1.	Metal Dust	425	Kg/Year	By Sale			
1. 2.	Metal Scrap	2547	Kg/Year				
4.	Metal Sciap	2011	116, 1041				
() O	han Conditions: In	dustry shoul	ld monitor effli	uent quality regularly.			
	mer Conditions: In	mala with t	the provision	s of the Water (Prevention &			
4. Ine	applicant shall co.	Core Art	$\frac{1077}{1077}$ (to be	roformed as Coss Act) and			
				e referred as Cess Act) and			
	endment Rules, 200						
	-	umption for	the following o	ategories is as under			
	(i) Domestic		•••	10.0 CMD			
((ii) Industrial Proces	sing	•••	0.0 CMD			
	(iii) Industrial Coolir	ıg	•••	CNID			
((iv) Agriculture / Gar	dening	•••	1.0 CMD			
ſ	The applicant shall	regularly s	submit to the	e Board the returns of water			
(consumption in the	prescribed	form and pag	y the Cess as specified under			
	Section 3 of the said			X			
		ID ACT.					
	IDITIONS UNDER A		lutanta. FC				
Sta	ndards for Emission			d 150 mg/Nm ³			
	(i) SPM/T	PW	Not to excee				
	(ii) SO2		Notiforexcee				
(i)	The applicant s	hall observ	e the followi	ng fuel pattern:-			
(4)	THE MPPROUVE			G			
N.	Sr. No. * Type Of F			TOM TOM TOM			
	STINO & INDEALID	HEL SECONDER OF					
	1 HSD	~ 01	.50	Lit/Hr			
(ii)	The applicant	shall ere	ct the chin	mev(s) of the following			
	specifications:#						
S.No. 44	specifications: SEGAMECIA			Remarks			
	Stack Attached			above the roof			
1	DG set (500 KVA)		Height + + + + + + + + + + + + + + + + + + +	above the roof			
1	Stack Attached		- Height 👟 🛶				
1	DG set (500 KVA) DG set (250 KVA)		Height 3.00 3.00	above the roof above the roof			
1 2 (i) '	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA)	install a co	Height 200 3.00 3.00 omprehensive	above the roof above the roof control system consisting of			
1 2 ï) '	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a	install a co s is warrant	Height 3.00 3.00 omprehensive ed with refere	above the roof above the roof control system consisting of nce to generation of emission			
1 2 i) ' ε	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a undoperate and main	install a co s is warrant ntain the sar	Height 3.00 3.00 omprehensive ed with refere ne continuous	above the roof above the roof control system consisting of			
1 2 i) ' 2 2 2 2 2 2 2 2 2 2	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a indioperate and main follutants to the follo	install a co s is warrant ntain the sar wing standa	Height 3.00 3.00 omprehensive ed with refere ne continuous	above the roof above the roof control system consisting of nce to generation of emission			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a und operate and main follutants to the follo Control Equipment	install a co s is warrant ntain the sar wing standa	3.00 3.00 mprehensive ed with reference ne continuous ards:	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a und operate and main follutants to the follo Control Equipment	install a co s is warrant ntain the sar wing standa	3.00 3.00 mprehensive ed with reference ne continuous ards:	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a ind operate and main follutants to the follo Control Equipment Fume extraction sys	install a co s is warrant ntain the san wing standa : - stem follow	Height 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust co	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of oblector system of sufficient			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall control equipments a indoperate and main follutants to the follo Control Equipment Fume extraction sys capacity shall be pro	install a co s is warrant ntain the san wing standa : - stem follow wided to fur	Height 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust co	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a ind operate and main follutants to the follo Control Equipment Fume extraction sys capacity shall be pro properly & continuo	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly	Height 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust contact and all so	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient cources of SPM/TPM operated			
	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a ind operate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be proproperly & continuo There shall not be ar	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary	Height 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust contact and all so	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient ources of SPM/TPM operated			
1 (i) (i) (i) (i) (i) (i) (i) (i) (i) (i)	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a indioperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be proproperly & continuo There shall not be ar iditions for D.G. Set	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary :	Height 3.00 3.00 3.00 mprehensive ed with reference ne continuous ards: ed by dust contact and all so nace and all so	above the roof above the roof control system consisting of nce to generation of emission ly so as to achieve the level of ollector system of sufficient ources of SPM/TPM operated sion			
1 (i) (i) (i) (i) (i) (i) (i) (i) (i) (i)	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a indioperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be proproperly & continuo There shall not be ar iditions for D.G. Set	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary :	Height 3.00 3.00 3.00 mprehensive ed with reference ne continuous ards: ed by dust contact and all so nace and all so	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient ources of SPM/TPM operated			
1 (i) (i) (i) (i) (i) (i) (i) (i) (i) (i)	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a indioperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be proproperly & continuo There shall not be ar iditions for D.G. Set	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co	Height 3.00 3.00 3.00 mprehensive ed with refere ne continuous ards: ed by dust co nace and all so fugitive emiss ontrolled by pr	above the roof above the roof control system consisting of nce to generation of emission ly so as to achieve the level of ollector system of sufficient ources of SPM/TPM operated sion			
1 2 (i) 6. Con a. Noi. or b	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a undoperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro properly & continuo There shall not be ar ditions for D.G. Set se from the D.G. Set y treating the room a	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically.	Height 3.00 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust contact and all so refugitive emission ontrolled by pre-	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of bullector system of sufficient ources of SPM/TPM operated sion oviding an acoustic enclosure			
1 2 2 0 3 0 6. Con 0 a. Noi 0 b. Ind 0	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a ind operate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be an ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic es	Height 3.00 3.00 3.00 omprehensive ed with reference ne continuous ards: ed by dust contact and all so fugitive emistry ontrolled by pre- nclosure for contact of the solution of the solution of the solution of the solution of the solution of the solution of the solution of the solution of the solution of the solution	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient purces of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic			
1 2 (i) a a a a b Index encil	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall ontrol equipments a indioperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be ar ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide losure/ acoustic treat	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic ent tment of the	Height 3.00 3.00 3.00 mprehensive ed with reference in a continuous and since and all so fugitive emission ontrolled by pre- inclosure for co room should	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient cources of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic be designed for minimum 25			
1 2 (i) a a a a a b Indiana b Indiana dB	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall control equipments a undoperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be an ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide losure/ acoustic treat (A) insertion loss or	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic ent tment of the for meeting	Height 3.00 3.00 3.00 mprehensive ed with referent ne continuouslier ards: ed by dust contact and all so receard all so recear	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of oblector system of sufficient ources of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic be designed for minimum 25 noise standards, whichever is			
1 2 (i) a a a a a a b Indiana b Indiana dB	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall control equipments a undoperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be an ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide losure/ acoustic treat (A) insertion loss or	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic ent tment of the for meeting	Height 3.00 3.00 3.00 mprehensive ed with referent ne continuouslier ards: ed by dust contact and all so receard all so recear	above the roof above the roof control system consisting of nce to generation of emission by so as to achieve the level of collector system of sufficient cources of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic be designed for minimum 25			
1 2 (i) a a a a a a b Indiana b Indiana dB	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall control equipments a undoperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be an ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide losure/ acoustic treat (A) insertion loss or	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic ent tment of the for meeting	Height 3.00 3.00 3.00 mprehensive ed with referent ne continuouslier ards: ed by dust contact and all so receard all so recear	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of oblector system of sufficient ources of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic be designed for minimum 25 noise standards, whichever is			
1 2 (i) a a a a a b Indiana or b b. Indiana dB	DG set (500 KVA) DG set (250 KVA) DG set (250 KVA) The applicant shall control equipments a undoperate and main follutants to the follo Control Equipment Fume extraction syst capacity shall be pro- properly & continuo There shall not be an ditions for D.G. Set se from the D.G. Set y treating the room a ustry should provide losure/ acoustic treat (A) insertion loss or	install a co s is warrant ntain the san wing standa : - stem follow wided to fur usly ny secondary : should be co acoustically. e acoustic ent tment of the for meeting	Height 3.00 3.00 3.00 mprehensive ed with referent ne continuouslier ards: ed by dust contact and all so receard all so recear	above the roof above the roof control system consisting of nce to generation of emission y so as to achieve the level of oblector system of sufficient ources of SPM/TPM operated sion oviding an acoustic enclosure ontrol of noise. The acoustic be designed for minimum 25 noise standards, whichever is			

SRO Sataral/I/R/L/48433000.

~

Page 2 of 4

also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.

- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions, and ambient air quality Regularly.
- 7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RUBES 2008:
 - (i) The Industry shall not generate any hazardous wastes.

8. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area./inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

SRO Sataral/I/R/L/48433000.

Page 3 of 4

viii.The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992. ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant. x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained. xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System. xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory. 9. This is issued with the approval of Consent Committee meeting of the Board in its meeting held on 17/08/2013 10. You shall submit Bank Guarantee of Rs. 5/ Lakhs in favor of Regional Officer Pune within 15 days towards Operation & maintenance of pollution control system. The Bank Guarantee shall be valid up to 30/05/2014. 11. Industry applied renewal of consent with expansion with C.I. Rs. 34.90 Crs (existing 17.12 Crs) & Consent Committee has decided to grant plain renewal of consent only & issue Show cause notice for refusal of expansion as not satisfactory RRZ 12. The Capital investment of the industry is Rs. 17.12 Crs. (V.M. Motghare) 2 2 Member Secretar To, M/s. RPK Indi at No. 1122 (P),1129 (P),1140,1295,1296, Plot No Tàl Khandala, Dist. Satara 412 801 Shirwal. Copy to: RO- MPCB Pune /SRO-MPCB Satara- They are directed to ensure the compliance of consent condition & obtain the BG of Rs. 5/- Lakh from the industry & submit the report within 1 month period CAO/Cess Branch/Master File **Received Consent fee of -**

S.No HI HI Bank Name : A set I will DD. No.								
1	HDFC Bank	000204	20/02/2013	75000				
2	HDFC Bank	000556	16/05/2013	50000				

SRO SataraJ/U/R/L/48433000.

Page 4 of 4