


MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 nd - 4 th Floor
Fax: 24024068 / 24023515		Opp. Cine Planet Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: pci2@mpcb.gov.in		Mumbai-400 022.

Red/L.S.I

Date: /08/2013

Consent No: BO/AST/RO NaviMumbai/EIC No NM-4487-13/R/CC- **7193**

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].


CONSENT is hereby granted to

**M/s. Indian Oil Corporation Ltd.
T-20, MIDC Talaja
Dist-Raigad, Maharashtra**

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- The Consent to Operate is granted for a period up to: 31/08/2018.**
- The Consent is valid for the manufacture of -**

Sl. No.	Product Name	Maximum Quantity	UOM
1	Servo Brake Fluid Super HD-210 L BRL	50	KL/M
2	Servo System FG 68-210 L BRL	4	KL/M
3	Servo Conval 46-210 BRL	1.8	KL/M
4	Servo Line 100-210 L BRL	2.2	KL/M
5	Servo Line 150-210 L BRL	2.2	KL/M
6	Servofilm 100-210 L BRL	12.58	KL/M
7	Servofilm 460-210 L BRL	10.8	KL/M
8	Servospin 2-210 L BRL	3.6	KL/M
9	Servospin 12-210 L BRL	14	KL/M
10	Servospin 22-210 L BRL	20	KL/M
11	Servospin EE 10-210 L BRL	2.6	KL/M
12	Servospin 5-210 L BRL	10.5	KL/M
13	Servo Knit Clean 32-210 L BRL	4.1	KL/M
14	Servo Syngear 220-210 L BRL	10	KL/M
15	Servo Syngear 320-210 L BRL	1.6	KL/M
16	Servosyngear 460-210 BRL	2	KL/M
17	Servofriz NH 68-210 L BRL	3.2	KL/M
18	Servofriz ECO 68-210 L BRL	2	KL/M
19	Servofriz ECO 150-210 L BRL	2	KL/M



20	Servoquench 11-210 L BRL	18	KL/M
21	Servoquench 707-210 L BRL	4.4	KL/M
22	Servoquench C 11-210 L BRL	7.9	KL/M
23	Servocut 945-210 L BRL	68	KL/M
24	Servocut BR-210 L BRL	1.68	KL/M
25	Servocut GR-210 L BRL	30	KL/M
26	Servocut 151-210 L BRL	9.51	KL/M
27	Servocut 201-210 L BRL	4.62	KL/M
28	Servocut 253-210 L BRL	5.96	KL/M
29	Servocut 353-210 L BRL	2	KL/M
30	Servohone 7-210 L BRL	60	KL/M
31	Servogrind 12-210 L BRL	2	KL/M
32	Servomet 033-210 L BRL	12.6	KL/M
33	Servo RP 125-210 L BRL	16.53	KL/M
34	Servo RP 200-210 L BRL	8.75	KL/M
35	Servo RP 103 Wd-210 L BRL	9.89	KL/M
36	Servo RP 104 WD-210 L BRL	80	KL/M
37	Servoteleshocab-210 L BRL	2	KL/M
38	Servo Shocab ES-210 L BRL	12	KL/M
39	Servocress 68-210 L BRL	1.8	KL/M
40	Servocress 150-210 L BRL	1.2	KL/M
41	Servosynco E-46-210 L BRL	1.2	KL/M
42	Servosynco E-68-210 L BRL	1.2	KL/M
43	Servosynco E 100-210 L BRL	0.63	KL/M
44	Servosynco E-150-210 L BRL	1.2	KL/M
45	Servosyngear 460 RR-210 L BRL	9.07	KL/M
46	Servo Therm Medium-210 L BRL	16.72	KL/M
47	Servo Therm Special-210 L BRL	6.6	KL/M
48	Servotherm S Medium-210 L BRL	6.3	KL/M
49	Servotorque 10-210 L BRL	28.78	KL/M
50	Servo Transtrac HVI-210 L BRL	1.2	KL/M
51	Servo Steerol 22 (j) L-210 L BRL	40	KL/M
52	Servosteel EP 100 Plus-210 L BRL	2	KL/M
53	Servo DS 2-168 KG DRM	1.8	KL/M
54	Servoelectra-210 L BRL	26	KL/M
55	Servo DMFA-210 L BRL	1	KL/M
56	Hyundai Servo Coolant-210 L BRL	20	KL/M
57	Servo Kool Plus-210 L BRL	60.76	KL/M
58	Servofyress HFDU 46 ES-210 L BRL	2	KL/M
59	Servo Cool Ready-210 L BRL	1.5	KL/M
60	Servo Kool NFSC-210 L BRL	1.3	KL/M
61	Servo Kool TM-210 L BRL	100	KL/M
62	Servo RP 102 WD-210 L BRL	2.8	KL/M
63	Servo Cubrol 210 Ltr BRL	2	KL/M
64	Univys N-46-210 L BRL	2	KL/M
65	Servo Cut-375	2	KL/M
66	Synlock 10 Bulk	2	KL/M
67	Synlock 10 Bulk	1	KL/M
68	Syngear AMP 320	15	KL/M
69	Lubrex 22	10	KL/M
70	Way-32	2	KL/M

71	Way-68	2	KL/M
72	Way-220	2	KL/M
73	Way 100	2	KL/M
74	Way H 32	2	KL/M
75	Way H 57	2	KL/M
76	Way H 68	2	KL/M
77	Mesh Plus 100	2	KL/M
78	Mesh Plus 150	2	KL/M
79	Mesh Plus 220	20.2	KL/M
80	Mesh Plus 320	10	KL/M
81	Mesh Plus 460	26	KL/M
82	Spark 2	2	KL/M
83	Lubrex 150	12	KL/M
84	RP 180 ES (WE requirements only)	12	KL/M
85	Calib 2	2	KL/M
86	Calib 5	2	KL/M
87	Servosynth 5	8.5	KL/M
88	Servo Quench 107	12	KL/M
89	Servo cut 335	6.09	KL/M
90	Servospark 2	5.37	KL/M
91	Servo Fyress WG 46	1.35	KL/M
92	Servo Kool ST	2.1	KL/M
93	Servo Anti Corr BF	10	KL/M
94	Servo Way 100	4	KL/M
95	Servo Syngear-320 Plus	6.99	KL/M
96	Servo RP 180 ES	7.3	KL/M
97	Servocut GR-Bulk	216	KL/M
98	Servo Kool TM-Bulk	120	KL/M
99	Servofilm-12-Bulk	54	KL/M
100	IOC Process.Oil-Bulk	18	KL/M
	Servo Brake Fluid Super HD-20X1/2 L		KL/M
101	HDPE	8	
102	Kool Ready	1.46	KL/M
103	Servo Transtrac HVI-20X1/2 L HDPE	8	KL/M
104	Hyundai Coolant (10X1)	12	KL/M
105	Kool Plus (10X1)	16.5	KL/M
106	Servo Kool Plus-20X1/2L-HDPE	5.4	KL/M

The industry should maintain the total production quantity of 1500 KL/Month.

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed **0.30 m³**.
(ii) The daily quantity of sewage effluent from the factory shall not exceed **10.00 m³**.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
2	Suspended Solids	Not to exceed	100.00 mg/l.
3	BOD 3 Days 27 degree C	Not to exceed	100.00 mg/l.
4	COD	Not to exceed	250.00 mg/l
5	Oil & Grease	Not to exceed	10.00 mg/l
6	Sulphates	Not to exceed	1000.0 mg/l
7	TDS	Not to exceed	2100.0 mg/l
8	Zinc	Not to exceed	50 mg/l

(iv) **Trade Effluent Disposal:** The treated effluent shall be used for gardening purpose. There shall be no discharge outside the industry premises.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l
(2)	BOD 3 days 27o C.	Not to exceed	100	mg/l

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:** N.A

(viii) **Other Conditions:** Industry should monitor effluent quality regularly from MoEF approved laboratory.

4. **The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

(i)	Domestic purpose	...	12.00 CMD
(ii)	Water gets Polluted & Pollutants are Biodegradable	...	2.00 CMD
(iii)	Water gets Polluted, Pollutants are not Biodegradable & Toxic	...	0.00 CMD
(iv)	Industrial Cooling, spraying in mine pits or boiler feed	...	29.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. **CONDITIONS UNDER AIR ACT:**

(i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a. **Control Equipment:** Industry shall provide necessary APC devices to control the emissions.

b. **Standards for Stack Emissions:**

a.	SPM/TPM	Not to exceed	150 mg/Nm ³
b.	SO ₂	Not to exceed	126 kg/Day

- (i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	LDO	3.50	MT/day

- (ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler	38.00
2	D.G. Set of 380 KVA	8.00

- (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- (vi) Other Conditions:
- 1) The industry should not cause any nuisance in surrounding area.
 - 2) The industry should monitor stack emissions and ambient air quality regularly.

Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use

g. D.G. Set shall be operated only in case of power failure The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set:

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

(i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
-N.A-				

(ii) Treatment: - NIL

(iii) Whenever due to any accident or release of gases or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emissions and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organizations as require under the law.

7. Industry shall comply with following additional conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by the applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
8. The consent should not be construed as any exemption from obtaining necessary NOC from other Govt. agencies as may deemed fit necessary.
9. The industry shall also comply with the Industry-specific standards notified under Environment Protection Act.
10. This consent is issued pursuant to the decision of the 7st Consent Committee of 2013 held on 10.07.2013.
11. The Capital investment of the industry is Rs. 42.16 crores.

(V. M. Motghare)
Member Secretary

To,
Indian Oil Corporation Ltd
T-20, MIDC Taloja
Dist-Raigad,
Maharashtra

Copy to:

- 1) Regional Officer, MPCB, Navi Mumbai} They are directed to ensure the compliance of consent conditions.
- 2) Sub-Regional, Officer, MPCB, Taloja - 1} They are directed to ensure the compliance the consent conditions.
- 3) Chief Accounts Officer, MPCB, ,Mumbai

Received Consent fee of -

Sr No.	Amount(Rs)	DD No.	Date	Drawn On
1	375100	402036	12 Mar 2013	SBI Bank
2	46250	985767	22 Aug 2013	SBI Bank