MAHARASHTRA POLLUTION CONTROL BOARD

Phone :

Fax

Email

Visit At :

http://mpcb.gov.in



Consent No.BO/JD (WPC)/RO TN-4595-13/ O/CC- 7423

Date: /07/2013

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008 [To be referred as Water Act, Air Act and HW (M,H & TM) Rules respectivelyl.

CONSENT is hereby granted to

M/s D' Decor Home Fabrics Pvt. Ltd. Plot No. F-6/1, MIDC Tarapur, Tal. Palghar, Dist. Thane -401506

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M,H &TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to:31.01.2015

2. The Consent is valid for the manufacture of -

2. The Consent is valid for the manufacture of	100
Product Name And Carlo Maximum	
S. No. 11 July 1982 1982 1982 Quantity	
Dyeing & Printing of 25 Lac Mtrs/M	ļ
Grey Fabrics	

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed
- (ii) The daily quantity of sewage effluent from the factory shall not exceed $9.50 M^3$.
- (iii) Trade Effluent:

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

\$ 6.A		Between	5.5 to 9.0	
1		Not to exceed	100	mg/l.
	Suspended Solids	Not to exceed	100	mg/l.
3	BOD 3 days 27 Deg. C.	Not to exceed	250	mg/l.
4	COD	Not to exceed	10	mg/l.
5	Oil & Grease	Not to exceed	2	mg/l.
6	Detergent	Not to exceed	50	mg/l.
7	TAN	Not to exceed	-ffluent shall be	recycled & rei

Trade Effluent Disposal: The treated trade effluent shall be recycled & reused 50% of treated effluent (525 CMD) with in one year (i.e. up to 31.08.2014) and remaining shall be discharged in to drainage system provided by MIDC

connected to CETP. In no case, at any time effluent shall finds its way to any water body directly or indirectly.

(v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

Suspended Solids

Not to exceed

mg/l. 100

BOD 3 days 27o C. (2)

Not to exceed

100 mg/l.

(vi) Sewage Effluent Disposal: The treated effluent shall be recycled to the maximum extend and remaining shall be discharged into sewerage system provided by MIDC.

(vii) Non-Hazardous Solid Wastes:

ST.	Type Of Waste : 12 and	Quan ty	UOM`	Disposal
1	Coal Ash	500.00	Kg/Day	Sale to Brick manufacturers
2	Rags/ Felts Small waste fabrics & waste cotton yarn	30.00	Kg/M	Sale

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

30.00 CMD

(ii) Water gets Polluted &_

Pollutants are Biodegradable ...

800.00 CMD

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...

0.00 CMD

(iv) Industrial Cooling, spraying

in mine pits or boiler feed

170.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

Industry shall provide dust collector of sufficient capacity to control the emissions.

b) Standards for Stack Emissions:

1) SPM

Not to exceed

mg/Nm3150

2) SO2

Not to exceed

kg/day 770

(ii) The applicant shall observe the following fuel pattern:-

TOUR TURBUSE IN E	Avise Of Briefs	SeQuantity # ***	on UOM-
	Furnace Oil	3.00	KL/day

		1 ~ .	0.5	T/Down
1	1 2	l Coal	25	T/Day
1				·

(iii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No. Height in Mtrs. Height in Mtrs.				
1	Boiler (working)	34.00		
2	Boiler(Stand By)	34.00		
3	D.G. Set (725 KVA)	10.00		

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then
 - The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG

manufacturer which would help to prevent noise levels of DG set from deteriorating with use

g. D.G. Set shall be operated only in case of power failure

h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below. (i)

Sr. No. Type Of Waste	Quantity	UOM	Disposal
1 34.3 Chemical sludge	2.0	MT/M	CHWTSDF
from waste water treatme			

Treatment: - NIL (ii)

The authorization is hereby granted to operate a facstorage, transport & disposal of hazardous waste.

Waste (M,H & TM) The industry should comply with the Hazardous 2. Rules, 2008.

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office. W.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management , Handling & transboundry) Rules, 2008 and shown & submitted to the Board as & when asked for.

Industry shall comply with following additional conditions:

The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.

iii. Solid waste - The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms

& conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

vii. The applicant shall make an application for renewal of the consent at least 60

days before the date of the expiry of the consent.

viii.The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

ix. As inspection book shall be opened and made available to the Board's officers

during their visit to the applicant.

- The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of theterminal manholes. No effluent shall find its way other than in designed and provided collection System.

Neither storm water nor discharge from other premises shall be allowed to xii.

mix with the effluents from the factory.

- 9. The Board reserves the right to amend or add any condition in this consent and same shall be binding on the applicant.
- 10. This consent shall not be construed as any exemption from obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
- 11. If any Chamber of MIDC is found chocked or pipe line carrying effluent from industry to CETP is breaked/leaked, industry shall stop voluntarily discharge of treated effluent into drainage pipeline provided by MIDC. In such cases the treated effluent shall be stored within premises or to be disposed to CETP by Tankers. Proper manifest system of the same to be maintained and submitted to Sub-Regional Officer/Regional Officer of Board.

12.(i) Industry shall submit Bank Guarantee of Rs. 5 lakh towards 0 & M of

pollution control system.

(ii) Industry shall recycle and reuse 50% of treated effluent (525 CMD) with in one year (i.e. up to 31.08.2014) and upgrade air pollution control system with in 4 months (i.e. up to 20.12.2013) and submit Bank Guarantee of Rs. 5 lakh for compliance of same.

13. The consent is issued pursuant to the Consent Committee meeting of Board held on 17.08..2013.

14. The Capital investment of the industry is Rs. 4820 Lacs.

(Rajeev Kumar Mital) Member Secretary

To, M/s D' Decor Home Fabrics Pvt. Ltd. Plot No. F-6/1, MIDC Tarapur, Tal. Palghar, Dist. Thane -401506

Copy to :- RO Thane/SRO Tarapur-I: They are directed to obtain Bank Guarantees from industry ensure compliance of consent conditions.

CAO/Cess wing/Master file.

Received Consent fee of -

64 NA 45	Amount (Rs.)	DD. No. Prof. P. Date	Drawn	$\mathbf{On}^{[r]}$	
1	275000	445313 25 April 2013	Union	Bank	of
^			India		

^{*} Balance fees of Rs 31,250/z/-- from the above submitted fees will be adjusted during next renewal of Consent.