# MAHARASHATRA POLLUTION CONTROL BOARD

Phone : 2402 0781/2401 0437

Fax : 220

220424068

Email

jdwater@mpcb.gov.in

Visit At :

http://mpcb.gov.in



Kalpataru Point 02<sup>nd</sup>,03<sup>rd</sup> & 04<sup>th</sup> floor Opp. Cineplanet Near Sion Circle, Sion (E),

Mumbai- 400 022

Date: 04/09/2013

Red/LSI

Consent No: BO/JD(WPC)/EIC No PN-18624 - 13/R/CC- 4485

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M, H & TM) Rules respectively].

CONSENT is hereby granted to

United Spirits Ltd., Gat No. 344, At- Pimpli, Tal- Baramati, Dist-Pune Pune-413102

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M, H & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.08.2015.

2. The Consent is valid for the manufacture of -

Sr. No. 1. s	Rioduci Name	Maximum (8)	COM TO THE
1	IMFL CONTRACTOR	30,00,000	Ltr/M
2	Spirit ( By using only Grape as	1,00,000	Ltr/M
	a raw material)		

### 3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 2.00M3. (Industry shall achieve ZERO discharge)
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 18.00M3.
- (iii) Trade Effluent:

Treatment: The applicant will provide comprehensive treatment consists of biomethanisation / reboiler is as primary followed by well designed aerobic composting. The arrangement shall be leaked proof and no effluent or leakages/seepages shall find its way into environment thereby causing pollution of surface/ground/generated water.

**Conditions for Aerobic Composting:** 

i. The spent wash should be stored in impervious tanks. The spent wash tanks should have proper lining with HDPE and should be kept in proper condition to prevent ground water pollution. As per the CPCB recommendation and undertaking given by the company, storage should not exceed 30 days capacity.

SRO Pune I/I/R/I /75152000

- Applicant shall ensure availability of adequate filler material such as press mud, bagasses, agricultural, biological waste as required for effective composting system.
- iii. Composted material shall meet the following specifications—

Moisture

... 30 to 35%

C/N Nitrogen

... Below 17 ... 1.5 to 2%

Phosphorous

... 1.5 to 2%

Potassium

... 3 to 4%

- iv. The composting site shall be prepared as per the guideline. Composting shall be such that it includes mechanical mixing and spraying of spent wash along with mechanical aeration to ensure thorough composting. Hand/ manual spraying of spent wash shall not be permitted.
- The compost leachete (1 gr. of compost mixed with 100 ml. of distilled water and filtered) Filterate shall conform to the following limit.

Between

7.5 to 8.0

BOD 3 days 27 Deg. C.

Not to exceed

- vi. A pucca leak proof guard pond of 30 days holding capacity as per (i) above shall cope up with the effluent discharge during short term process disturbances In case of prolonged disturbance in effluent treatment and disposal system, distillery shall be shut down and shall not be restarted without rectifying the system.
- vii. The composting site/pits shall be made leak proof by proper lining. A catch drain shall be provided around the composting site to collect the storage pound for application on compost depots. Arrangements for overturning of compost material in windrows and spraying of spent wash shall be made to ensure appropriate aeration and uniform distribution of spent wash.
- viii. In case of composting in open fields, the application of spent wash shall stop by end of April, so that compost is ready and the site is cleared of the composted manure before monsoon (i.e. 31st May). The manure shall be collected and stored on a raised platform with suitable rain cover so that the compost manure is not washed away by rain/runoff.
- Characteristic of soil, ground water and effect on crop yield should be monitored in the area where compost is used as manure and results thereof shall be compiled and reported in the Environment statement to be submitted every year.
- The test wells shall be provided around the compost site for ground water monitoring. The well water quality has to be maintained at 2006 level.
- Top pullover impervious sheets shall be provided for entire compost yard, press mudand compost storage so as to cover the same during untimely rains and idles period.
- The operation of distillery should be restricted to 270 days in a year and that it will not operate during rainy season.
- (iv) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)Suspended Solids Not to exceed

100 mg/l.

(2)BOD 3 days 27o C.

Not to exceed

100 mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) Non-Hazardous Solid Wastes:

Sr. Nö.	Type Of	Waste ↓ 😘	Quantity ==	UOM -	Treatment.	Dispos	
1	Grape	Skin	400,00	MT/Year		By	secured
	Compost					landfill	within
		· <u> </u>				own pre	mises

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose

25.00 CMD

(ii) Water gets Polluted &

Pollutants are Biodegradable ...

107.00 CMD

(iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic ...

 $0.00~\mathrm{CMD}$ 

(iv) Industrial Cooling, spraying in mine pits or boiler feed

10.00 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

### 5. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:
  - a) Control Equipment: Wet scrubber/ESP of sufficient capacity shall be provided to bagasse fired boiler.
  - b) Standards for Stack Emissions:

1) SPM

Not to exceed

150 mg/Nm3

2) SO2

Not to exceed

94.68 Kg/Hr

(ii) The applicant shall observe the following fuel pattern:-

Sr.:No.	Type Of Fuel Lie Ka	Quantity 4	UOM
1	Briquettes & Bagasse	1.83	MT/Hr
2	F.O.	125.00	Lit/Hr

(iii) The applicant shall erect the chimney(s) of the following specifications:-

	Sr. No. 198	Chimney Attached To	Height in Mrs.
et.	1-	Boiler	30.00
de de	12 ()	D.G Set (320 KVA)	*5.0
Sagara Sagara	<b>3</b>	D.G Set (500 KVA)	*5.0

(\* above the roof of the building in which it is installed)

- (iv) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

#### (vi) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.

#### 6. CONDITIONS **UNDER** HAZARDOUS WASTE (MANAGEMENT, HANDLING TRANSBOUNDRY MOVEMENT) RULES, 2008:

The Industry shall handle hazardous wastes as specified below.

## Sr. No. Fr Type Of Waste Quantity Will UOM Disposal ---- Industry shall not generate any type of Hazardous Waste---

Treatment: -(ii)

The authorization is hereby granted to operate a facility for collection, storage, 1. transport & disposal of hazardous waste.

The industry should comply with the Hazardous Waste (M, H &TM) Rules, 2008. 2.

Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office &

concerned Regional Office. Sub Regional Office.

#### Industry shall comply with following additional conditions: 7.

The applicant shall maintain good housekeeping and take adequate measures for control i. of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.

The applicant shall bring minimum 33% of the available open land under green ii.

coverage/ tree plantation.
Solid waste - The non-hazardous solid waste arising in the factory premises, sweepings, iii. etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.

The applicant shall provide for an alternate electric power source sufficient to operate all iv. pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.

The applicant shall not change or alter quantity, quality, the rate of discharge, ٧. temperature or the mode of the effluent / emissions or hazardous wastes or control

equipments provided for without previous written permission of the Board.

The applicant shall provide facility for collection of environmental samples and samples vi. of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

The applicant shall make an application for renewal of the consent at least 60 days vii.

before the date of the expiry of the consent.

The firm shall submit to this office, the 30th day of September every year, the viii. Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.

- As inspection book shall be opened and made available to the Board's officers during ix. their visit to the applicant.
- The applicant shall install a separate electric meter showing the consumption of energy x. for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Separate drainage system shall be provided for collection of trade and sewage Xi. effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- Neither storm water nor discharge from other premises shall be allowed to mix with the xii. effluents from the factory.
- The Board reserves the right to amend or add any condition in this consent and same 8. shall be binding on the applicant.
- This consent shall not be construed as any exemption from obtaining necessary No 9. Objection Certificate from other Government agencies as may deemed fit necessary.
- The industry shall submit bank Guarantee of Rs. 2.0 Lakhs towards continuous 10. compliance of ZERO discharge of spent wash in favor of the Regional Officer, Pune within 15 days period. The Bank Guarantee shall be valid up to 31.12.2015.
- The consent is issued as per the decision of Consent Committee meeting held on 11. 22.08.2013.
- The Capital investment of the industry is Rs 12. 28.97 Crs.

For and on Behalf of the

Maharashtre, Polluftion Control Board,

(Rajeev Kumar Mital, IAS Member Secretary

To.

M/s. United Spirits Ltd

Gat No. 344, At- Pimpli, Tal- Baramati, Dist- Pune

Pune-413102

Copy to:

Regional Officer, MPCB, Pune / Sub-Regional Officer, MPCB, Pune-I

- They are directed to collect the Bank Guarantees from industry within 15 days and ensure the compliance of the consent conditions.

CAO / Cess wing

Received Consent fee of-

Sr. No.	Amount(Rs.)	₩DD: No.Vic	Date This like	Drawn On
1	225000	915068	16 Mar 2010	SBI Bank

<sup>\*</sup>Fees of Rs.28, 000/- from the above submitted fees will be adjusted during next renewal of consent.