

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 4010437/4020781
 /4037124/4035273
 Fax : 24044532/4024068 /4023516
 Email : enquiry@mpcb.gov.in
 Visit At : <http://mpcb.gov.in>



Kalpataru Point, 3rd & 4th floor, Sion- Matunga
 Scheme Road No. 8, Opp. Cine Planet Cinema, Near
 Sion Circle, Sion (E),
 Mumbai - 400 022

Red/LSI

Date 26/09 /2013

Consent No: *Format 1.0/BO/JDWPC/EIC TN4160-13/R/CAC-8033*

To,
 M/s Bombay Rayon Fashion Ltd
 C-6 & 7, MIDC Tarapur
 Dist Thane,

Subject: Consent to Operate RED category.

Ref : 1. Earlier Consent granted vide no. BO/JD-WPC/RO ABAD/EIC TN-3432-12/O/CAC-554....dtd 13.8.2012 (Textile plant). And BO/JD-WPC/RO ABAD/EIC TN-3958-12/O/CAC-711....dtd 13.12.2012 (Captive power plant).
 2. Minutes of CC/CAC meeting held on 12.7.2013

Your application Dated: 17-12-2012 & 20.8.2013

For: Consent to Renewal & Amalgamation under Section 25/26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization under Rule 5 of the Hazardous Wastes (M, H & T M) Rules 2008 is considered and the consent is hereby granted subject to the following terms and conditions and as detailed in the schedule I, II, III & IV annexed to this order:

- The consent is granted for a period from 1.1.2013 to 31.01.2014. The actual capital investment of the industry is Rs. 791.39 Crs. (A - Towards power plants 40.29 Crs , B- Other than power plant i.e. Textile plants 751.10 Crs) (As per C.A. Certificate submitted by industry)
- The Consent is valid for the manufacture of -

Sr. No.	Product / By-Product Name	Maximum Quantity in MTA
1	Processed Fabrics (Including Yarn Dyeing printing, finishing)	9000000 Million meters /M
2	Captive power generation using imported Coal (Electricity)	8 MW

- Conditions under Water (P&CP), 1974 Act for discharge of effluent:

Sr. no.	Description	Permitted quantity of discharge (CMD)	Standards to be achieved	Disposal
1.	Trade effluent	Total effluent = 3262 CMD. Textile Plant- 3000 CMD Power Plant - 262CMD	As per Schedule -I	Industry shall achieve 50 % i.e 1500CMD ,recycle of Treated effluent within 1 year The treated effluent from power plant shall be recycled/reused 100%

2.	Domestic effluent	55	As per Schedule -I	CETP

4. Conditions under Air (P& CP) Act, 1981 for air emissions:

Sr. no.	Description of stack / source	Number of Stack	Standards to be achieved
1.	Boiler, furnace	2	As per Schedule -II
2.	DG set	1	As per Schedule -II

5. Conditions about Non Hazardous Wastes:

Sr. no.	Type Of Waste	Quantity & UoM	Treatment	Disposal
1	Fly Ash	14 MT/D	-	Sale to Brick manufacturers
2	Card Board Waste	1.2 MT/M	-	Sale to outside parties
3	Fabric waste	1.2 MT/M	-	Sale to outside parties

6. Conditions under Hazardous Waste (MH & TM) Rules, 2008 for treatment and disposal of hazardous waste:

Sr. No.	Type Of Waste	Category	Quantity	UOM	Treatment	Disposal
1	Chemical sludge from ETP	33.3	6	MT/M	-	CHWTSDF

7. The Board reserves the right to review, amend, suspend, revoke etc. this consent and the same shall be binding on the industry.

8. This consent should not be construed as exemption from obtaining necessary NOC/permission from any other Government authorities.

For and on behalf of the
Maharashtra Pollution Control Board

(Rajeev Kumar Mittal)
Member Secretary

Received Consent fee of -

Sr. No.	Amount (Rs.)	DD No.	Date	Drawn By
1	1502300.00	116266	31/12/2012	Axis Bank
2	25000	021023	26/8/2013	ICICI Bank
3	1,31,900	021229	05.09.2013	ICICI Bank Ltd.

Copy to:

1. Regional Officer -Thane and Sub-Regional Officer- Trapur I MPCB. They are directed to ensure the compliance of the consent conditions.
2. Chief Accounts Officer, MPCB, Mumbai.
3. CC/CAC desk- for record & website updation purposes.

Schedule-I

Terms & conditions for compliance of Water Pollution Control:

- 1) A) As per your application, you have provided the Effluent Treatment Plant (ETP) with the design capacity of 8000 CMD.
B) The Applicant shall operate the effluent treatment plant (ETP) to treat the trade effluent so as to achieve the following standards prescribed by the Board or under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

Textile Plant

Sr No.	Parameters	Standards prescribed by Board (If any)
		Limiting Concentration in mg/l, except for pH
01	pH	6.0 to 8.5
02	Oil & Grease	10
03	BOD (3 days 27oC)	100
04	Total Dissolved Solids	-
05	COD	250
06	Detergent	2
07	TAN	50
08	Suspended Solids	100

B) Captive Power Plant

a) Condenser cooling Water:

- 1) pH Between 6.5 to 8.5
2) Temperature not to exceed 7 Degree C. Higher than the intake water temperature.
3) Free available Chlorine not to exceed 0.5 mg/l.

b) Boiler Blow down:

- 1) Suspended solids Not to exceed 100 mg/l.
2) Oil & Grease Not to exceed 20 mg/l.
3) Copper (Total) Not to exceed 1 mg/l.
4) Iron (Total) Not to exceed 1 mg/l.

c) Cooling Tower Blow down:

- 1) Free available Chlorine Not to exceed 0.5 mg/l.
2) Zinc Not to exceed 1 mg/l.
3) Chromium (Total) Not to exceed 0.2 mg/l.
4) Phosphate Not to exceed 5 mg

d) D.M. Plant Effluent:

- 1) PH Between 5.5 to 9
2) BOD 3 days 27 Deg. C. Not to exceed 30 mg/l
3) COD Not to exceed 250mg/l
4) Suspended Solids Not to exceed 100mg/l.
5) Oil & Grease Not to exceed 10mg/l.
6) TDS Not to exceed 2100mg/l.

C) Disposal For Power Plant Effluent - Industry shall recycle/reuse the treated effluent 100% for ash quenching/Toilet flushing etc.

D) Disposal For Textile Plant Effluent - Industry shall achieve 50 % i.e 1500 CMD recycle/reuse within 1 year i.e upto 31.08.2014.

A.] As per your consent application domestic effluent shall be discharged into drainage system provided by MIDC which is further connected to CETP.

B] The Applicant shall operate the sewage treatment system to treat the sewage so as to achieve the following standards/ prescribed under EP Act, 1986 and Rules made there under from time to time, whichever is stringent.

- | | | | | |
|-----|-------------------|---------------|-----|-------|
| (1) | Suspended Solids. | Not to exceed | 100 | mg/l. |
| (2) | BOD 3 days 27oC. | Not to exceed | 100 | mg/l. |

C] The treated sewage shall be discharged into drainage system provided by MIDC which is further connected to CETP.

D] In case the treatment system is combined for trade effluent and sewage then the standards and disposal path prescribed at sr no.1 B & C of schedule I shall be applicable.

- 2) The Board reserves its rights to review plans, specifications or other data relating to plant setup for the treatment of waterworks for the purification thereof & the system for the disposal of sewage or trade effluent or in connection with the grant of any consent conditions. The Applicant shall obtain prior consent of the Board to take steps to establish the unit or establish any treatment and disposal system or and extension or addition thereto.
- 3) The industry shall ensure replacement of pollution control system or its parts after expiry of its expected life as defined by manufacturer so as to ensure the compliance of standards and safety of the operation thereof.

4) The Applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 and as amended, by installing water meters, filing water cess returns in Form-I and other provisions as contained in the said act.

Sr. no.	Purpose for water consumed	Water consumption quantity (CMD)
1.	Industrial Cooling, spraying in mine pits or boiler feed	3669
2.	Domestic purpose	391
3.	Processing whereby water gets polluted & pollutants are easily biodegradable	6490
4.	Processing whereby water gets polluted & pollutants are not easily biodegradable and are toxic	-

5) The Applicant shall provide Specific Water Pollution control system as per the conditions of EP Act, 1986 and rule made there under from time to time/ Environmental Clearance/ CREP guidelines.

Schedule-II

Terms & conditions for compliance of Air Pollution Control:

- As per your application, you have proposed to install/ provided the Air pollution control (APC) system and also proposed to erect / erected following stack (s) and to observe the following fuel pattern-

Sr. No.	Stack Attached To	APC System	Height in Mtrs.	Type of Fuel	Quantity & UoM	S %	SO ₂ Kg/Day
1	Thermopack & process Boiler	Multi cyclone type of dust collectors followed by bag filters provided to coal fired boiler	48	coal	30 MT/D	< 0.5	600
2	D.G.Set (1500 KVA)	Stack of adequate height	8 meter above roof	HSD	200 Ltr/day	0.5	
3	Boiler for power plant	ESP	68	coal	200 MT/day	< 0.5	2000

- specific control equipments- Nil
- The applicant shall operate and maintain above mentioned air pollution control system, so as to achieve the level of pollutants to the following standards:

Particulate matter	Not to exceed	100 mg/Nm ³ .
--------------------	---------------	--------------------------

- The Applicant shall obtain necessary prior permission for providing additional control equipment with necessary specifications and operation thereof or alteration or replacement well before its life come to an end or erection of new pollution control equipment.
- The Board reserves its rights to vary all or any of the condition in the consent, if due to any technological improvement or otherwise such variation (including the change of any control equipment, other in whole or in part is necessary).

Schedule-III
Details of Bank Guarantees

Sr. No.	Consent (C to E/O/R)	Amt of BG Imposed	Submission Period	Purpose of BG	Compliance Period	Validity Date
1	Renewal	5.0 Lakhs	15 days	Towards achieving 50 % recycle within 1 year	One year	31.05.2014
2	Renewal	5.0 Lakhs	15 days	Towards O & M of pollution control system	One year	31.05.2014

Maharashtra Pollution Control Board

Schedule-IV

General Conditions:

- 1) The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous waste to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- 2) Industry should monitor effluent quality, stack emissions and ambient air quality monthly/quarterly.
- 3) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- 4) Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- 5) The applicant shall provide an alternate electric power source sufficient to operate all pollution control facilities installed to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms and conditions of this consent.
- 6) The firm shall submit to this office, the 30th day of September every year , the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as per the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- 7) The industry shall recycle/reprocess/reuse/recover Hazardous Waste as per the provision contain in the HW(MH&TM) Rules 2008, which can be recycled/processed/reused/recovered and only waste which has to be incinerated shall go to incineration and waste which can be used for land filling and cannot be recycled/reprocessed etc. should go for that purpose, in order to reduce load on incineration and landfill site/environment.
- 8) The industry should comply with the Hazardous Waste (M,H & TM) Rules, 2008 and submit the Annual Returns as per Rule 5(6) & 22(2) of Hazardous Waste (M,H & TM) Rules, 2008 for the preceding year April to March in Form-IV by 30th June of every year.
- 9) An inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- 10) The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent .
- 11) Industry shall strictly comply with the Water (P&CP) Act, 1974, Air (P&CP) Act,1981 and Environmental Protection Act,1986 and industry specific standard under EP Rules 1986 which are available on MPCB website(www.mpcb.gov.in).
- 12) The industry shall constitute an Environmental cell with qualified staff/personnel/agency to see the day to day compliance of consent condition towards Environment Protection.
- 13) Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of the collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes/sewers downstream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system.
- 14) Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

- 15) The applicant shall install a separate meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- 16) Conditions for D.G. Set
 - a) Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
 - b) Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
 - c) Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
 - d) Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
 - e) A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
 - f) D.G. Set shall be operated only in case of power failure.
 - g) The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
 - h) The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel.
- 17) The industry should not cause any nuisance in surrounding area.
- 18) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB (A) during day time and 70 dB (A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.
- 19) The applicant shall maintain good housekeeping.
- 20) The applicant shall bring minimum 33% of the available open land under green coverage/ plantation. The applicant shall submit a yearly statement by 30th September every year on available open plot area, number of trees surviving as on 31st March of the year and number of trees planted by September end.
- 21) The non-hazardous solid waste arising in the factory premises, sweepings, etc. be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal of solid waste.
- 22) The applicant shall not change or alter the quantity, quality, the rate of discharge, temperature or the mode of the effluent/emissions or hazardous wastes or control equipments provided for without previous written permission of the Board. The industry will not carry out any activity, for which this consent has not been granted/without prior consent of the Board.
- 23) The industry shall ensure that fugitive emissions from the activity are controlled so as to maintain clean and safe environment in and around the factory premises.
- 24) The industry shall submit quarterly statement in respect of industries obligation towards consent and pollution control compliance's duly supported with documentary evidences (format can downloaded from MPCB official site).
- 25) The industry shall submit official e-mail address and any change will be duly informed to the MPCB.
- 26) The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.

-----0000-----