MAHARASHTRA PO	LLUTION	CONTROL BOARD
Tel: 24010437/24020781/24014701	MAHARASHTRA	Kalpataru Point, 2 nd - 4 th Fl.
Fax: 24024068 / 24023516		Opp. Cine Planct Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: mpcb@vsnl.net		Mumbai-400 022.
Red/L.S.I		Date: 21 /10 /2013

Consent No: BO/JD (APC)/EIC No. TN-4680-13/E/CC-8848

Consent to Establish under Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Viraj Profiles Ltd. Plot No. G-1/4, MIDC Tarapur, Boisar, Dist. Thane.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to establish is granted for a period up to commissioning of the unit or 5 year which ever is earlier.

2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Metal (Recovered	1000	MT/M
	from Slag)		

3. CONDITIONS UNDER WATER ACT:

The daily quantity of trade effluent from the factory shall not exceed 10.0 M³. (ii) The daily quantity of sewage effluent from the factory shall not exceed 5.0 M³.

(iii) Trade Effluent :

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

SRO the method is really the

Page 1 of 5

L	pН	Between	5.5 to 9.0
2	BOD 3 days 27 Deg. C	Not to exceed	30 mg/l
3	COD	Not to exceed	250 mg/l
	Oil & Grease	Not to exceed	10 mg/l
1	Suspended Solids	Not to exceed	100 mg/l.
;	Chloride	Not to exceed	600 mg/l.
r	Sulphate	Not to exceed	1000 mg/l.
5	Iron (as Fe)	Not to exceed	3.0 mg/l.
	Total metal	Not to exceed	10.0 mg/l.

- (iv) **Trade Effluent Disposal:** The industrial effluent shall be recycled 100 % in process after treatment. There shall not be any discharge outside the factory premises.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100 mg/l.
(2)	BOD 3 days 27o C.	Not to exceed	100 mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vi) Non-Hazardous Solid Wastes:

Sr. No.	Type of waste	Quantity	Disposal
1	Slag	12000 MT/M	Land filling own premises/ dispose to authorized Cement mfg plant.

(viii) Other Conditions:

- i) The unit shall carry out monthly monitoring of treated domestic as well as Industrial effluent and submit the report of the same to the Board regularly
- ii) The unit shall take necessary efforts for segregation of solid waste at source only and disposal salable waste regularly. The records showing waste segregation at source to be maintained.
- iii) The unit shall take necessary efforts regarding rain water harvesting every monsoosn.
- 4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic	•••	5.00 CMD
(ii) Industrial Processing		50.0 CMD
(iii) Industrial Cooling		30.0 CMD
(iv) Industrial Processing		
& floor washing	•••	0.00 CMD
(iv) Agriculture / Gardening	•••	10.0 CMD

Page 2 of 5

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

(i)The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

Control Equipment:

- i) Industry shall provide dust collector/bag filter at slag crushing & screening section.
- ii) Conveyor system for handling of finished & raw materials shall be closed with cladding with dust suppression system.
- iii) Fume extraction system followed by dust collection system of sufficient capacity should be provided to all sources of SPM/TPM shall be operated properly and continuously.
- iv) There shall not be any secondary (Fugitive) emissions.

b. Standards for Emissions of Air Pollutants:

(i)	SPM/TPM	Not to exceed 150 mg/Nm ³
(ii)	SO ₂	Not to exceed 610 Kg/Day.

c. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

SRO Tarapar ELRH 925 Globe

Page 3 of 5

(I) The applicant shal	observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM	
1	HSD/Diesel		KL/D	

(ii)The applicant shall erect the chimney(s) of the following specifications:-

	Sr. No.	Chimney Attached To	Height in Mtrs.
'	1	D.G. Set (1 Nos)100 KVA	3.0 meter above shed

i. The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

j. The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(iii) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 3) The D.G. Set shall be utilized as a standby power source and shall be operate only in case of power failure

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) RULES, 2008: The Industry shall not generate any hazardous wastes

7. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.

PROFEMENT REPORTS FOR

Page 4 of 5

- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory
- 8. The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.
- 9. This issued with approval of Consent Committee meeting of the Board held on dtd. 21/09/2013.
- 10. You shall submit Bank Guarantee of Rs. 5/ Lakhs in favor of Regional Officer, THANE within 15 days towards consent condition. The Bank Guarantee shall be valid up to 21/09/2018.
- 11. Industry shall not increase any effluent load to CETP Tarapur.
- 12. The Capital investment of the industry is Rs.55.62 Crs (existing CTE Rs.36.22 Crs + proposed CTE Rs.19.40 Crs)

(Rajeev Kumar Mital IAS) Member Secretary

To,

M/s. Viraj Profiles Ltd., Plot No. G-1/4, MIDC Tarapur, Boisar,Dist. Thane

Copy to:

1) Regional Officer- Thane/Sub-Regional Officer, MPCB, Tarapur-I they are directed to ensure the Compliance of consent conditions & submit the report within 1 month Period.

2) Chief Accounts Officer, MPCB, Mumbai

Received	Consent	fee	of

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	50100/-	000496	03/07/2013	HDFC Bank

SRO Longue Es R. E. 92531000

Page 5 of 5