


MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2nd - 4th Floor
Fax: 24024068 / 24023515		Opp. Cine Planet Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: ast@mpcb.gov.in		Mumbai-400 022.

RED/L.S.I

Date: 02/12/2013

Consent No: BO/AS (T)/RO KP/EIC NO.KP-13667-13/R/CC-9930

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s Pentokey Organy India Ltd.
Plot No. D-1/1, MIDC Lote Parshuram,
Tal-Khed, Dist - Ratnagiri.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 28/02/2018.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity
1	Acetic Anhydride	41.70 MT/M.
2	N-Butyl Acetate	2733.90 MT/M.
3	Ethyl Acetate	
4	Acetaldehyde	500 MT/M.
5	Acetic Acid	600 MT/M.
6	Electricity (Co-generation for captive use)	0.6 MW

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 117 m³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 30 m³.
- (iii) **Trade Effluent :**

Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	6.5 to 8.5
2	Suspended Solids	Not to exceed	100 mg/l.
3	BOD 3 days 27 deg C	Not to exceed	100 mg/l
4	COD	Not to exceed	250 mg/l.
5	Oil & Grease	Not to exceed	10 mg/l
6	T.D.S	Not to exceed	2100 mg/l
7	Sulphate	Not to exceed	1000 mg/l
8	Chlorides	Not to exceed	600 mg/l

B) Captive Power Plant**I. Condenser Cooling Water:**

- | | | |
|----------------------------|---------------|------------------------------------------------|
| 1. pH | Between | 6.5 to 8.5 |
| 2. Temperature | Not to exceed | 5 °C Higher than the intake water temperature. |
| 3. Free available Chlorine | Not to exceed | 0.5 mg/l. |

II. Boiler Blowdown:

- | | | |
|---------------------|---------------|-----------|
| 1. Suspended Solids | Not to exceed | 100 mg/l. |
| 2. Oil & Grease | Not to exceed | 20 mg/l. |
| 3. Copper (Total) | Not to exceed | 1 mg/l. |
| 4. Iron (Total) | Not to exceed | 1 mg/l. |

III. Cooling Tower Blowdown:

- | | | |
|----------------------------|---------------|-----------|
| 1. Free available chlorine | Not to exceed | 0.5 mg/l. |
| 2. Zinc | Not to exceed | 1 mg/l. |
| 3. Chromium (Total) | Not to exceed | 0.2 mg/l. |
| 4. Phosphate | Not to exceed | 5 mg/l. |

(iv) **Trade Effluent Disposal:** The treated effluent shall be reused for gardening up to maximum extent and remaining shall be disposed into CETP.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

- | | | | |
|-----------------------|---------------|-----|-------|
| (1) Suspended Solids | Not to exceed | 200 | mg/l. |
| (2) BOD 3 days 27o C. | Not to exceed | 100 | mg/l. |

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Disposal
1	Boiler Ash	20	MT/Day	Sale to Brick manufacturers.

(viii) **Other Conditions:**

- 1) Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

- | | | | |
|---------------------------------------------------------------------|-----|------|-----|
| (i) Domestic purpose | ... | 40 | CMD |
| (ii) Water gets Polluted & Pollutants are Biodegradable | ... | 120 | CMD |
| (iii) Water gets Polluted, Pollutants are not Biodegradable & Toxic | ... | ---- | CMD |
| (iv) Industrial Cooling, spraying in mine pits or boiler feed | ... | 140 | CMD |
| (v) Agriculture / Gardening | ... | ---- | CMD |

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

a) Control Equipment:

1. Scrubber system of sufficient capacity should be provided to control the emissions and operated properly.
2. There shall not be any secondary (fugitive) emissions.

b) Standards for Emissions of Air Pollutants:

(i) SPM	Not to exceed	150 Mg/Nm ³
(ii) SO ₂	Not to exceed	1080 kg/day
(iii) HCL/Acid Mist	Not to exceed	35 mg/Nm ³

c) Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure.
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(ii) **The applicant shall observe the following fuel pattern:-**

Sr. No.	Type Of Fuel	Quantity
1	Furnace Oil OR Rice Husk OR Coal	12 KL/day 100 MT/Day 60 MT/day
2	Diesel	30 Kg/Hr.

(iii) **The applicant shall erect the chimney(s) of the following specifications:-**

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Boiler 1 & 2	30.5
2	Boiler 3	35
3	Scrubbers (2 Nos.)	25
4	D.G. Set (220 KVA)	3.0*

(* Above the roof of building in which it is installed.)

(iv) **The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents**

attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

- (v) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(vi) **Other Conditions:**

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. No.	Type Of Waste	Quantity	Disposal
1	34.3 Chemical sludge from waste water treatment	3 MT/Y	CHWTSDF

- (ii) Treatment: - NIL

7. Whenever due to any accident or gas leakage or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of Industry, Safety and Health, Police Station, Fire Brigade, Directorate of Health Services, Department of Explosives, Board and Local Body and the production process should be stopped by taking all necessary safety measures. The industry shall also monitor the emission and ensure that the emissions do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

8. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

- Viii The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
9. The consent should not be construed as any exemption from obtaining necessary NOC from other Government agencies as may deemed fit necessary.
10. The industry shall also comply with the industry specific standards notified under Environment Protection Act.
11. If CETP does not operate efficiently and problem of pollution occurs, industry should voluntarily stop the production or total effluent should reuse.
12. **Industry shall submit Bank Guarantee of Rs. 5 Lakh to the Regional Officer, Kolhapur within 15 days, towards O & M of Pollution Control Systems, which shall be valid up to 30.06.2018.**
13. This consent is issued as per the decision taken in 15th Consent Committee meeting of the Board held on 27/11/2013.
14. The Capital investment for expansion is Rs. 30.43 Cr.

This consent is issued with reference to the Powers delegated as per Office Note dtd. 11.11.2013

Mirashe
21/11/13
(P. K. Mirashe)

Assistant Secretary Technical

To,
M/s Pentokey Organy India Ltd.
Plot No. D-1/1, MIDC Lote Parshuram,
Tal-Khed, Dist - Ratnagiri.

Copy to:

- 1) Regional Officer, MPCB, Kolhapur 2) Sub Regional Officer, Chiplun -They are directed to obtain BG of Rs 5.0 Lakh from industry towards O & M of PCS and ensure the compliance of consent conditions.
3) Chief Account Officer, MPCB, Mumbai, 4) Cess Branch, MPCB, 5) Master File.

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	325000	011502	06/06/2013	Bank of India
2	50000	121653	25/10/2010	Bank of India

The balance fees Rs. 31,250/-, with the Board will be considered at the time of next renewal of consent.