

MAHARASHTRA POLLUTION CONTROL BOARD

Tel: 24010437/24020781/24014701		Kalpataru Point, 2 nd - 4 th Fl.
Fax: 24024068 / 24023516		Opp. Cine Planet Cinema,
Website: http://mpcb.gov.in		Near Sion Circle, Sion (E)
E-mail: mpcb@vsnl.net , jdair@mpcb.gov.in		Mumbai-400 022.

Red/L.S.I

Consent No: BO/JD(APC)/EIC No. PN- 18662-13/R/CC-10080 Date: 09/12/2013

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2008

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

.....
CONSENT is hereby granted to

**M/s. Foseco India Ltd.,
Gat No.922/923, Sanaswadi,
Tal. Shirur, Dist. Pune -412 208.,
Maharashtra.**

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period up to: 31.05.2014.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Sleeves	267	MT/M
2	Flat Board	25	MT/M
3	Coating	1250	MT/M
4	Moulding Material	1250	MT/M
5	Metal Treatment Powder and Paste for Foundry	830	MT/M

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 44.0M³.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 13.8 M³.

(iii) Trade Effluent Treatment :

The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to standards as specified in schedule -VI of part A of Environmental protection Rules, 1986. These standards are applicable only for disposal of treated effluent on land for irrigation. Effluent standards applicable at the site delivery point.

1	pH	Between	5.5 to 9.0
2	Oil & Grease	Not to exceed	10 mg/l
3	Suspended Solids	Not to exceed	1000 mg/l.
4	BOD 3 Days 27 degree C	Not to exceed	30 mg/l.
5	COD	Not to exceed	250 mg/l.
6	TDS	Not to exceed	2100 mg/l.
7	Sulphates	Not to exceed	1000 mg/l.
8	Chlorides	Not to exceed	600 mg/l

(iv) **Trade Effluent Disposal:** The treated effluent shall be reused /recycled back in to process for cooling purpose and remaining treated effluent shall be utilized on land for gardening /plantation in the premises only. There shall not be any discharge outside the factory premises.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

1	Suspended Solids	Not to exceed	100 mg/l.
2	BOD 3 days 27o C.	Not to exceed	100 mg/l.

(vi) **Non-Hazardous Solid Wastes:**

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	Plastic bags and packing material	3.0	MT/M		Sale
2	Bio mass sludge	2.5	MT/M	-----	Sale
3	Empty containers	70	No/M	-----	Sale

(vii) **Other Conditions:**

- The unit shall carry out monthly monitoring of treated domestic as well as industrial effluent and submit the report of the same to the Board regularly
- The unit shall take necessary efforts for segregation of solid waste at source only and disposal salable waste regularly. The records showing waste segregation at source to be maintained.
- The unit shall take necessary efforts regarding rain water harvesting every monsoosn.

4. **The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under**

The daily water consumption for the following categories is as under:

I	Domestic	18.0 CMD
ii	Industrial Processing	75.0 CMD
iii	Industrial Cooling	22.0 CMD
iv	Agriculture / Gardening	50.0 CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT:

(i)The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

A) Control Equipment:

1. Fume extraction system followed by dust collection system of sufficient capacity shall be provided at all dust generating locations and operated properly and continuously.
2. Fume extraction system followed by Scrubbing system sufficient capacity shall be provided to all sources of gaseous emission.
3. There shall not be any secondary (fugitive) emissions.

B) Standards for Emissions of Air Pollutants :

i	SPM/TPM	Not to exceed	150 mg/Nm ³
iii	SO ₂	Not to exceed	157.0 Kg /Day

C) The applicant shall observe the following fuel pattern:-

Sr.No.	Type of fuel	Qty	UOM
1	HSD	310	Ltr/Hr
2	LPG	220	Kg /Hr
3	LDO	60	Ltr/Hr

D) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1	Thermopac	18
2	D.G.Set(500 X 3 KVA)	4.5
3	Oven	15
4	Dust collector 3 nos	1.0 above roof ridge

E) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

F) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality Regularly.
- 3) The D.G. Set shall be utilized as a standby power source and shall be operate only in case of power failure.

6. Conditions for D.G. Set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- d. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- e. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- f. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- g. D.G. Set shall be operated only in case of power failure
- h. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set

7. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDARY MOVEMENT) RULES, 2008:

- (i) The Industry shall handle hazardous wastes as specified below.

Sr. N	Cate-gory	Type Of Waste	Quantity	UOM	Treatment	Disposal
1	34.3	ETP Sludge	1500	Kg / M	-----	CHWTSDF
2	5.1	Used oil/ Spent oil	440.0	Litrs / M	-----	To Authorized Recycler / reprocessor
3	33.3	Discarded /Empty containers barrels/ liners	1020	Nos/ M	-----	Sale To Authorized Recycler.
4	23.1	Waste /residue(non made with vegetable Or animal mate)	8.40	MT/Y		CHWTSDF

- (ii) Treatment: - NIL.

- a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Board, concerned Police Station, office of Directorate of Health Services, Department of Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.
- b. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- c. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2003 and shown & submitted to the Board as & when asked for.

8. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.
- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. ix. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.

- xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection system
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.

9. Industry shall carry out feasibility study regarding treatment of domestic and industrial effluent in ETP within 2 months[i.e. up to 31.01.2014] and based on the feasibility if necessary ,industry should provide it within 6 months[i.e. up to 31.05.2014] and shall submit bank guarantee of Rs.5 Lakhs towards compliance of the same.

10. This issued with approval of Consent Committee meeting of the Board held on dtd. 27.11.2013.

11. The Capital investment of the industry is Rs. 49.11 Crs.

This consent is issued as per empowerment delegated by Hon'ble Member Secretary to HOD's vide office note dated 11.11.2013.

For and On Behalf of the
Maharashtra Pollution Control Board,


(V.M.Motghare) 27/11/13
Joint Director [Air Pollution Control]

To,
M/s. Foseco India Ltd.,
Gat No.922/923, Sanaswadi,
Tal. Shirur, Dist. Pune -412 208.,
Maharashtra.

Copy to:

RO- MPCB Pune /SRO- Pune-II, MPCB Pune-

- They are directed to forfeit the bank guarantee of Rs.5 lakhs out of Rs.10 Lakhs and obtain top up B.G. of Rs.10 Lakhs from the industry towards operational and maintenance of pollution control system. Also as per condition no. 9 ensure the compliance of consent conditions & submit the performance report within 1 month period.

- CAO/Cess Branch/Master File

Received Consent fee of -

Sr. No.	Amount(Rs.)	DD. No.	Date	Drawn On
1	2,25,100/-	059724	24.07.2013	ICICI Bank