VAHARASHATRA POLLUTION CONTROL BOARD

.

24024068 / 24044532

mail : mpcb@vsnl.net



Kalpataru Point, 2nd, 3rd & 4th Floor,

Opp. Cineplanet, Near Sion Circle, Sion (E), Mumbai-400022.

init At : http://mpcb.gov.in

.EIC No: PN- 19964-13

nirastructure Project/Orange/LSI Consent No. MPCB/RO(HQ)/Pune/CE/CC/ 262

Date: 8 HJanuary 2014

1

Consent to Establish Section 25 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008

.....

ONSENT is hereby granted to,

M/s. Pharande Promoters & Builders,

"Woodsville Phase-III",

Gat No. 725, 728 to 736 at Borhatewadi,

Tal. Haveli, Dist- Pune.

Located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

- 1 The Consent to Establish is granted for a period up to: <u>Commissioning of the unit or</u> five years period, whichever is earlier.
- 2. The Consent is valid for development of land/Plot as new construction Activity for construction of Residential project developed by, M/s. Pharande Promoters & Builders,
 - n mod as "Woodsville Phase-III" at Gat No. 725, 728 to 736 at Borhatewadi, Tal Haveli, Dist
 - une, on total plot area of 25,400.0 sq.mt and total Built up area 56,812.11 sq.mt including
 - a dates for development of Residential project & Services as per Construction a muencement Certificate issued by local body

CONDITIONS UNDER WATER ACT:

The daily quantity of sewage effluent from the project shall not exceed:- 258.0 M³/Day.

Sewage Effluent Treatment: The applicant shall provide comprehensive treatment

ystem as is warranted with reference to influent quality and operate and maintain the

/ Chineset Chinehwad /I/O/L/94663000 "Woodsville Phase-III"

same continuously so as to achieve the quality of treated effluent to the following standards.

1	TT		
	pH	Not to exceed	6.5 to 9.0
	Suspended Solids	Not to exceed	100 mg/l.
3	BOD 3 Days 27 degree C	Not to exceed	
4	Fecal Coliform	Not to exceed	100 mg/l.
			500/100/1 mg/l.

Sewage Effluent Disposal: The treated domestic effluent shall be 80% recycled and reused for flushing, fire fighting and cooling of Air conditioners and remaining shall be discharged to Municipal sewer. In no case, effluent shall find its way to any water body directly/indirectly at any time.

Project proponent shall operate STP for five years from the date of obtaining Occupation Certificate.

IV. Non-Hazardous Solid Wastes:

Sr. No.	Type Of Waste	Quantity	UOM	Treatment	Disposal
	Bio degradable waste	477.00	Kg/Day	OWC Proposed	Used as manure
2 Maa	Non Bio-degradable waste	477.00		Authorized	Sale
3	STP Sludge	38.70	Kg/Day	recyclers	Used as manure

v. Other Conditions (during Construction Phase):

- All activities shall be in resonance with the provisions of Indian Forest Act, 1927 (16 of 1927), Forest (Conservation) Act, 1980 (69 of 1980) and Wildlife (Protection) Act, 1972 (53 of 1972), and special notification published for area wherever applicable and all the Environmental Statutes and Instruments.
- This Consent to Establish is issued only for New Construction/Developing Construction
 Project purposes.
- 3. No quarrying activities shall be commenced in the area unless appropriate permissions are obtained for a limited quarrying material required for construction of local residential housing and traditional road maintenance work, provided that such quarrying is not done on Forest Lands and the material is not exported to the outside
- 1. There shall be no felling of trees whether on Forest, Government, Revenue or Private lands except as per prevailing Rules.
- Extraction of Groundwater for the project shall require prior permission of the State Ground Water Authority or other relevant authorities, as applicable.
- Near the activities that are related to water (like activity of water parks, water sports) and/or in the vicinity of lake, Dissolved Oxygen shall not be less than 5 mg/liter.
- In order to ensure that the water from this project do not enter into outside environment, the nallas crossing the township/complex premises, shall be lined, covered and made water tight by the applicant within the premises with intermittent inspection of chambers following good engineering practices as per the regulations of Docal body.
- The Applicant shall prepare management plan for water harvesting, roof-water reclamation, water/storm water conservation and implement the same before handling over of complex for occupation.

2 :: angat Chinchwad /I/O/L/94663000 "Woodsville Phase-III"

2

- 9. Applicant shall provide fixtures for showers, toilet, flushing and drinking should be of low flow either by use of aerators or pressure reducing devices or sensor based control.
- 10. The Applicant shall draw plans for the segregation of solid wastes into biodegradable and non-biodegradable components. The biodegradable material shall be recycled through scientific in-house composting (i.e vermi-composting facility within premises) with the approval of local body. The proper demarked area shall be identified for collection & storage of MSW properly which, shall be finally disposed off at approved Municipal Solid Waste landfill site of local body environmentally acceptable location and method. It is clarified that the term solid waste includes domestic, commercial, and garden wastes, but does not include hazardous and bio-medical wastes. The activities of bio-composting and engineered landfill shall be as per the Municipal Solid Waste (M&H) Rules, 2000
- 11. The applicant/generator shall be responsible for safe and scientific collection, transportation, treatment and disposal of Bio-Medical Waste as per the provisions made under the Bio-Medical Waste (Management & Handling) Rules, 1998. Any activity as defined under BMW (M & H) Rules has to obtain a separate Authorization from Maharashtra Pollution Control Board.
- 12. Vehicles hired for construction activities should be operated only during non peak
- 13. Ready mixed concrete used in building construction should apply separately for consent
- 14. applicant, during the construction stage shall provide
 - a. Septic tank and soak pit of adequate capacity for the domestic effluent generated due to workers residing at site.
 - b. Proper loading and unloading of construction material, excavated material and its proper disposal as per MSW (M&H) Rules 2000. С.
 - Cutting of trees is not permitted, however in unavoidable conditions necessary permission from the local body shall be obtained.

d. Green belt of 33% of the open space shall be developed.

15. E-Waste shall be disposed to authorized re processor.

The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under The daily water

The daily	water	consumption f	or th	ie foll	owing	optomoria		,	
G) Dom.		-L reom 1			owing.	categories	is as	under	

	Domestic	Ū.	320.20 CMD
	Water gets Polluted &		040.40 UMD
	Pollutants are Biodegradable		0.00 CMD
(m)	Water gets Polluted, Pollutants		
	are not Biodegradable & Toxic		0.00 CMD
	Industrial Cooling, spraying		
	spraying		0.00CMD

The applicant shall regularly submit to the Board the returns of water consumption in the rescribed form and pay the Cess as specified under Section 3 of the said Act.

CONDITIONS UNDER AIR (Prevention & Control of Pollution) ACT, 1981:

(i) The Applicant may install 3 no. of diesel generating sets (DG Sets), of capacities 125 KVA each, shall be equipped with comprehensive control system as is warranted with reference to generations of emissions and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

) Econymi Chinchwad /I/O/L/94663000 "Woodsville Phase-III"

 \mathbf{V}

3

a. Standards for Emissions of Air Pollutants:

(1) SPM/TPM	Not to exceed	150 mg/Nm3
(ii) SO2 (DG Set)	Not to exceed	48.0 Kg/day

(ii) The following measures shall be taken:

- a. Adequate mitigation measures shall be taken to control emissions of SO2, NOx, SPM, and RSPM.
- b. Applicant shall achieve following Ambient Air Quality standards.

1.	SPM Not to Exceed (Annual Average) Not to Exceed (24 hours)	$\frac{140}{200}$	µg/ m3 µg/ m3	
.) 	SO2 Not to Exceed (Annual Average) Not to Exceed (24 hours)	60 80	μg/ m3 μg/ m3	
2).	NOx Not to Exceed (Annual Average) Not to Exceed (24 hours)	60 80	μg/ m3 μg/ m3	
4.	RSPM Not to Exceed (Annual Average) Not to Exceed (24 hours)	$\begin{array}{c} 60 \\ 100 \end{array}$	μg/ m3 μg/ m3	

(iii) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
1	Diesel	35.0	Ltr / Hr

(iv)

The applicant shall erect the chimney(s) of the following specifications:	
---	--

Sr. No.	Chimney Attached To	Height in Mtrs.
1		6.00 (Each DG Set above terrace)

(v) Conditions for D.G. Set

701

- 1 Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- 2. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- 3. The industry shall take adequate measures for control of noise levels from its own sources within the premises in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during the night time. Day time is reckoned between 6 a.m. to 10 p.m and night time is reckoned between 10 p.m to 6 a.m.
- 4. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper sitting and
- 5. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.

k Ph.,pr: Chinchwad 4/O/L/94663000 "Woodsville Phase-III"

4

- 6. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use.
- 7. D.G. Set shall be operated only in case of power failure.
- 8. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.

(vi) Other Condition

- a) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.
- b) Water spraying shall be done on ground to avoid fugitive emissions.
- c) Construction material shall be carried in enclosed vehicles during construction

(vii) Conditions for Utilities like Kitchen, Eating Places etc:

- 1. The kitchen shall be provided with exhaust system chimney with oil catcher connected to chimney through ducting.
- 2. The toilet shall be provided with exhaust system connected to chimney through
- 3. The air conditioner shall be vibration proof and the noise shall not exceed 68 dB (A). 4. The exhaust hot air from A.C. shall be attached to Chimney at least 5 mtrs. higher

than the nearest tallest building through ducting and shall discharge into open air in such way that no nuisance is caused to neighbors.

- (viii) The Applicant shall take adequate measures for control of noise levels from its own sources within the complex (residential cum Commercial) in respect of noise to less than 55 dB(A) during day time and 45 dB(A) during the night time. Daytime is reckoned as between 6 a.m. to 10 p.m. and Nighttime is reckoned between 10 p.m. to 6 a.m.
- (ix) Construction equipments generating noise of less than 65/90 db(A) are permitted.
- No construction work is permitted during nighttime.

Conditions under Hazardous waste (Management, Transboundry movement) Rule, 2008 handling & (\mathbf{i})

The Industry shall handle hazardous wastes as specified below.

Sr. No. Type Of Waste Quantity UOM Disposal

- Nil -

This Board reserves the right to amend or add any conditions in this consent and the same shall be binding on the Applicant.

- 8. This consent shall not be construed as exemption from obtaining necessary NOC from any other Government agencies as may deem feat necessary.
- The applicant shall obtain Consent to Operate from Maharashtra Pollution Control Board before commissioning of the project.
- 10. The applicant shall comply with the conditions stipulated in Environment Clearance granted by GOM, vide no: SEAC-2212/CR-390/TC-2 dated 26th June 2013.

> Emperi Chinchwad 1/O/L/94663000 "Woodsville Phase-III"

- 1. The applicant shall submit Board Resolution towards commencement of construction work without obtaining consent to Establish from the Board and applicant shall submit a Bank Guarantee of Rs. 2.0 Lakh towards submission of Board resolution by 31/01/2014
- 12. This is issued pursuant to the decision of Consent Committee of the Board in its meeting held on 27th December 2013.
- 13. The applicant shall submit a Bank Guarantee of Rs. 5.0 Lakh at Regional Officer, Pune within 15 days for compliance of Consent condition Bank Guarantee shall be valid for period upto five years.
- 14 The proposed Capital investment of the project is Rs. 122.30 Crore.

To,

M/s. Pharande Promoters & Builders, "Woodsville Phase-III",

Gat No. 725, 728 to 736 at Borhatewadi,

Tal. Haveli, Dist- Pune. 410205.

Copy to:

- 1. Regional Officer, MPCB, Pune.- He is directed to obtain necessary Bank Guarantee from the applicant and ensure compliance of consent conditions.
- 2. Sub Regional officer Pimpri Chinchwad, MPCB, Pune.
- 3. Chief Accounts Officer, Mumbai, MPCB,
- 1. Cess Branch, MPCB, Mumbai.

5. Master file

(Rajeev Kuma)

Member Secretary

l) IAS

6

Received Consent fee of

Sr. No.	Amount(Rs.)	DD No	Date	
1	125000/-			Drawn On
2	119710/-	113364	09/10/2013	TJSB Ltd
	115710/-	559505	01/10/2013	HDFC Bank

unosi Chinchwad /I/O/L/94663000 "Woodsville Phase-III"