MAHARASHATRA POLLUTION CONTROL BOARD

	•		1	33	23	12	
P	h	0	n	e		:	

Fax

4010437/4020781 /4037124/4035273 24044532/4024068 /4023516



Kalpataru Point, 3rd & 4th floor, Sion- Matunga Scheme Road No. 8, Opp. Cine Planet Cinema, Near Sion Circle, Sion (E),

1

Mumbai - 400 022

Email enquiry@mpcb.gov.in

> Red/S.S.I/Recycler EIC No: NM-4616-13

Consent No: BO/MPCB/RO(HQ)/Navi Mumbai/CO/B-9965 Date: 4 /12/2013

Consent to Operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous Wastes (Management, Handling & Transboundry Movement) Rules 2008 & Authorization / Renewal of Authorization under Rule 9(1) of the E-Waste (M&H) Rules,

[To be referred as Water Act, Air Act and HW (M&H) Rules respectively].

CONSENT is hereby granted to

M/s. Eco friend Industries A-205, TTC Industrial area, MIDC Pwane, Navi Mumbài=

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(M&H) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

The Consent to Operate is granted for a period up to:. 17/04/2017 1. [Subject to having valid registration from MPCB as "E-Waste Recycler" as per

provisions of the Rule 11 of the E-Waste (M&H) Rules, 2011.]

2. The Consent is valid for the manufacture of -

SIC. No.	Product Name	Maximim	UOM
2	Collection, segregation and dismantling of electrical and electronic wastes as per the provisions of the E-Waste (MH&) Rules, 2011. (Using Environmentally Sound technology as per E-Waste (MH&) Rules, 2011)		MT/A
	E-waste Recycling- Precocious Metal Recovery, Gold, Silver, Copper and PCB from E-waste	240	MT/A
	Using Environmentally Sound technology as per E-Waste (MH&) Rules, 2011)		
3	By-Products:		
i)	Polymer Resin Circuit Boards	35	2000
ii)	Inorganic Salts		MT/M
3. CC	DNDITIONS UNDER WATER ACT.	0.5	MT/M

INDER WATER ACT:

(i) The daily quantity of trade effluent from the factory shall not exceed 0.40 M³. (ii) The daily quantity of sewage effluent from the factory shall not exceed 3.00 M³. SRO Navi Mumbai 1/1/R/S/41777000

(iii) Trade Effluent Treatment: The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

mll		
рн	Between	5.5 to 9.0
Suspended Solids	Not to exceed	
BOD 3 days 27 deg. C		100 mg/l
		100 mg/l.
		250 mg/l.
Off & Grease	Not to exceed	10 mg/l.
	pH Suspended Solids BOD 3 days 27 deg. C. COD Oil & Grease	Suspended SolidsNot to exceedBOD 3 days 27 deg. C.Not to exceedCODNot to exceed

- (iv) Trade Effluent Disposal: The treated effluent shall be connected to sewerage system provided by MIDC and shall be disposed into CETP.
- (v) Sewage Effluent Treatment: The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.
 - Suspended Solids (1)
- Not to exceed (100
- BOD 3 days 27o C. (2)
- Not to exceed. 001mg/l.

mg/l.

(vi) Sewage Effluent Disposal: The treated domestic effluent shall be soaked in a soak pit, which shall be got cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only

(vii) Non-Hazardous Solid Wastes:

DENG	Lyne of Washe	RUOM	Dreatment	
1.	Scrap/plastic packing 2.00	MT/Day		
	material/wood card	MITDay		Sale to
	boards/gunny bags			authorized
				party

(viii)Other Conditions: Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under The daily w ę,

water consumption	for the following	categories is as under:

www.womestic purpose		3.00 CMD
(ii) Water gets Polluted &	•••	STOR CIVID
Pollutants are Biodegradable	•••	0.40 CMD
(iii) Water gets Polluted, Pollutants		
are not Biodegradable & Toxic	•••	0.00 CMD
(iv) Industrial Cooling, spraying	•	oloc omp
in mine pits or boiler feed		0.50CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to

SRO Navi Mumbai 1/I/R/S/41777000

(i)

Control Equipment: Industry shall provide filter bag house dust collector of sufficient capacity to control the emissions. a. Standards for Emissions of Air Pollutants: (i) SPM/TPM Not to exceed 150 mg/Nm3 (ii) SO2 Not to exceedkg/day Standards for Stack Emissions: (i) The applicant shall observe the following fuel pattern:- Standards for Stack Emissions: (ii) The applicant shall observe the following fuel pattern:- Iii Coal 90.00 Kg/Hr. (ii) The applicant shall erect the chimney(s) of the following specifications:- Standards for Inspection to/and for use of the Board's Staff. The chimney(s) we attached to various sources of emission shall be designated by numbers attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officing to less than 75 dB(A) during day time and 70 dB(A) during night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions (vi) Other Conditions
 a. Januards for Emissions of Air Pollutants: SPM/TPM Not to exceed SO2 Not to exceed So2 Not to exceed Standards for Stack Emissions: (i) SO2 Not to exceed
(i) SPM/TPM Not to exceed 150 ng/Nm3 (ii) SO2 Not to exceed
(ii) SO2 Not to exceed
Standards for Stack Emissions: (i) The applicant shall observe the following fuel pattern:- Standards for Stack Emissions: (ii) The applicant shall erect the chimney(s) of the following specifications:- (ii) The applicant shall erect the chimney(s) of the following specifications:- III Colligned (1) (iii) The applicant shall provide ports in the chimney(s) and facilities such as ladder, platform etc. for monitoring the airemissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect official to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Berliaerit
Str. No. Unit Offend Out 1. Coal 50.00 Kg/Hr. (ii) The applicant shall erect the chimney(s) of the following specifications:- Interchine Muss Str. No. Climmev Attacheret 400 Interchine Muss 1. Furnace 30.00 (iii) The applicant shall provide ports in the chimney (s) and facilities such as ladder, platform etc. for monitoring the air-emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officing to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is veckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Bernhausty.
Str. No. Unit Offend Out 1. Coal 50.00 Kg/Hr. (ii) The applicant shall erect the chimney(s) of the following specifications:- Interchine Muss Str. No. Climmev Attacheret 400 Interchine Muss 1. Furnace 30.00 (iii) The applicant shall provide ports in the chimney (s) and facilities such as ladder, platform etc. for monitoring the air-emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officing to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is veckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Bernhausty.
I. Coal Gate and the state of the s
 (ii) The applicant shall erect the chimney(s) of the following specifications:- Se Nor Communicy Autochect Ho. Herein Mark (ii) The applicant shall provide ports in the chimney(s) and facilities such as ladder, platform etc. for monitoring the air-emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take-adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officiate to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: (vi) Other Conditions: (vi) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Brenditer in the premise is reckoned in the premise is reckoned in the premise is reckoned in the premise in the start of the start is a surrounding area.
 specifications:- SENC Chumney Attachad 200 Heidham Mars Furnace 30.00 (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air-emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officiate to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time isyeckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: (vi) Other Conditions (vi) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Bernlarky
Ste No. Centimese Attacking the air emission 1. Furnace 30.00 (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officiate to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is weekoned between 10 p.m. and 6 a.m. (vi) Other Conditions: 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Berulated
Image: Inductor for the second sec
Image: Inductor for the second sec
 (iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officiate to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: (vi) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Repulsation
 open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect offnoise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Berularty
 open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect offnoise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Berularty
 open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect offnoise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Berularty
 (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officiate to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Begulariy
 such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification. (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect officies to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Begularity
 (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Bernlariy
 (iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Bepularity
 standard in respect officise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Bernlariy
 standard in respect officise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Bernlariy
 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions. 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Repularity
 p.m. and night time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m. (vi) Other Conditions: The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality
 (vi) Other Conditions: 1) The industry should not cause any nuisance in surrounding area. 2) The industry should monitor stack emissions and ambient air quality Repularity
 The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Repularly
 The industry should not cause any nuisance in surrounding area. The industry should monitor stack emissions and ambient air quality Repularly
Repularly
Regularly.
6. CONDITIONS UNDER HAZARDOUS WASTE (MANAGEMENT, HANDLING & TRANSBOUNDRY MOVEMENT) BILLES 2008.
(i) The Industry shall handle hazardous wastes as specified below.
SIN NOT INVOLTION
311 - Dooidana 31 Ion
wastes waste
1. The authorization is hereby granted to operate a facility for collection, storage, transport & disposal of basendo
2. The industry should comply with the conditions of E –Waste (M&H) Rules, 2011.
a. Whenever due to any accident or other unforeseen act or even, such emissions occur or is approhended to
$\gamma = \gamma =$
3

Explosives, Inspectorate of Factories and Local Body. In case of failure of pollution control equipments, the production process connected to it shall be stopped.

- b. Industry shall obtain renewal of registration from MPCB as E-Waste dismantler by using environmentally sound technology as per the provisions of the Rule11 of the E-Waste (M&H) Rules, 2011.
- c. The unit has to display and maintain the data online outside the factory main gate in Marathi & English both on a 6'x4' display board in the manner and the report of the compliance along with photograph shall be submitted to this office & concerned Regional Office/ Sub Regional Office.
- d. It shall be ensured that the Hazardous waste is handled, managed & disposed of strictly in accordance with the Hazardous Waste (Management & Handling) Rules, 1989 as amended on 2008 and shown & submitted to the Board as & when asked for.
- 7. Specific Conditions for storage, Handling and Disposal of Waste from Electrical & Electronic equipment (WEEE):
- i) Collection of WEEE -

The applicant must provide appropriate and dedicated vehicles duly identified as per the norms for transportation of Hazardous Waste. The applicant shall obtain all the required permits for transportation of WEEE from competent authority. The applicant shall ensure the safe transport of the WEEE without any spillage during transportation.

Storage for disassembled parts: The applicant must provide appropriate storage for disassembled spare parts from WEEE. Some spare parts (e.g. motors and compressors) will contain oil and/or other fluids. Such part must be appropriately segregated and stored in containers that are secured such that oil and other fluids cannot escape from them. These containers must be stored on an area with an area with an impermeable surface and a sealed drainage system.

ii) Storage for other components and residues:_

Other components and residues arising from the treatment of WEEE will need to be contained following their removal for disposal or recovery. Where they contain hazardous substances they should be stored on impermeable surface and in appropriate containers or bays with weatherproof covering. Containers should be clearly labeled to identify their contents and must be secured so that liquids, including rain water cannot enter them. Components should be segregated having regard to heir eventual destinations and the compatibility of the component types. All batteries should be handled and stored having regard to the potential fire risk associated with team

iii) Balances :-

WEEE Guidelines also requires that sites for handling of WEEE have "balances to measure the weight of the segregated waste'. The objective is to ensure that a record of weights can be maintained of WEEE entering a facility and components and materials leaving each site (together with their destinations). The nature of the weighing equipment should be appropriate for the type and quantity of WEEE being processed.

- iv) Plastic. which cannot be recycled and is hazardous in nature, is recommended to be land filled in nearby CHWTSDF.
- vi) Ferrous and non ferrous metal recycling facilities fall under the purview of existing environmental regulations for air, water, noise, land and soil

SRO Navi Mambar F/08/S/41777060

pollution and generation of hazardous waste and the same should be

 v) CFCS should be either reused or incinerated in common hazardous waste Incineration facilities at CHWTSDF.
 viii) Wasto Oil about the state of the

- viii) Waste Oil should be either reused or incinerated in common hazardous
 waste incineration facilities.
 ix) PCB's containing and the state of the
- ix) PCB's containing capacitors shall be incinerated in common hazardous waste incineration facilities at CHWTSDF.
 x) Mercury recovery and has a common hazardous a common haz
- x) Mercury recovery and lead recycling facilities from batteries fall under the existing environmental regulations for air; water; noise, land and soil pollution and generation of hazardous waste and the same should be followed. In case Mercury or lead recovery is very low, they can be temporarily stored at e-waste dismantling facility and later disposed in TSDF.

8. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste The non hazardous solid wasterarising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.

vin The applicant shall make an application for renewal of the consent at least 60 days before the date of the expiry of the consent.

- viii. The firm shall submit to this office, the 30th day of September every year, the Environmental Statement Report for the financial year ending 31st March in the prescribed Form-V as pre the provisions of rule 14 of the Environment (Protection) (Second Amendment) Rules, 1992.
- ix. Industry shall file annual return in form 3 regarding handling of annual returns to MPC Board on or before 30th June following the financial year to which that return relate.
- x. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.

SRO Navi Mumbai 1/I/R/S/41777000

- x. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- Xi. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xii. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- 9. This Consent shall not be constructed as any exemption for obtaining necessary No Objection Certificate from other Government agencies as may deemed fit necessary.
- 10. The activity of Precious metal recovery from Electrical and Electronic waste does not attract the provisions of EIA notification 2006 and amendment there to. Hence the condition of <u>obtaining Environmental</u> <u>clearance from Competent authority</u> stipulated in Consent to establish granted by MPC Board vide no: BO/MPCB/RO(HQ)/NM/CE/B-106 dated: 18/11/2011 at sr. no 1 ** and at sr no: 14 is here by omitted.
- 11. This Consent is issued with an overriding effect on the earlier consent granted vide no.: BO/MPCB/RO(HQ)/Navi Mumbai/COR/B-87 dated 07/09/2012 valid upto 17/04/2017.
- 12. The Capital investment of the industry is Rs. 9.95 Crs

To,

M/s. Eco friend Industries, A-205, TTC Industrial area, MIDC, Pwane, Navi Mumbai

Copy to:

Regional Officer, MPCB, Navi Mumbai
 Sub-Regional Office, MPCB, Navi Mumbai- I
 Chief Accounts Officer, MPCB, Mumbai.

Received Consent fee of -

STANO.	Amount(Rs.)	DD. No.	- Date	
Tang	25000/-	732382	07/05/2013	HDFC Bank

- SRO Navi Mumbai 17//R/S/41777000

6

027-12-13

(Dr. Y.B|Sontakke) Regional Officer (HQ)